

Introduction to

Ada: Laboratories

Gustavo A. Hoffmann

LEARN.
ADACORE.COM

LEARN.
ADACORE.COM

Introduction to Ada: Laboratories

Release 2025-06

Gustavo A. Hoffmann

Jun 27, 2025

CONTENTS:

1 Imperative language **3**
- 1.1 Hello World . . . 3
- 1.2 Greetings . . . 3
- 1.3 Positive Or Negative . . . 4
- 1.4 Numbers . . . 5

2 Subprograms **7**
- 2.1 Subtract procedure . . . 7
- 2.2 Subtract function . . . 8
- 2.3 Equality function . . . 9
- 2.4 States . . . 10
- 2.5 States #2 . . . 11
- 2.6 States #3 . . . 13
- 2.7 States #4 . . . 14

3 Modular Programming **17**
- 3.1 Months . . . 17
- 3.2 Operations . . . 18

4 Strongly typed language **21**
- 4.1 Colors . . . 21
- 4.2 Integers . . . 23
- 4.3 Temperatures . . . 27

5 Records **31**
- 5.1 Directions . . . 31
- 5.2 Colors . . . 33
- 5.3 Inventory . . . 37

6 Arrays **41**
- 6.1 Constrained Array . . . 41
- 6.2 Colors: Lookup-Table . . . 43
- 6.3 Unconstrained Array . . . 46
- 6.4 Product info . . . 49
- 6.5 String_10 . . . 52
- 6.6 List of Names . . . 54

7 More About Types **59**
- 7.1 Aggregate Initialization . . . 59
- 7.2 Versioning . . . 61
- 7.3 Simple todo list . . . 63
- 7.4 Price list . . . 65

8 Privacy **71**
- 8.1 Directions . . . 71

8.2 Limited Strings . . . 73
8.3 Bonus exercise . . . 77
8.3.1 Colors . . . 77
8.3.2 List of Names . . . 78
8.3.3 Price List . . . 78

9 Generics **79**
9.1 Display Array . . . 79
9.2 Average of Array of Float . . . 81
9.3 Average of Array of Any Type . . . 83
9.4 Generic list . . . 86

10 Exceptions **89**
10.1 Uninitialized Value . . . 89
10.2 Numerical Exception . . . 90
10.3 Re-raising Exceptions . . . 92

11 Tasking **95**
11.1 Display Service . . . 95
11.2 Event Manager . . . 96
11.3 Generic Protected Queue . . . 98

12 Design by contracts **101**
12.1 Price Range . . . 101
12.2 Pythagorean Theorem: Predicate . . . 102
12.3 Pythagorean Theorem: Precondition . . . 104
12.4 Pythagorean Theorem: Postcondition . . . 106
12.5 Pythagorean Theorem: Type Invariant . . . 108
12.6 Primary Color . . . 110

13 Object-oriented programming **115**
13.1 Simple type extension . . . 115
13.2 Online Store . . . 117

14 Standard library: Containers **123**
14.1 Simple todo list . . . 123
14.2 List of unique integers . . . 125

15 Standard library: Dates & Times **129**
15.1 Holocene calendar . . . 129
15.2 List of events . . . 130

16 Standard library: Strings **135**
16.1 Concatenation . . . 135
16.2 List of events . . . 137

17 Standard library: Numerics **141**
17.1 Decibel Factor . . . 141
17.2 Root-Mean-Square . . . 143
17.3 Rotation . . . 145

18 Solutions **151**
18.1 Imperative Language . . . 151
18.1.1 Hello World . . . 151
18.1.2 Greetings . . . 151
18.1.3 Positive Or Negative . . . 151
18.1.4 Numbers . . . 152
18.2 Subprograms . . . 153
18.2.1 Subtract Procedure . . . 153
18.2.2 Subtract Function . . . 154

18.2.3 Equality function . . . 155
18.2.4 States . . . 156
18.2.5 States #2 . . . 157
18.2.6 States #3 . . . 158
18.2.7 States #4 . . . 158
18.3 Modular Programming . . . 159
18.3.1 Months . . . 159
18.3.2 Operations . . . 161
18.4 Strongly typed language . . . 163
18.4.1 Colors . . . 163
18.4.2 Integers . . . 164
18.4.3 Temperatures . . . 167
18.5 Records . . . 170
18.5.1 Directions . . . 170
18.5.2 Colors . . . 171
18.5.3 Inventory . . . 174
18.6 Arrays . . . 176
18.6.1 Constrained Array . . . 176
18.6.2 Colors: Lookup-Table . . . 178
18.6.3 Unconstrained Array . . . 180
18.6.4 Product info . . . 182
18.6.5 String_10 . . . 185
18.6.6 List of Names . . . 186
18.7 More About Types . . . 189
18.7.1 Aggregate Initialization . . . 189
18.7.2 Versioning . . . 191
18.7.3 Simple todo list . . . 192
18.7.4 Price list . . . 194
18.8 Privacy . . . 196
18.8.1 Directions . . . 196
18.8.2 Limited Strings . . . 198
18.9 Generics . . . 201
18.9.1 Display Array . . . 201
18.9.2 Average of Array of Float . . . 202
18.9.3 Average of Array of Any Type . . . 204
18.9.4 Generic list . . . 206
18.10 Exceptions . . . 208
18.10.1 Uninitialized Value . . . 208
18.10.2 Numerical Exception . . . 209
18.10.3 Re-raising Exceptions . . . 211
18.11 Tasking . . . 213
18.11.1 Display Service . . . 213
18.11.2 Event Manager . . . 214
18.11.3 Generic Protected Queue . . . 216
18.12 Design by contracts . . . 218
18.12.1 Price Range . . . 218
18.12.2 Pythagorean Theorem: Predicate . . . 219
18.12.3 Pythagorean Theorem: Precondition . . . 221
18.12.4 Pythagorean Theorem: Postcondition . . . 223
18.12.5 Pythagorean Theorem: Type Invariant . . . 224
18.12.6 Primary Colors . . . 226
18.13 Object-oriented programming . . . 228
18.13.1 Simple type extension . . . 228
18.13.2 Online Store . . . 230
18.14 Standard library: Containers . . . 233
18.14.1 Simple todo list . . . 233
18.14.2 List of unique integers . . . 234
18.15 Standard library: Dates & Times . . . 236

18.15.1 Holocene calendar . . . 236
18.15.2 List of events . . . 237
18.16 Standard library: Strings . . . 239
18.16.1 Concatenation . . . 239
18.16.2 List of events . . . 241
18.17 Standard library: Numerics . . . 244
18.17.1 Decibel Factor . . . 244
18.17.2 Root-Mean-Square . . . 245
18.17.3 Rotation . . . 248

Copyright © 2019 – 2024, AdaCore

This book is published under a CC BY-SA license, which means that you can copy, redistribute, remix, transform, and build upon the content for any purpose, even commercially, as long as you give appropriate credit, provide a link to the license, and indicate if changes were made. If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original. You can find license details on this page[1]



These labs contain exercises for the Introduction to Ada course.

This document was written by Gustavo A. Hoffmann and reviewed by Michael Frank.

Note

The code examples in this course use an 80-column limit, which is a typical limit for Ada code. Note that, on devices with a small screen size, some code examples might be difficult to read.

[1] http://creativecommons.org/licenses/by-sa/4.0

CHAPTER

ONE

IMPERATIVE LANGUAGE

For the exercises below (except for the first one), don't worry about the details of the `Main` procedure. You should just focus on implementing the application in the subprogram specified by the exercise.

1.1 Hello World

Goal: create a "Hello World!" application.

Steps:

1. Complete the `Main` procedure.

Requirements:

1. The application must display the message "Hello World!".

Remarks:

1. The part that you have to modify is indicated by the *`-- Implement the application here!`* comment in the source code.

Listing 1: main.adb

```
with Ada.Text_IO; use Ada.Text_IO;

procedure Main is
begin
   --  Implement the application here!
   null;
end Main;
```

1.2 Greetings

Goal: create an application that greets a person.

Steps:

1. Complete the `Greet` procedure.

Requirements:

1. Given an input string <name>, procedure `Greet` must display the message "Hello <name>!".
    1. For example, if the name is "John", it displays the message "Hello John!".

Remarks:

1. You can use the concatenation operator (`&`).

2. The part that you have to modify is indicated by the `-- Implement the application here!` comment in the source code.

Listing 2: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

procedure Main is

   procedure Greet (Name : String) is
   begin
      --  Implement the application here!
      null;
   end Greet;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Greet (Argument (1));
end Main;
```

1.3 Positive Or Negative

Goal: create an application that classifies integer numbers.

Steps:

1. Complete the `Classify_Number` procedure.

Requirements:

1. Given an integer number `X`, procedure `Classify_Number` must classify `X` as positive, negative or zero and display the result:
   1. If `X > 0`, it displays `Positive`.
   2. If `X < 0`, it displays `Negative`.
   3. If `X = 0`, it displays `Zero`.

Listing 3: classify_number.ads

```
procedure Classify_Number (X : Integer);
```

Listing 4: classify_number.adb

```
with Ada.Text_IO; use Ada.Text_IO;

procedure Classify_Number (X : Integer) is
begin
   --  Implement the application here!
   null;
end Classify_Number;
```

Listing 5: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Classify_Number;

procedure Main is
   A : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   A := Integer'Value (Argument (1));

   Classify_Number (A);
end Main;
```

1.4 Numbers

Goal: create an application that displays numbers in a specific order.

Steps:

1. Complete the `Display_Numbers` procedure.

Requirements:

1. Given two integer numbers, `Display_Numbers` displays all numbers in the range starting with the smallest number.

Listing 6: display_numbers.ads

```
procedure Display_Numbers (A, B : Integer);
```

Listing 7: display_numbers.adb

```
procedure Display_Numbers (A, B : Integer) is
begin
   --  Implement the application here!
   null;
end Display_Numbers;
```

Listing 8: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_Numbers;

procedure Main is
   A, B : Integer;
begin
   if Argument_Count < 2 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
```

(continues on next page)

(continued from previous page)

```
12    elsif Argument_Count > 2 then
13       Put_Line ("Ignoring additional arguments...");
14    end if;
15
16    A := Integer'Value (Argument (1));
17    B := Integer'Value (Argument (2));
18
19    Display_Numbers (A, B);
20 end Main;
```

CHAPTER

TWO

SUBPROGRAMS

2.1 Subtract procedure

Goal: write a procedure that subtracts two numbers.

Steps:

1. Complete the procedure `Subtract`.

Requirements:

1. `Subtract` performs the operation `A - B`.

Listing 1: subtract.ads

```
--  Write the correct parameters for the procedure below.
procedure Subtract;
```

Listing 2: subtract.adb

```
procedure Subtract is
begin
   --  Implement the procedure here.
   null;
end Subtract;
```

Listing 3: main.adb

```
with Ada.Command_Line;      use Ada.Command_Line;
with Ada.Text_IO;           use Ada.Text_IO;

with Subtract;

procedure Main is
   type Test_Case_Index is
     (Sub_10_1_Chk,
      Sub_10_100_Chk,
      Sub_0_5_Chk,
      Sub_0_Minus_5_Chk);

   procedure Check (TC : Test_Case_Index) is
      Result : Integer;
   begin
      case TC is
      when Sub_10_1_Chk =>
         Subtract (10, 1, Result);
         Put_Line ("Result: " & Integer'Image (Result));
      when Sub_10_100_Chk =>
         Subtract (10, 100, Result);
```

(continues on next page)

(continued from previous page)

```
         Put_Line ("Result: " & Integer'Image (Result));
      when Sub_0_5_Chk =>
         Subtract (0, 5, Result);
         Put_Line ("Result: " & Integer'Image (Result));
      when Sub_0_Minus_5_Chk =>
         Subtract (0, -5, Result);
         Put_Line ("Result: " & Integer'Image (Result));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

2.2 Subtract function

Goal: write a function that subtracts two numbers.

Steps:

1. Rewrite the `Subtract` procedure from the previous exercise as a function.

Requirements:

1. `Subtract` performs the operation `A - B` and returns the result.

Listing 4: subtract.ads

```
--  Write the correct signature for the function below.
--  Don't forget to replace the keyword "procedure" by "function."
procedure Subtract;
```

Listing 5: subtract.adb

```
procedure Subtract is
begin
   --  Implement the function here!
   null;
end Subtract;
```

Listing 6: main.adb

```
with Ada.Command_Line;     use Ada.Command_Line;
with Ada.Text_IO;          use Ada.Text_IO;

with Subtract;

procedure Main is
   type Test_Case_Index is
     (Sub_10_1_Chk,
      Sub_10_100_Chk,
      Sub_0_5_Chk,
      Sub_0_Minus_5_Chk);
```

(continues on next page)

(continued from previous page)

```
12
13    procedure Check (TC : Test_Case_Index) is
14       Result : Integer;
15    begin
16       case TC is
17       when Sub_10_1_Chk =>
18          Result := Subtract (10, 1);
19          Put_Line ("Result: " & Integer'Image (Result));
20       when Sub_10_100_Chk =>
21          Result := Subtract (10, 100);
22          Put_Line ("Result: " & Integer'Image (Result));
23       when Sub_0_5_Chk =>
24          Result := Subtract (0, 5);
25          Put_Line ("Result: " & Integer'Image (Result));
26       when Sub_0_Minus_5_Chk =>
27          Result := Subtract (0, -5);
28          Put_Line ("Result: " & Integer'Image (Result));
29       end case;
30    end Check;
31
32 begin
33    if Argument_Count < 1 then
34       Put_Line ("ERROR: missing arguments! Exiting...");
35       return;
36    elsif Argument_Count > 1 then
37       Put_Line ("Ignoring additional arguments...");
38    end if;
39
40    Check (Test_Case_Index'Value (Argument (1)));
41 end Main;
```

2.3 Equality function

Goal: write a function that compares two values and returns a flag.

Steps:

1. Complete the `Is_Equal` subprogram.

Requirements:

1. `Is_Equal` returns a flag as a **`Boolean`** value.
2. The flag must indicate whether the values are equal (flag is **`True`**) or not (flag is **`False`**).

Listing 7: is_equal.ads

```
1 --  Write the correct signature for the function below.
2 --  Don't forget to replace the keyword "procedure" by "function."
3 procedure Is_Equal;
```

Listing 8: is_equal.adb

```
1 procedure Is_Equal is
2 begin
3    --  Implement the function here!
4    null;
5 end Is_Equal;
```

Listing 9: main.adb

```
with Ada.Command_Line;     use Ada.Command_Line;
with Ada.Text_IO;          use Ada.Text_IO;

with Is_Equal;

procedure Main is
   type Test_Case_Index is
     (Equal_Chk,
      Inequal_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Display_Equal (A, B  : Integer;
                               Equal : Boolean) is
      begin
         Put (Integer'Image (A));
         if Equal then
            Put (" is equal to ");
         else
            Put (" isn't equal to ");
         end if;
         Put_Line (Integer'Image (B) & ".");
      end Display_Equal;

      Result : Boolean;
   begin
      case TC is
      when Equal_Chk =>
         for I in 0 .. 10 loop
            Result := Is_Equal (I, I);
            Display_Equal (I, I, Result);
         end loop;
      when Inequal_Chk =>
         for I in 0 .. 10 loop
            Result := Is_Equal (I, I - 1);
            Display_Equal (I, I - 1, Result);
         end loop;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

2.4 States

Goal: write a procedure that displays the state of a machine.

Steps:

1. Complete the procedure `Display_State`.

Requirements:

1. The states can be set according to the following numbers:

Number	State
0	Off
1	On: Simple Processing
2	On: Advanced Processing

2. The procedure `Display_State` receives the number corresponding to a state and displays the state (indicated by the table above) as a user message.

Remarks:

1. You can use a case statement to implement this procedure.

Listing 10: display_state.ads

```
procedure Display_State (State : Integer);
```

Listing 11: display_state.adb

```
with Ada.Text_IO; use Ada.Text_IO;

procedure Display_State (State : Integer) is
begin
   null;
end Display_State;
```

Listing 12: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_State;

procedure Main is
   State : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   State := Integer'Value (Argument (1));

   Display_State (State);
end Main;
```

2.5 States #2

Goal: write a function that returns the state of a machine.

Steps:

1. Implement the function `Get_State`.

Requirements:

1. Implement same state machine as in the previous exercise.
2. Function `Get_State` must return the state as a string.

Remarks:

1. You can implement a function returning a string by simply using quotes in a return statement. For example:

Listing 13: get_hello.ads

```
function Get_Hello return String;
```

Listing 14: get_hello.adb

```
function Get_Hello return String is
begin
   return "Hello";
end Get_Hello;
```

Listing 15: main.adb

```
with Ada.Text_IO;      use Ada.Text_IO;
with Get_Hello;

procedure Main is
   S : constant String := Get_Hello;
begin
   Put_Line (S);
end Main;
```

2. You can reuse your previous implementation and replace it by a case expression.
    1. For values that do not correspond to a state, you can simply return an empty string ("").

Listing 16: get_state.ads

```
function Get_State (State : Integer) return String;
```

Listing 17: get_state.adb

```
function Get_State (State : Integer) return String is
begin
   return "";
end Get_State;
```

Listing 18: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Get_State;

procedure Main is
   State : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
```

(continues on next page)

(continued from previous page)

```
14    end if;
15
16    State := Integer'Value (Argument (1));
17
18    Put_Line (Get_State (State));
19 end Main;
```

2.6 States #3

Goal: implement an on/off indicator for a state machine.

Steps:

1. Implement the function `Is_On`.
2. Implement the procedure `Display_On_Off`.

Requirements:

1. Implement same state machine as in the previous exercise.
2. Function `Is_On` returns:
   - `True` if the machine is on;
   - otherwise, it returns `False`.
3. Procedure `Display_On_Off` displays the message
   - "On" if the machine is on, or
   - "Off" otherwise.
4. `Is_On` must be called in the implementation of `Display_On_Off`.

Remarks:

1. You can implement both subprograms using if expressions.

Listing 19: is_on.ads

```
1 function Is_On (State : Integer) return Boolean;
```

Listing 20: is_on.adb

```
1 function Is_On (State : Integer) return Boolean is
2 begin
3    return False;
4 end Is_On;
```

Listing 21: display_on_off.ads

```
1 procedure Display_On_Off (State : Integer);
```

Listing 22: display_on_off.adb

```
1 with Ada.Text_IO; use Ada.Text_IO;
2 with Is_On;
3
4 procedure Display_On_Off (State : Integer) is
5 begin
6    Put_Line ("");
7 end Display_On_Off;
```

Listing 23: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_On_Off;
with Is_On;

procedure Main is
   State : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   State := Integer'Value (Argument (1));

   Display_On_Off (State);
   Put_Line (Boolean'Image (Is_On (State)));
end Main;
```

2.7 States #4

Goal: implement a procedure to update the state of a machine.

Steps:

1. Implement the procedure `Set_Next`.

Requirements:

1. Implement the same state machine as in the previous exercise.
2. Procedure `Set_Next` updates the machine's state with the next one in a *circular* manner:
   - In general, after a call to `Set_Next` for an integer variable `N` (`Set_Next (N)`), the new value of `N` must be the next number for that variable `N` (i.e., `N := N'Old + 1`).
     - In other words, a call to `Set_Next (N)` has the same effect as `N := N + 1`.
     - For example, after the statements `N := 1; Set_Next (N);`, we have that `N = 2`.
   - However, if the state is the last valid one for the machine (which, for this exercise, it's 2), the next state must be the first valid one (in this case: 0).
     - In other words, for `N := 2; Set_Next (N);`, we have that `N = 0`.

Remarks:

1. You can use an if expression to implement `Set_Next`.

Listing 24: set_next.ads

```
procedure Set_Next (State : in out Integer);
```

Listing 25: set_next.adb

```
procedure Set_Next (State : in out Integer) is
begin
   null;
end Set_Next;
```

Listing 26: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Set_Next;

procedure Main is
   State : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   State := Integer'Value (Argument (1));

   Set_Next (State);
   Put_Line (Integer'Image (State));
end Main;
```

CHAPTER

THREE

MODULAR PROGRAMMING

3.1 Months

Goal: create a package to display the months of the year.

Steps:

1. Convert the `Months` procedure below to a package.
2. Create the specification and body of the `Months` package.

Requirements:

1. `Months` must contain the declaration of strings for each month of the year, which are stored in three-character constants based on the month's name.
    - For example, the string `"January"` is stored in the constant `Jan`. These strings are then used by the `Display_Months` procedure, which is also part of the `Months` package.

Remarks:

1. The goal of this exercise is to create the `Months` package.
    1. In the code below, `Months` is declared as a procedure.
        - Therefore, we need to *convert* it into a real package.
    2. You have to modify the procedure declaration and implementation in the code below, so that it becomes a package specification and a package body.

Listing 1: months.ads

```
--  Create specification for Months package, which includes
--  the declaration of the Display_Months procedure.
--
procedure Months;
```

Listing 2: months.adb

```
--  Create body of Months package, which includes
--  the implementation of the Display_Months procedure.
--
procedure Months is

   procedure Display_Months is
   begin
      Put_Line ("Months:");
      Put_Line ("- " & Jan);
      Put_Line ("- " & Feb);
      Put_Line ("- " & Mar);
      Put_Line ("- " & Apr);
```

(continues on next page)

(continued from previous page)

```
      Put_Line ("- " & May);
      Put_Line ("- " & Jun);
      Put_Line ("- " & Jul);
      Put_Line ("- " & Aug);
      Put_Line ("- " & Sep);
      Put_Line ("- " & Oct);
      Put_Line ("- " & Nov);
      Put_Line ("- " & Dec);
   end Display_Months;

begin
   null;
end Months;
```

Listing 3: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Months;           use Months;

procedure Main is

   type Test_Case_Index is
     (Months_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Months_Chk =>
            Display_Months;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

3.2 Operations

Goal: create a package to perform basic mathematical operations.

Steps:

1. Implement the `Operations` package.
    1. Declare and implement the `Add` function.
    2. Declare and implement the `Subtract` function.
    3. Declare and implement the `Multiply`: function.
    4. Declare and implement the `Divide` function.
2. Implement the `Operations.Test` package

1. Declare and implement the `Display` procedure.

Requirements:

1. Package `Operations` contains functions for each of the four basic mathematical operations for parameters of **`Integer`** type:
    1. Function `Add` performs the addition of `A` and `B` and returns the result;
    2. Function `Subtract` performs the subtraction of `A` and `B` and returns the result;
    3. Function `Multiply` performs the multiplication of `A` and `B` and returns the result;
    4. Function `Divide` performs the division of `A` and `B` and returns the result.
2. Package `Operations.Test` contains the test environment:
    1. Procedure `Display` must use the functions from the parent (`Operations`) package as indicated by the template in the code below.

Listing 4: operations.ads

```
package Operations is

   --  Create specification for Operations package, including the
   --  declaration of the functions mentioned above.
   --

end Operations;
```

Listing 5: operations.adb

```
package body Operations is

   --  Create body of Operations package.
   --

end Operations;
```

Listing 6: operations-test.ads

```
package Operations.Test is

   --  Create specification for Operations package, including the
   --  declaration of the Display procedure:
   --
   --   procedure Display (A, B : Integer);
   --

end Operations.Test;
```

Listing 7: operations-test.adb

```
package body Operations.Test is

   --  Implement body of Operations.Test package.
   --

   procedure Display (A, B : Integer) is
      A_Str : constant String := Integer'Image (A);
      B_Str : constant String := Integer'Image (B);
   begin
      Put_Line ("Operations:");
      Put_Line (A_Str & " + " & B_Str & " = "
```

(continues on next page)

(continued from previous page)

```
                & Integer'Image (Add (A, B))
                & ",");
      --  Use the line above as a template and add the rest of the
      --  implementation for Subtract, Multiply and Divide.
   end Display;

end Operations.Test;
```

Listing 8: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Operations;
with Operations.Test;  use Operations.Test;

procedure Main is

   type Test_Case_Index is
     (Operations_Chk,
      Operations_Display_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Operations_Chk =>
            Put_Line ("Add (100, 2) = "
                      & Integer'Image (Operations.Add (100, 2)));
            Put_Line ("Subtract (100, 2) = "
                      & Integer'Image (Operations.Subtract (100, 2)));
            Put_Line ("Multiply (100, 2) = "
                      & Integer'Image (Operations.Multiply (100, 2)));
            Put_Line ("Divide (100, 2) = "
                      & Integer'Image (Operations.Divide (100, 2)));
         when Operations_Display_Chk =>
            Display (10, 5);
            Display ( 1, 2);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

CHAPTER

FOUR

STRONGLY TYPED LANGUAGE

4.1 Colors

Goal: create a package to represent HTML colors in hexadecimal form and its corresponding names.

Steps:

1. Implement the `Color_Types` package.
    1. Declare the `HTML_Color` enumeration.
    2. Declare the `Basic_HTML_Color` enumeration.
    3. Implement the `To_Integer` function.
    4. Implement the `To_HTML_Color` function.

Requirements:

1. Enumeration `HTML_Color` has the following colors:
    - Salmon
    - Firebrick
    - Red
    - Darkred
    - Lime
    - Forestgreen
    - Green
    - Darkgreen
    - Blue
    - Mediumblue
    - Darkblue
2. Enumeration `Basic_HTML_Color` has the following colors: Red, Green, Blue.
3. Function `To_Integer` converts from the `HTML_Color` type to the HTML color code — as integer values in hexadecimal notation.
    - You can find the HTML color codes in the table below.
4. Function `To_HTML_Color` converts from `Basic_HTML_Color` to `HTML_Color`.
5. This is the table to convert from an HTML color to a HTML color code in hexadecimal notation:

Color	HTML color code (hexa)
Salmon	#FA8072
Firebrick	#B22222
Red	#FF0000
Darkred	#8B0000
Lime	#00FF00
Forestgreen	#228B22
Green	#008000
Darkgreen	#006400
Blue	#0000FF
Mediumblue	#0000CD
Darkblue	#00008B

Remarks:

1. In order to express the hexadecimal values above in Ada, use the following syntax: 16#<hex_value># (e.g.: `16#FFFFFF#`).
2. For function `To_Integer`, you may use a **`case`** for this.

Listing 1: color_types.ads

```
package Color_Types is

   --  Include type declaration for HTML_Color!
   --
   --  type HTML_Color is [...]
   --

   --  Include function declaration for:
   --  function To_Integer (C : HTML_Color) return Integer;

   --  Include type declaration for Basic_HTML_Color!
   --
   --  type Basic_HTML_Color is [...]
   --

   --  Include function declaration for:
   --  - Basic_HTML_Color => HTML_Color
   --
   --  function To_HTML_Color [...];
   --
end Color_Types;
```

Listing 2: color_types.adb

```
package body Color_Types is

   --  Implement the conversion from HTML_Color to Integer here!
   --
   --  function To_Integer (C : HTML_Color) return Integer is
   --  begin
   --  --  Hint: use 'case' for the HTML colors;
   --  --        use 16#...# for the hexadecimal values.
   --  end To_Integer;

   --  Implement the conversion from Basic_HTML_Color to HTML_Color here!
   --
   --  function To_HTML_Color [...] is
```

(continues on next page)

(continued from previous page)

```
   --
end Color_Types;
```

Listing 3: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;
with Ada.Integer_Text_IO;

with Color_Types; use Color_Types;

procedure Main is
   type Test_Case_Index is
     (HTML_Color_Range,
      HTML_Color_To_Integer,
      Basic_HTML_Color_To_HTML_Color);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when HTML_Color_Range =>
            for I in HTML_Color'Range loop
               Put_Line (HTML_Color'Image (I));
            end loop;
         when HTML_Color_To_Integer =>
            for I in HTML_Color'Range loop
               Ada.Integer_Text_IO.Put (Item  => To_Integer (I),
                                        Width => 6,
                                        Base  => 16);
               New_Line;
            end loop;
         when Basic_HTML_Color_To_HTML_Color =>
            for I in Basic_HTML_Color'Range loop
               Put_Line (HTML_Color'Image (To_HTML_Color (I)));
            end loop;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

4.2 Integers

Goal: implement a package with various integer types.

Steps:

1. Implement the `Int_Types` package.
    1. Declare the integer type `I_100`.
    2. Declare the modular type `U_100`.

3. Implement the `To_I_100` function to convert from the `U_100` type.
4. Implement the `To_U_100` function to convert from the `I_100` type.
5. Declare the derived type `D_50`.
6. Declare the subtype `S_50`.
7. Implement the `To_D_50` function to convert from the `I_100` type.
8. Implement the `To_S_50` function to convert from the `I_100` type.
9. Implement the `To_I_100` function to convert from the `D_50` type.

Requirements:

1. Types `I_100` and `U_100` have values between 0 and 100.
    1. Type `I_100` is an integer type.
    2. Type `U_100` is a modular type.
2. Function `To_I_100` converts from the `U_100` type to the `I_100` type.
3. Function `To_U_100` converts from the `I_100` type to the `U_100` type.
4. Types `D_50` and `S_50` have values between 10 and 50 and use `I_100` as a base type.
    1. `D_50` is a derived type.
    2. `S_50` is a subtype.
5. Function `To_D_50` converts from the `I_100` type to the `D_50` type.
6. Function `To_S_50` converts from the `I_100` type to the `S_50` type.
7. Functions `To_D_50` and `To_S_50` saturate the input values if they are out of range.
    - If the input is less than 10 the output should be 10.
    - If the input is greater than 50 the output should be 50.
8. Function `To_I_100` converts from the `D_50` type to the `I_100` type.

Remarks:

1. For the implementation of functions `To_D_50` and `To_S_50`, you may use the type attributes `D_50'First` and `D_50'Last`:
    1. `D_50'First` indicates the minimum value of the `D_50` type.
    2. `D_50'Last` indicates the maximum value of the `D_50` type.
    3. The same attributes are available for the `S_50` type (`S_50'First` and `S_50'Last`).
2. We could have implemented a function `To_I_100` as well to convert from `S_50` to `I_100`. However, we skip this here because explicit conversions are not needed for subtypes.

Listing 4: int_types.ads

```
1  package Int_Types is
2
3     --  Include type declarations for I_100 and U_100!
4     --
5     --  type I_100 is [...]
6     --  type U_100 is [...]
7     --
8
9     function To_I_100 (V : U_100) return I_100;
10
11    function To_U_100 (V : I_100) return U_100;
```

(continues on next page)

(continued from previous page)

```
12
13    --  Include type declarations for D_50 and S_50!
14    --
15    --  [...] D_50 is [...]
16    --  [...] S_50 is [...]
17    --
18
19    function To_D_50 (V : I_100) return D_50;
20
21    function To_S_50 (V : I_100) return S_50;
22
23    function To_I_100 (V : D_50) return I_100;
24
25 end Int_Types;
```

Listing 5: int_types.adb

```
1  package body Int_Types is
2
3     function To_I_100 (V : U_100) return I_100 is
4     begin
5        --  Implement the conversion from U_100 to I_100 here!
6        --
7        null;
8     end To_I_100;
9
10    function To_U_100 (V : I_100) return U_100 is
11    begin
12       --  Implement the conversion from I_100 to U_100 here!
13       --
14       null;
15    end To_U_100;
16
17    function To_D_50 (V : I_100) return D_50 is
18       Min : constant I_100 := I_100 (D_50'First);
19       Max : constant I_100 := I_100 (D_50'Last);
20    begin
21       --  Implement the conversion from I_100 to D_50 here!
22       --
23       --  Hint: using the constants above simplifies the checks needed for
24       --        this function.
25       --
26       null;
27    end To_D_50;
28
29    function To_S_50 (V : I_100) return S_50 is
30    begin
31       --  Implement the conversion from I_100 to S_50 here!
32       --
33       --  Remark: don't forget to verify whether an explicit conversion like
34       --          S_50 (V) is needed.
35       --
36       null;
37    end To_S_50;
38
39    function To_I_100 (V : D_50) return I_100 is
40    begin
41       --  Implement the conversion from I_100 to D_50 here!
42       --
43       --  Remark: don't forget to verify whether an explicit conversion like
44       --          I_100 (V) is needed.
```

(continues on next page)

(continued from previous page)

```
      --
      null;
   end To_I_100;

end Int_Types;
```

Listing 6: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Int_Types;        use Int_Types;

procedure Main is
   package I_100_IO is new Ada.Text_IO.Integer_IO (I_100);
   package U_100_IO is new Ada.Text_IO.Modular_IO (U_100);
   package D_50_IO  is new Ada.Text_IO.Integer_IO (D_50);

   use I_100_IO;
   use U_100_IO;
   use D_50_IO;

   type Test_Case_Index is
     (I_100_Range,
      U_100_Range,
      U_100_Wraparound,
      U_100_To_I_100,
      I_100_To_U_100,
      D_50_Range,
      S_50_Range,
      I_100_To_D_50,
      I_100_To_S_50,
      D_50_To_I_100,
      S_50_To_I_100);

   procedure Check (TC : Test_Case_Index) is
   begin
      I_100_IO.Default_Width := 1;
      U_100_IO.Default_Width := 1;
      D_50_IO.Default_Width  := 1;

      case TC is
         when I_100_Range =>
            Put (I_100'First);
            New_Line;
            Put (I_100'Last);
            New_Line;
         when U_100_Range =>
            Put (U_100'First);
            New_Line;
            Put (U_100'Last);
            New_Line;
         when U_100_Wraparound =>
            Put (U_100'First - 1);
            New_Line;
            Put (U_100'Last + 1);
            New_Line;
         when U_100_To_I_100 =>
            for I in U_100'Range loop
               I_100_IO.Put (To_I_100 (I));
               New_Line;
```

(continues on next page)

(continued from previous page)

```
54             end loop;
55          when I_100_To_U_100 =>
56             for I in I_100'Range loop
57                Put (To_U_100 (I));
58                New_Line;
59             end loop;
60          when D_50_Range =>
61             Put (D_50'First);
62             New_Line;
63             Put (D_50'Last);
64             New_Line;
65          when S_50_Range =>
66             Put (S_50'First);
67             New_Line;
68             Put (S_50'Last);
69             New_Line;
70          when I_100_To_D_50 =>
71             for I in I_100'Range loop
72                Put (To_D_50 (I));
73                New_Line;
74             end loop;
75          when I_100_To_S_50 =>
76             for I in I_100'Range loop
77                Put (To_S_50 (I));
78                New_Line;
79             end loop;
80          when D_50_To_I_100 =>
81             for I in D_50'Range loop
82                Put (To_I_100 (I));
83                New_Line;
84             end loop;
85          when S_50_To_I_100 =>
86             for I in S_50'Range loop
87                Put (I);
88                New_Line;
89             end loop;
90       end case;
91    end Check;
92
93 begin
94    if Argument_Count < 1 then
95       Put_Line ("ERROR: missing arguments! Exiting...");
96       return;
97    elsif Argument_Count > 1 then
98       Put_Line ("Ignoring additional arguments...");
99    end if;
100
101   Check (Test_Case_Index'Value (Argument (1)));
102 end Main;
```

4.3 Temperatures

Goal: create a package to handle temperatures in Celsius and Kelvin.

Steps:

1. Implement the `Temperature_Types` package.
    1. Declare the `Celsius` type.
    2. Declare the `Int_Celsius` type.

3. Implement the `To_Celsius` function.
4. Implement the `To_Int_Celsius` function.
5. Declare the `Kelvin` type.
6. Implement the `To_Celsius` function to convert from the `Kelvin` type.
7. Implement the `To_Kelvin` function.

Requirements:

1. The custom floating-point types declared in `Temperature_Types` must use a precision of six digits.
2. Types `Celsius` and `Int_Celsius` are used for temperatures in Celsius:
   1. `Celsius` is a floating-point type with a range between -273.15 and 5504.85.
   2. `Int_Celsius` is an integer type with a range between -273 and 5505.
3. Functions `To_Celsius` and `To_Int_Celsius` are used for type conversion:
   1. `To_Celsius` converts from `Int_Celsius` to `Celsius` type.
   2. `To_Int_Celsius` converts from `Celsius` and `Int_Celsius` types:
4. `Kelvin` is a floating-point type for temperatures in Kelvin using a range between 0.0 and 5778.0.
5. The functions `To_Celsius` and `To_Kelvin` are used to convert between temperatures in `Kelvin` and `Celsius`.
   1. In order to convert temperatures in Celsius to Kelvin, you must use the formula $K = C + 273.15$, where:
      - *K* is the temperature in Kelvin, and
      - *C* is the temperature in Celsius.

Remarks:

1. When implementing the `To_Celsius` function for the `Int_Celsius` type:
   1. You'll need to check for the minimum and maximum values of the input values because of the slightly different ranges.
   2. You may use variables of floating-point type (**`Float`**) for intermediate values.
2. For the implementation of the functions `To_Celsius` and `To_Kelvin` (used for converting between `Kelvin` and `Celsius`), you may use a variable of floating-point type (**`Float`**) for intermediate values.

Listing 7: temperature_types.ads

```
package Temperature_Types is

   --  Include type declaration for Celsius!
   --
   --  Celsius is [...];
       --  Int_Celsius is [...];
   --

   function To_Celsius (T : Int_Celsius) return Celsius;

   function To_Int_Celsius (T : Celsius) return Int_Celsius;

   --  Include type declaration for Kelvin!
   --
   --  type Kelvin is [...];
```

(continues on next page)

(continued from previous page)

```
   --
end Temperature_Types;
```

Listing 8: temperature_types.adb

```
package body Temperature_Types is

   function To_Celsius (T : Int_Celsius) return Celsius is
   begin
      null;
   end To_Celsius;

   function To_Int_Celsius (T : Celsius) return Int_Celsius is
   begin
      null;
   end To_Int_Celsius;

   --  Include function implementation for:
   --  - Kelvin  => Celsius
   --  - Celsius => Kelvin
   --
   --  function To_Celsius [...] is
   --  function To_Kelvin  [...] is
   --
end Temperature_Types;
```

Listing 9: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Temperature_Types; use Temperature_Types;

procedure Main is
   package Celsius_IO     is new Ada.Text_IO.Float_IO (Celsius);
   package Kelvin_IO      is new Ada.Text_IO.Float_IO (Kelvin);
   package Int_Celsius_IO is new Ada.Text_IO.Integer_IO (Int_Celsius);

   use Celsius_IO;
   use Kelvin_IO;
   use Int_Celsius_IO;

   type Test_Case_Index is
     (Celsius_Range,
      Celsius_To_Int_Celsius,
      Int_Celsius_To_Celsius,
      Kelvin_To_Celsius,
      Celsius_To_Kelvin);

   procedure Check (TC : Test_Case_Index) is
   begin
      Celsius_IO.Default_Fore := 1;
```

(continues on next page)

(continued from previous page)

```
25       Kelvin_IO.Default_Fore  := 1;
26       Int_Celsius_IO.Default_Width := 1;
27
28       case TC is
29          when Celsius_Range =>
30             Put (Celsius'First);
31             New_Line;
32             Put (Celsius'Last);
33             New_Line;
34          when Celsius_To_Int_Celsius =>
35             Put (To_Int_Celsius (Celsius'First));
36             New_Line;
37             Put (To_Int_Celsius (0.0));
38             New_Line;
39             Put (To_Int_Celsius (Celsius'Last));
40             New_Line;
41          when Int_Celsius_To_Celsius =>
42             Put (To_Celsius (Int_Celsius'First));
43             New_Line;
44             Put (To_Celsius (0));
45             New_Line;
46             Put (To_Celsius (Int_Celsius'Last));
47             New_Line;
48          when Kelvin_To_Celsius =>
49             Put (To_Celsius (Kelvin'First));
50             New_Line;
51             Put (To_Celsius (0));
52             New_Line;
53             Put (To_Celsius (Kelvin'Last));
54             New_Line;
55          when Celsius_To_Kelvin =>
56             Put (To_Kelvin (Celsius'First));
57             New_Line;
58             Put (To_Kelvin (Celsius'Last));
59             New_Line;
60       end case;
61    end Check;
62
63 begin
64    if Argument_Count < 1 then
65       Put_Line ("ERROR: missing arguments! Exiting...");
66       return;
67    elsif Argument_Count > 1 then
68       Put_Line ("Ignoring additional arguments...");
69    end if;
70
71    Check (Test_Case_Index'Value (Argument (1)));
72 end Main;
```

CHAPTER

FIVE

RECORDS

5.1 Directions

Goal: create a package that handles directions and geometric angles.

Steps:

1. Implement the `Directions` package.
    1. Declare the `Ext_Angle` record.
    2. Implement the `Display` procedure.
    3. Implement the `To_Ext_Angle` function.

Requirements:

1. Record `Ext_Angle` stores information about the extended angle (see remark about *extended angles* below).
2. Procedure `Display` displays information about the extended angle.
    1. You should use the implementation that has been commented out (see code below) as a starting point.
3. Function `To_Ext_Angle` converts a simple angle value to an extended angle (`Ext_Angle` type).

Remarks:

1. We make use of the algorithm implemented in the `Check_Direction` procedure (chapter on imperative language).
2. For the sake of this exercise, we use the concept of *extended angles*. This includes the actual geometric angle and the corresponding direction (North, South, Northwest, and so on).

Listing 1: directions.ads

```
1  package Directions is
2
3     type Angle_Mod is mod 360;
4
5     type Direction is
6       (North,
7        Northeast,
8        East,
9        Southeast,
10       South,
11       Southwest,
12       West,
13       Northwest);
14
```

(continues on next page)

(continued from previous page)

```
15    function To_Direction (N: Angle_Mod) return Direction;
16
17    --  Include type declaration for Ext_Angle record type:
18    --
19    --  NOTE: Use the Angle_Mod and Direction types declared above!
20    --
21    --  type Ext_Angle is [...]
22    --
23
24    function To_Ext_Angle (N : Angle_Mod) return Ext_Angle;
25
26    procedure Display (N : Ext_Angle);
27
28 end Directions;
```

Listing 2: directions.adb

```
1  with Ada.Text_IO; use Ada.Text_IO;
2
3  package body Directions is
4
5     procedure Display (N : Ext_Angle) is
6     begin
7        --  Uncomment the code below and fill the missing elements
8        --
9        --  Put_Line ("Angle: "
10       --            & Angle_Mod'Image (____)
11       --            & " => "
12       --            & Direction'Image (____)
13       --            & ".");
14       null;
15    end Display;
16
17    function To_Direction (N : Angle_Mod) return Direction is
18    begin
19       case N is
20          when   0        => return North;
21          when   1 ..  89 => return Northeast;
22          when  90        => return East;
23          when  91 .. 179 => return Southeast;
24          when 180        => return South;
25          when 181 .. 269 => return Southwest;
26          when 270        => return West;
27          when 271 .. 359 => return Northwest;
28       end case;
29    end To_Direction;
30
31    function To_Ext_Angle (N : Angle_Mod) return Ext_Angle is
32    begin
33       --  Implement the conversion from Angle_Mod to Ext_Angle here!
34       --
35       --  Hint: you can use a return statement and an aggregate.
36       --
37       null;
38    end To_Ext_Angle;
39
40 end Directions;
```

Listing 3: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Directions;        use Directions;

procedure Main is
   type Test_Case_Index is
     (Direction_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
      when Direction_Chk =>
         Display (To_Ext_Angle (0));
         Display (To_Ext_Angle (30));
         Display (To_Ext_Angle (45));
         Display (To_Ext_Angle (90));
         Display (To_Ext_Angle (91));
         Display (To_Ext_Angle (120));
         Display (To_Ext_Angle (180));
         Display (To_Ext_Angle (250));
         Display (To_Ext_Angle (270));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

5.2 Colors

Goal: create a package to represent HTML colors in RGB format using the hexadecimal form.

Steps:

1. Implement the `Color_Types` package.
    1. Declare the RGB record.
    2. Implement the `To_RGB` function.
    3. Implement the `Image` function for the RGB type.

Requirements:

1. The following table contains the HTML colors and the corresponding value in hexadecimal form for each color element:

Color	Red	Green	Blue
Salmon	#FA	#80	#72
Firebrick	#B2	#22	#22
Red	#FF	#00	#00
Darkred	#8B	#00	#00
Lime	#00	#FF	#00
Forestgreen	#22	#8B	#22
Green	#00	#80	#00
Darkgreen	#00	#64	#00
Blue	#00	#00	#FF
Mediumblue	#00	#00	#CD
Darkblue	#00	#00	#8B

2. The hexadecimal information of each HTML color can be mapped to three color elements: red, green and blue.
    1. Each color element has a value between 0 and 255, or `00` and FF in hexadecimal.
    2. For example, for the color *salmon*, the hexadecimal value of the color elements are:
        - red = FA,
        - green = 80, and
        - blue = 72.
3. Record RGB stores information about HTML colors in RGB format, so that we can retrieve the individual color elements.
4. Function `To_RGB` converts from the `HTML_Color` enumeration to the RGB type based on the information from the table above.
5. Function `Image` returns a string representation of the RGB type in this format:
    - `"(Red => 16#..#, Green => 16#...#, Blue => 16#...# )"`

Remarks:

1. We use the exercise on HTML colors from the previous lab on *Strongly typed language* (page 21) as a starting point.

Listing 4: color_types.ads

```
1  package Color_Types is
2
3     type HTML_Color is
4       (Salmon,
5        Firebrick,
6        Red,
7        Darkred,
8        Lime,
9        Forestgreen,
10       Green,
11       Darkgreen,
12       Blue,
13       Mediumblue,
14       Darkblue);
15
16    function To_Integer (C : HTML_Color) return Integer;
17
18    type Basic_HTML_Color is
19      (Red,
```

(continues on next page)

(continued from previous page)

```
      Green,
      Blue);

   function To_HTML_Color (C : Basic_HTML_Color) return HTML_Color;

   subtype Int_Color is Integer range 0 .. 255;

   --  Replace type declaration for RGB record below
   --
   --  - NOTE: Use the Int_Color type declared above!
   --
   --  type RGB is [...]
   --
   type RGB is null record;

   function To_RGB (C : HTML_Color) return RGB;

   function Image (C : RGB) return String;

end Color_Types;
```

Listing 5: color_types.adb

```
with Ada.Integer_Text_IO;

package body Color_Types is

   function To_Integer (C : HTML_Color) return Integer is
   begin
      case C is
         when Salmon      => return 16#FA8072#;
         when Firebrick   => return 16#B22222#;
         when Red         => return 16#FF0000#;
         when Darkred     => return 16#8B0000#;
         when Lime        => return 16#00FF00#;
         when Forestgreen => return 16#228B22#;
         when Green       => return 16#008000#;
         when Darkgreen   => return 16#006400#;
         when Blue        => return 16#0000FF#;
         when Mediumblue  => return 16#0000CD#;
         when Darkblue    => return 16#00008B#;
      end case;

   end To_Integer;

   function To_HTML_Color (C : Basic_HTML_Color) return HTML_Color is
   begin
      case C is
         when Red   => return Red;
         when Green => return Green;
         when Blue  => return Blue;
      end case;
   end To_HTML_Color;

   function To_RGB (C : HTML_Color) return RGB is
   begin
      --  Implement the conversion from HTML_Color to RGB here!
      --
      return (null record);
   end To_RGB;

```

(continues on next page)

(continued from previous page)

```
39    function Image (C : RGB) return String is
40       subtype Str_Range is Integer range 1 .. 10;
41       SR : String (Str_Range);
42       SG : String (Str_Range);
43       SB : String (Str_Range);
44    begin
45       --  Replace argument in the calls to Put below
46       --  with the missing elements (red, green, blue)
47       --  from the RGB record
48       --
49       Ada.Integer_Text_IO.Put (To    => SR,
50                                Item  => 0,    --  REPLACE!
51                                Base  => 16);
52       Ada.Integer_Text_IO.Put (To    => SG,
53                                Item  => 0,    --  REPLACE!
54                                Base  => 16);
55       Ada.Integer_Text_IO.Put (To    => SB,
56                                Item  => 0,    --  REPLACE!
57                                Base  => 16);
58       return ("(Red => " & SR
59               & ", Green => " & SG
60               & ", Blue => "  & SB
61               &")");
62    end Image;
63
64 end Color_Types;
```

Listing 6: main.adb

```
1  with Ada.Command_Line; use Ada.Command_Line;
2  with Ada.Text_IO;      use Ada.Text_IO;
3
4  with Color_Types;      use Color_Types;
5
6  procedure Main is
7     type Test_Case_Index is
8       (HTML_Color_To_RGB);
9
10    procedure Check (TC : Test_Case_Index) is
11    begin
12       case TC is
13          when HTML_Color_To_RGB =>
14             for I in HTML_Color'Range loop
15                Put_Line (HTML_Color'Image (I) & " => "
16                          & Image (To_RGB (I)) & ".");
17             end loop;
18       end case;
19    end Check;
20
21 begin
22    if Argument_Count < 1 then
23       Put_Line ("ERROR: missing arguments! Exiting...");
24       return;
25    elsif Argument_Count > 1 then
26       Put_Line ("Ignoring additional arguments...");
27    end if;
28
29    Check (Test_Case_Index'Value (Argument (1)));
30 end Main;
```

5.3 Inventory

Goal: create a simplified inventory system for a store to enter items and keep track of assets.

Steps:

1. Implement the `Inventory_Pkg` package.
    1. Declare the `Item` record.
    2. Implement the `Init` function.
    3. Implement the `Add` procedure.

Requirements:

1. Record `Item` collects information about products from the store.
    1. To keep it simple, this record only contains the name, quantity and price of each item.
    2. The record components are:
        - `Name` of `Item_Name` type;
        - `Quantity` of **`Natural`** type;
        - `Price` of **`Float`** type.
2. Function `Init` returns an initialized item (of `Item` type).
    1. Function `Init` must also display the item name by calling the `To_String` function for the `Item_Name` type.
        - This is already implemented in the code below.
3. Procedure `Add` adds an item to the assets.
    1. Since we want to keep track of the assets, the implementation must accumulate the total value of each item's inventory, the result of multiplying the item quantity and its price.

Listing 7: inventory_pkg.ads

```
package Inventory_Pkg is

   type Item_Name is
     (Ballpoint_Pen, Oil_Based_Pen_Marker, Feather_Quill_Pen);

   function To_String (I : Item_Name) return String;

   --  Replace type declaration for Item record:
   --
   type Item is null record;

   function Init (Name     : Item_Name;
                  Quantity : Natural;
                  Price    : Float) return Item;

   procedure Add (Assets : in out Float;
                  I      : Item);

end Inventory_Pkg;
```

Listing 8: inventory_pkg.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Inventory_Pkg is

   function To_String (I : Item_Name) return String is
   begin
      case I is
         when Ballpoint_Pen        => return "Ballpoint Pen";
         when Oil_Based_Pen_Marker => return "Oil-based Pen Marker";
         when Feather_Quill_Pen    => return "Feather Quill Pen";
      end case;
   end To_String;

   function Init (Name     : Item_Name;
                  Quantity : Natural;
                  Price    : Float) return Item is
   begin
      Put_Line ("Item: " & To_String (Name) & ".");

      --  Replace return statement with the actual record initialization!
      --
      return (null record);
   end Init;

   procedure Add (Assets : in out Float;
                  I      : Item) is
   begin
      --  Implement the function that adds an item to the inventory here!
      --
      null;
   end Add;

end Inventory_Pkg;
```

Listing 9: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Inventory_Pkg;     use Inventory_Pkg;

procedure Main is
   --  Remark: the following line is not relevant.
   F   : array (1 .. 10) of Float := (others => 42.42);

   type Test_Case_Index is
     (Inventory_Chk);

   procedure Display (Assets : Float) is
      package F_IO is new Ada.Text_IO.Float_IO (Float);

      use F_IO;
   begin
      Put ("Assets: $");
      Put (Assets, 1, 2, 0);
      Put (".");
      New_Line;
   end Display;

```

(continues on next page)

(continued from previous page)

```
24    procedure Check (TC : Test_Case_Index) is
25       I      : Item;
26       Assets : Float := 0.0;
27
28       --  Please ignore the following three lines!
29       pragma Warnings (Off, "default initialization");
30       for Assets'Address use F'Address;
31       pragma Warnings (On, "default initialization");
32    begin
33       case TC is
34       when Inventory_Chk =>
35          I := Init (Ballpoint_Pen,        185,  0.15);
36          Add (Assets, I);
37          Display (Assets);
38
39          I := Init (Oil_Based_Pen_Marker, 100,  9.0);
40          Add (Assets, I);
41          Display (Assets);
42
43          I := Init (Feather_Quill_Pen,      2, 40.0);
44          Add (Assets, I);
45          Display (Assets);
46       end case;
47    end Check;
48
49 begin
50    if Argument_Count < 1 then
51       Put_Line ("ERROR: missing arguments! Exiting...");
52       return;
53    elsif Argument_Count > 1 then
54       Put_Line ("Ignoring additional arguments...");
55    end if;
56
57    Check (Test_Case_Index'Value (Argument (1)));
58 end Main;
```

CHAPTER

SIX

ARRAYS

6.1 Constrained Array

Goal: declare a constrained array and implement operations on it.

Steps:

1. Implement the `Constrained_Arrays` package.
    1. Declare the range type `My_Index`.
    2. Declare the array type `My_Array`.
    3. Declare and implement the `Init` function.
    4. Declare and implement the `Double` procedure.
    5. Declare and implement the `First_Elem` function.
    6. Declare and implement the `Last_Elem` function.
    7. Declare and implement the `Length` function.
    8. Declare the object `A` of `My_Array` type.

Requirements:

1. Range type `My_Index` has a range from 1 to 10.
2. `My_Array` is a constrained array of `Integer` type.
    1. It must make use of the `My_Index` type.
    2. It is therefore limited to 10 elements.
3. Function `Init` returns an array where each element is initialized with the corresponding index.
4. Procedure `Double` doubles the value of each element of an array.
5. Function `First_Elem` returns the first element of the array.
6. Function `Last_Elem` returns the last element of the array.
7. Function `Length` returns the length of the array.
8. Object `A` of `My_Array` type is initialized with:
    1. the values 1 and 2 for the first two elements, and
    2. 42 for all other elements.

Listing 1: constrained_arrays.ads

```
package Constrained_Arrays is

   --  Complete the type and subprogram declarations:
   --
   --  type My_Index is [...]
   --
   --  type My_Array is [...]
   --
   --  function Init ...
   --
   --  procedure Double ...
   --
   --  function First_Elem ...
   --
   --  function Last_Elem ...
   --
   --  function Length ...
   --
   --  A : ...

end Constrained_Arrays;
```

Listing 2: constrained_arrays.adb

```
package body Constrained_Arrays is

   --  Create the implementation of the subprograms!
   --

end Constrained_Arrays;
```

Listing 3: main.adb

```
with Ada.Command_Line;   use Ada.Command_Line;
with Ada.Text_IO;        use Ada.Text_IO;

with Constrained_Arrays; use Constrained_Arrays;

procedure Main is
   type Test_Case_Index is
     (Range_Chk,
      Array_Range_Chk,
      A_Obj_Chk,
      Init_Chk,
      Double_Chk,
      First_Elem_Chk,
      Last_Elem_Chk,
      Length_Chk);

   procedure Check (TC : Test_Case_Index) is
      AA : My_Array;

      procedure Display (A : My_Array) is
      begin
         for I in A'Range loop
            Put_Line (Integer'Image (A (I)));
         end loop;
      end Display;

      procedure Local_Init (A : in out My_Array) is
```

(continues on next page)

(continued from previous page)

```
      begin
         A := (100, 90, 80, 10, 20, 30, 40, 60, 50, 70);
      end Local_Init;
   begin
      case TC is
      when Range_Chk =>
         for I in My_Index loop
            Put_Line (My_Index'Image (I));
         end loop;
      when Array_Range_Chk =>
         for I in My_Array'Range loop
            Put_Line (My_Index'Image (I));
         end loop;
      when A_Obj_Chk =>
         Display (A);
      when Init_Chk =>
         AA := Init;
         Display (AA);
      when Double_Chk =>
         Local_Init (AA);
         Double (AA);
         Display (AA);
      when First_Elem_Chk =>
         Local_Init (AA);
         Put_Line (Integer'Image (First_Elem (AA)));
      when Last_Elem_Chk =>
         Local_Init (AA);
         Put_Line (Integer'Image (Last_Elem (AA)));
      when Length_Chk =>
         Put_Line (Integer'Image (Length (AA)));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

6.2 Colors: Lookup-Table

Goal: rewrite a package to represent HTML colors in RGB format using a lookup table.

Steps:

1. Implement the `Color_Types` package.
    1. Declare the array type `HTML_Color_RGB`.
    2. Declare the `To_RGB_Lookup_Table` object and initialize it.
    3. Adapt the implementation of the `To_RGB` function.

Requirements:

1. Array type `HTML_Color_RGB` is used for the table.
2. The `To_RGB_Lookup_Table` object of `HTML_Color_RGB` type contains the lookup table.

- This table must be implemented as an array of constant values.

3. The implementation of the To_RGB function must use the To_RGB_Lookup_Table object.

Remarks:

1. This exercise is based on the HTML colors exercise from a previous lab (*Records* (page 31)).
2. In the previous implementation, you could use a **case** statement to implement the To_RGB function. Here, you must rewrite the function using a look-up table.
    1. The implementation of the To_RGB function below includes the case statement as commented-out code. You can use this as your starting point: you just need to copy it and convert the case statement to an array declaration.
    1. Don't use a case statement to implement the To_RGB function. Instead, write code that accesses To_RGB_Lookup_Table to get the correct value.
3. The following table contains the HTML colors and the corresponding value in hexadecimal form for each color element:

Color	Red	Green	Blue
Salmon	#FA	#80	#72
Firebrick	#B2	#22	#22
Red	#FF	#00	#00
Darkred	#8B	#00	#00
Lime	#00	#FF	#00
Forestgreen	#22	#8B	#22
Green	#00	#80	#00
Darkgreen	#00	#64	#00
Blue	#00	#00	#FF
Mediumblue	#00	#00	#CD
Darkblue	#00	#00	#8B

Listing 4: color_types.ads

```
1  package Color_Types is
2
3     type HTML_Color is
4       (Salmon,
5        Firebrick,
6        Red,
7        Darkred,
8        Lime,
9        Forestgreen,
10       Green,
11       Darkgreen,
12       Blue,
13       Mediumblue,
14       Darkblue);
15
16    subtype Int_Color is Integer range 0 .. 255;
17
18    type RGB is record
19       Red   : Int_Color;
20       Green : Int_Color;
21       Blue  : Int_Color;
22    end record;
23
```

(continues on next page)

(continued from previous page)

```
   function To_RGB (C : HTML_Color) return RGB;

   function Image (C : RGB) return String;

   --  Declare array type for lookup table here:
   --
   --  type HTML_Color_RGB is ...

   --  Declare lookup table here:
   --
   --  To_RGB_Lookup_Table : ...

end Color_Types;
```

Listing 5: color_types.adb

```
with Ada.Integer_Text_IO;
package body Color_Types is

   function To_RGB (C : HTML_Color) return RGB is
   begin
      --  Implement To_RGB using To_RGB_Lookup_Table
      return (0, 0, 0);

      --  Use the code below from the previous version of the To_RGB
      --  function to declare the To_RGB_Lookup_Table:
      --
      --  case C is
      --     when Salmon      => return (16#FA#, 16#80#, 16#72#);
      --     when Firebrick   => return (16#B2#, 16#22#, 16#22#);
      --     when Red         => return (16#FF#, 16#00#, 16#00#);
      --     when Darkred     => return (16#8B#, 16#00#, 16#00#);
      --     when Lime        => return (16#00#, 16#FF#, 16#00#);
      --     when Forestgreen => return (16#22#, 16#8B#, 16#22#);
      --     when Green       => return (16#00#, 16#80#, 16#00#);
      --     when Darkgreen   => return (16#00#, 16#64#, 16#00#);
      --     when Blue        => return (16#00#, 16#00#, 16#FF#);
      --     when Mediumblue  => return (16#00#, 16#00#, 16#CD#);
      --     when Darkblue    => return (16#00#, 16#00#, 16#8B#);
      --  end case;

   end To_RGB;

   function Image (C : RGB) return String is
      subtype Str_Range is Integer range 1 .. 10;
      SR : String (Str_Range);
      SG : String (Str_Range);
      SB : String (Str_Range);
   begin
      Ada.Integer_Text_IO.Put (To    => SR,
                               Item  => C.Red,
                               Base  => 16);
      Ada.Integer_Text_IO.Put (To    => SG,
                               Item  => C.Green,
                               Base  => 16);
      Ada.Integer_Text_IO.Put (To    => SB,
                               Item  => C.Blue,
                               Base  => 16);
      return ("(Red => " & SR
              & ", Green => " & SG
              & ", Blue => "  & SB
```

(continues on next page)

(continued from previous page)

```
               &")");
   end Image;

end Color_Types;
```

Listing 6: main.adb

```
with Ada.Command_Line;     use Ada.Command_Line;
with Ada.Text_IO;          use Ada.Text_IO;

with Color_Types;          use Color_Types;

procedure Main is
   type Test_Case_Index is
     (Color_Table_Chk,
      HTML_Color_To_Integer_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Color_Table_Chk =>
            Put_Line ("Size of HTML_Color_RGB: "
                      & Integer'Image (HTML_Color_RGB'Length));
            Put_Line ("Firebrick: "
                      & Image (To_RGB_Lookup_Table (Firebrick)));
         when HTML_Color_To_Integer_Chk =>
            for I in HTML_Color'Range loop
               Put_Line (HTML_Color'Image (I) & " => "
                         & Image (To_RGB (I)) & ".");
            end loop;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

6.3 Unconstrained Array

Goal: declare an unconstrained array and implement operations on it.

Steps:

1. Implement the `Unconstrained_Arrays` package.
    1. Declare the `My_Array` type.
    2. Declare and implement the `Init` procedure.
    3. Declare and implement the `Init` function.
    4. Declare and implement the `Double` procedure.
    5. Declare and implement the `Diff_Prev_Elem` function.

Requirements:

1. My_Array is an unconstrained array (with a **Positive** range) of **Integer** elements.
2. Procedure Init initializes each element with the index starting with the last one.
   - For example, for an array of 3 elements where the index of the first element is 1 (My_Array (1 .. 3)), the values of these elements after a call to Init must be (3, 2, 1).
3. Function Init returns an array based on the length L and start index I provided to the Init function.
   1. I indicates the index of the first element of the array.
   2. L indicates the length of the array.
   3. Both I and L must be positive.
   4. This is its declaration: `function Init (I, L : Positive) return My_Array;`.
   5. You must initialize the elements of the array in the same manner as for the Init procedure described above.
4. Procedure Double doubles each element of an array.
5. Function Diff_Prev_Elem returns — for each element of an input array A — an array with the difference between an element of array A and the previous element.
   1. For the first element, the difference must be zero.
   2. For example:
      - **INPUT**: (2, 5, 15)
      - **RETURN** of Diff_Prev_Elem: (0, 3, 10), where
        - 0 is the constant difference for the first element;
        - 5 - 2 = 3 is the difference between the second and the first elements of the input array;
        - 15 - 5 = 10 is the difference between the third and the second elements of the input array.

Remarks:

1. For an array A, you can retrieve the index of the last element with the attribute 'Last.
   1. For example: `Y : Positive := A'Last;`
   2. This can be useful during the implementation of procedure Init.
2. For the implementation of the Init function, you can call the Init procedure to initialize the elements. By doing this, you avoid code duplication.
3. Some hints about attributes:
   1. You can use the range attribute (A'Range) to retrieve the range of an array A.
   2. You can also use the range attribute in the declaration of another array (e.g.: B : My_Array (A'Range)).
   3. Alternatively, you can use the A'First and A'Last attributes in an array declaration.

Listing 7: unconstrained_arrays.ads

```
1 package Unconstrained_Arrays is
2
3    --  Complete the type and subprogram declarations:
```

(continues on next page)

(continued from previous page)

```
   --
   --  type My_Array is ...;
   --
   --  procedure Init ...;

   function Init (I, L : Positive) return My_Array;

   --  procedure Double ...;
   --
   --  function Diff_Prev_Elem ...;

end Unconstrained_Arrays;
```

Listing 8: unconstrained_arrays.adb

```
package body Unconstrained_Arrays is

   --  Implement the subprograms:
   --

   --  procedure Init is...

   --  function Init (L : Positive) return My_Array is...

   --  procedure Double ... is...

   --  function Diff_Prev_Elem ... is...

end Unconstrained_Arrays;
```

Listing 9: main.adb

```
with Ada.Command_Line;     use Ada.Command_Line;
with Ada.Text_IO;          use Ada.Text_IO;

with Unconstrained_Arrays; use Unconstrained_Arrays;

procedure Main is
   type Test_Case_Index is
     (Init_Chk,
      Init_Proc_Chk,
      Double_Chk,
      Diff_Prev_Chk,
      Diff_Prev_Single_Chk);

   procedure Check (TC : Test_Case_Index) is
      AA : My_Array (1 .. 5);
      AB : My_Array (5 .. 9);

      procedure Display (A : My_Array) is
      begin
         for I in A'Range loop
            Put_Line (Integer'Image (A (I)));
         end loop;
      end Display;

      procedure Local_Init (A : in out My_Array) is
      begin
         A := (1, 2, 5, 10, -10);
      end Local_Init;
```

(continues on next page)

(continued from previous page)

```
29
30    begin
31       case TC is
32       when Init_Chk =>
33          AA := Init (AA'First, AA'Length);
34          AB := Init (AB'First, AB'Length);
35          Display (AA);
36          Display (AB);
37       when Init_Proc_Chk =>
38          Init (AA);
39          Init (AB);
40          Display (AA);
41          Display (AB);
42       when Double_Chk =>
43          Local_Init (AB);
44          Double (AB);
45          Display (AB);
46       when Diff_Prev_Chk =>
47          Local_Init (AB);
48          AB := Diff_Prev_Elem (AB);
49          Display (AB);
50       when Diff_Prev_Single_Chk =>
51          declare
52             A1 : My_Array (1 .. 1) := (1 => 42);
53          begin
54             A1 := Diff_Prev_Elem (A1);
55             Display (A1);
56          end;
57       end case;
58    end Check;
59
60 begin
61    if Argument_Count < 1 then
62       Put_Line ("ERROR: missing arguments! Exiting...");
63       return;
64    elsif Argument_Count > 1 then
65       Put_Line ("Ignoring additional arguments...");
66    end if;
67
68    Check (Test_Case_Index'Value (Argument (1)));
69 end Main;
```

6.4 Product info

Goal: create a system to keep track of quantities and prices of products.

Steps:

1. Implement the `Product_Info_Pkg` package.
    1. Declare the array type `Product_Infos`.
    2. Declare the array type `Currency_Array`.
    3. Implement the `Total` procedure.
    4. Implement the `Total` function returning an array of `Currency_Array` type.
    5. Implement the `Total` function returning a single value of `Currency` type.

Requirements:

1. Quantity of an individual product is represented by the `Quantity` subtype.

2. Price of an individual product is represented by the `Currency` subtype.
3. Record type `Product_Info` deals with information for various products.
4. Array type `Product_Infos` is used to represent a list of products.
5. Array type `Currency_Array` is used to represent a list of total values of individual products (see more details below).
6. Procedure `Total` receives an input array of products.
    1. It outputs an array with the total value of each product using the `Currency_Array` type.
    2. The total value of an individual product is calculated by multiplying the quantity for this product by its price.
7. Function `Total` returns an array of `Currency_Array` type.
    1. This function has the same purpose as the procedure `Total`.
    2. The difference is that the function returns an array instead of providing this array as an output parameter.
8. The second function `Total` returns a single value of `Currency` type.
    1. This function receives an array of products.
    2. It returns a single value corresponding to the total value for all products in the system.

Remarks:

1. You can use `Currency (Q)` to convert from an element `Q` of `Quantity` type to the `Currency` type.
    1. As you might remember, Ada requires an explicit conversion in calculations where variables of both integer and floating-point types are used.
    2. In our case, the `Quantity` subtype is based on the **`Integer`** type and the `Currency` subtype is based on the **`Float`** type, so a conversion is necessary in calculations using those types.

Listing 10: product_info_pkg.ads

```
1  package Product_Info_Pkg is
2
3     subtype Quantity is Natural;
4
5     subtype Currency is Float;
6
7     type Product_Info is record
8        Units : Quantity;
9        Price : Currency;
10    end record;
11
12    --  Complete the type declarations:
13    --
14    --  type Product_Infos is ...
15    --
16    --  type Currency_Array is ...
17
18    procedure Total (P   : Product_Infos;
19                     Tot : out Currency_Array);
20
21    function Total (P : Product_Infos) return Currency_Array;
22
23    function Total (P : Product_Infos) return Currency;
```

(continues on next page)

(continued from previous page)

```
24
25 end Product_Info_Pkg;
```

Listing 11: product_info_pkg.adb

```
1  package body Product_Info_Pkg is
2
3     --  Complete the subprogram implementations:
4     --
5
6     --  procedure Total (P   : Product_Infos;
7     --                   Tot : out Currency_Array) is ...
8
9     --  function Total (P : Product_Infos) return Currency_Array is ...
10
11    --  function Total (P : Product_Infos) return Currency is ...
12
13 end Product_Info_Pkg;
```

Listing 12: main.adb

```
1  with Ada.Command_Line;   use Ada.Command_Line;
2  with Ada.Text_IO;        use Ada.Text_IO;
3
4  with Product_Info_Pkg;   use Product_Info_Pkg;
5
6  procedure Main is
7     package Currency_IO is new Ada.Text_IO.Float_IO (Currency);
8
9     type Test_Case_Index is
10      (Total_Func_Chk,
11       Total_Proc_Chk,
12       Total_Value_Chk);
13
14    procedure Check (TC : Test_Case_Index) is
15       subtype Test_Range is Positive range 1 .. 5;
16
17       P    : Product_Infos (Test_Range);
18       Tots : Currency_Array (Test_Range);
19       Tot  : Currency;
20
21       procedure Display (Tots : Currency_Array) is
22       begin
23          for I in Tots'Range loop
24             Currency_IO.Put (Tots (I));
25             New_Line;
26          end loop;
27       end Display;
28
29       procedure Local_Init (P : in out Product_Infos) is
30       begin
31          P := ((1,   0.5),
32                (2,  10.0),
33                (5,  40.0),
34                (10, 10.0),
35                (10, 20.0));
36       end Local_Init;
37
38    begin
39       Currency_IO.Default_Fore := 1;
```

(continues on next page)

(continued from previous page)

```
40       Currency_IO.Default_Aft  := 2;
41       Currency_IO.Default_Exp  := 0;
42
43       case TC is
44       when Total_Func_Chk =>
45          Local_Init (P);
46          Tots := Total (P);
47          Display (Tots);
48       when Total_Proc_Chk =>
49          Local_Init (P);
50          Total (P, Tots);
51          Display (Tots);
52       when Total_Value_Chk =>
53          Local_Init (P);
54          Tot := Total (P);
55          Currency_IO.Put (Tot);
56          New_Line;
57       end case;
58    end Check;
59
60 begin
61    if Argument_Count < 1 then
62       Put_Line ("ERROR: missing arguments! Exiting...");
63       return;
64    elsif Argument_Count > 1 then
65       Put_Line ("Ignoring additional arguments...");
66    end if;
67
68    Check (Test_Case_Index'Value (Argument (1)));
69 end Main;
```

6.5 String_10

Goal: work with constrained string types.

Steps:

1. Implement the `Strings_10` package.
    1. Declare the `String_10` type.
    2. Implement the `To_String_10` function.

Requirements:

1. The constrained string type `String_10` is an array of ten characters.
2. Function `To_String_10` returns constrained strings of `String_10` type based on an input parameter of **`String`** type.
    - For strings that are more than 10 characters, omit everything after the 11th character.
    - For strings that are fewer than 10 characters, pad the string with `' '` characters until it is 10 characters.

Remarks:

1. Declaring `String_10` as a subtype of **`String`** is the easiest way.
    - You may declare it as a new type as well. However, this requires some adaptations in the `Main` test procedure.
2. You can use **`Integer`**`'Min` to calculate the minimum of two integer values.

Listing 13: strings_10.ads

```
package Strings_10 is

   --  Complete the type and subprogram declarations:
   --

   --  subtype String_10 is ...;

   --  Using "type String_10 is..." is possible, too. However, it
   --  requires a custom Put_Line procedure that is called in Main:
   --  procedure Put_Line (S : String_10);

   --  function To_String_10 ...;

end Strings_10;
```

Listing 14: strings_10.adb

```
package body Strings_10 is

   --  Complete the subprogram declaration and implementation:
   --
   --  function To_String_10 ... is

end Strings_10;
```

Listing 15: main.adb

```
with Ada.Command_Line;   use Ada.Command_Line;
with Ada.Text_IO;        use Ada.Text_IO;

with Strings_10;         use Strings_10;

procedure Main is
   type Test_Case_Index is
     (String_10_Long_Chk,
      String_10_Short_Chk);

   procedure Check (TC : Test_Case_Index) is
      SL   : constant String := "And this is a long string just for testing...";
      SS   : constant String := "Hey!";
      S_10 : String_10;

   begin
      case TC is
      when String_10_Long_Chk =>
         S_10 := To_String_10 (SL);
         Put_Line (String (S_10));
      when String_10_Short_Chk =>
         S_10 := (others => ' ');
         S_10 := To_String_10 (SS);
         Put_Line (String (S_10));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Ada.Text_IO.Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
```

(continues on next page)

(continued from previous page)

```
33       Ada.Text_IO.Put_Line ("Ignoring additional arguments...");
34    end if;
35
36    Check (Test_Case_Index'Value (Argument (1)));
37 end Main;
```

6.6 List of Names

Goal: create a system for a list of names and ages.

Steps:

1. Implement the `Names_Ages` package.
    1. Declare the `People_Array` array type.
    2. Complete the declaration of the `People` record type with the `People_A` element of `People_Array` type.
    3. Implement the `Add` procedure.
    4. Implement the `Reset` procedure.
    5. Implement the `Get` function.
    6. Implement the `Update` procedure.
    7. Implement the `Display` procedure.

Requirements:

1. Each person is represented by the `Person` type, which is a record containing the name and the age of that person.
2. `People_Array` is an unconstrained array of `Person` type with a positive range.
3. The `Max_People` constant is set to 10.
4. Record type `People` contains:
    1. The `People_A` element of `People_Array` type.
    2. This array must be constrained by the `Max_People` constant.
5. Procedure `Add` adds a person to the list.
    1. By default, the age of this person is set to zero in this procedure.
6. Procedure `Reset` resets the list.
7. Function `Get` retrieves the age of a person from the list.
8. Procedure `Update` updates the age of a person in the list.
9. Procedure `Display` shows the complete list using the following format:
    1. The first line must be `LIST OF NAMES:`. It is followed by the name and age of each person in the next lines.
    2. For each person on the list, the procedure must display the information in the following format:

```
NAME: XXXX
AGE: YY
```

Remarks:

1. In the implementation of procedure Add, you may use an index to indicate the last valid position in the array — see `Last_Valid` in the code below.
2. In the implementation of procedure `Display`, you should use the `Trim` function from the `Ada.Strings.Fixed` package to format the person's name — for example: `Trim (P.Name, Right)`.
3. You may need the `Integer'Min (A, B)` and the `Integer'Max (A, B)` functions to get the minimum and maximum values in a comparison between two integer values A and B.
4. Fixed-length strings can be initialized with whitespaces using the `others` syntax. For example: `S : String_10 := (others => ' ');`
5. You may implement additional subprograms to deal with other types declared in the `Names_Ages` package below, such as the `Name_Type` and the `Person` type.
    1. For example, a function `To_Name_Type` to convert from `String` to `Name_Type` might be useful.
    2. Take a moment to reflect on which additional subprograms could be useful as well.

Listing 16: names_ages.ads

```
package Names_Ages is

   Max_People : constant Positive := 10;

   subtype Name_Type is String (1 .. 50);

   type Age_Type is new Natural;

   type Person is record
      Name  : Name_Type;
      Age   : Age_Type;
   end record;

   --  Add type declaration for People_Array record:
   --
   --  type People_Array is ...;

   --  Replace type declaration for People record. You may use the
   --  following template:
   --
   --  type People is record
   --     People_A   : People_Array ...;
   --     Last_Valid : Natural;
   --  end record;
   --
   type People is null record;

   procedure Reset (P : in out People);

   procedure Add (P    : in out People;
                  Name : String);

   function Get (P    : People;
                 Name : String) return Age_Type;

   procedure Update (P    : in out People;
                     Name : String;
                     Age  : Age_Type);

   procedure Display (P : People);
```

(continues on next page)

(continued from previous page)

```
41
42 end Names_Ages;
```

Listing 17: names_ages.adb

```
1  with Ada.Text_IO;       use Ada.Text_IO;
2  with Ada.Strings;       use Ada.Strings;
3  with Ada.Strings.Fixed; use Ada.Strings.Fixed;
4
5  package body Names_Ages is
6
7     procedure Reset (P : in out People) is
8     begin
9        null;
10    end Reset;
11
12    procedure Add (P    : in out People;
13                   Name :        String) is
14    begin
15       null;
16    end Add;
17
18    function Get (P    : People;
19                  Name : String) return Age_Type is
20    begin
21       return 0;
22    end Get;
23
24    procedure Update (P    : in out People;
25                      Name :        String;
26                      Age  :        Age_Type) is
27    begin
28       null;
29    end Update;
30
31    procedure Display (P : People) is
32    begin
33       null;
34    end Display;
35
36 end Names_Ages;
```

Listing 18: main.adb

```
1  with Ada.Command_Line;   use Ada.Command_Line;
2  with Ada.Text_IO;        use Ada.Text_IO;
3
4  with Names_Ages;         use Names_Ages;
5
6  procedure Main is
7     type Test_Case_Index is
8       (Names_Ages_Chk,
9        Get_Age_Chk);
10
11    procedure Check (TC : Test_Case_Index) is
12       P : People;
13    begin
14       case TC is
15       when Names_Ages_Chk =>
16          Reset (P);
```

(continues on next page)

(continued from previous page)

```
17          Add (P, "John");
18          Add (P, "Patricia");
19          Add (P, "Josh");
20          Display (P);
21          Update (P, "John",     18);
22          Update (P, "Patricia", 35);
23          Update (P, "Josh",     53);
24          Display (P);
25       when Get_Age_Chk =>
26          Reset (P);
27          Add (P, "Peter");
28          Update (P, "Peter", 45);
29          Put_Line ("Peter is "
30                    & Age_Type'Image (Get (P, "Peter"))
31                    & " years old.");
32       end case;
33    end Check;
34
35 begin
36    if Argument_Count < 1 then
37       Ada.Text_IO.Put_Line ("ERROR: missing arguments! Exiting...");
38       return;
39    elsif Argument_Count > 1 then
40       Ada.Text_IO.Put_Line ("Ignoring additional arguments...");
41    end if;
42
43    Check (Test_Case_Index'Value (Argument (1)));
44 end Main;
```

CHAPTER

SEVEN

MORE ABOUT TYPES

7.1 Aggregate Initialization

Goal: initialize records and arrays using aggregates.

Steps:

1. Implement the `Aggregates` package.
    1. Create the record type Rec.
    2. Create the array type `Int_Arr`.
    3. Implement the `Init` procedure that outputs a record of Rec type.
    4. Implement the `Init_Some` procedure.
    5. Implement the `Init` procedure that outputs an array of `Int_Arr` type.

Requirements:

1. Record type Rec has four components of **`Integer`** type. These are the components with the corresponding default values:
    - `W` = 10
    - `X` = 11
    - `Y` = 12
    - `Z` = 13
2. Array type `Int_Arr` has 20 elements of **`Integer`** type (with indices ranging from 1 to 20).
3. The first `Init` procedure outputs a record of Rec type where:
    1. `X` is initialized with 100,
    2. `Y` is initialized with 200, and
    3. the remaining elements use their default values.
4. Procedure `Init_Some` outputs an array of `Int_Arr` type where:
    1. the first five elements are initialized with the value 99, and
    2. the remaining elements are initialized with the value 100.
5. The second `Init` procedure outputs an array of `Int_Arr` type where:
    1. all elements are initialized with the value 5.

Listing 1: aggregates.ads

```
package Aggregates is

   --  type Rec is ...;

   --  type Int_Arr is ...;

   procedure Init;

   --  procedure Init_Some ...;

   --  procedure Init ...;

end Aggregates;
```

Listing 2: aggregates.adb

```
package body Aggregates is

   procedure Init is null;

end Aggregates;
```

Listing 3: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Aggregates;        use Aggregates;

procedure Main is
   --  Remark: the following line is not relevant.
   F   : array (1 .. 10) of Float := (others => 42.42)
     with Unreferenced;

   type Test_Case_Index is
     (Default_Rec_Chk,
      Init_Rec_Chk,
      Init_Some_Arr_Chk,
      Init_Arr_Chk);

   procedure Check (TC : Test_Case_Index) is
      A : Int_Arr;
      R : Rec;
      DR : constant Rec := (others => <>);
   begin
      case TC is
         when Default_Rec_Chk =>
            R := DR;
            Put_Line ("Record Default:");
            Put_Line ("W => " & Integer'Image (R.W));
            Put_Line ("X => " & Integer'Image (R.X));
            Put_Line ("Y => " & Integer'Image (R.Y));
            Put_Line ("Z => " & Integer'Image (R.Z));
         when Init_Rec_Chk =>
            Init (R);
            Put_Line ("Record Init:");
            Put_Line ("W => " & Integer'Image (R.W));
            Put_Line ("X => " & Integer'Image (R.X));
            Put_Line ("Y => " & Integer'Image (R.Y));
            Put_Line ("Z => " & Integer'Image (R.Z));
```

(continues on next page)

(continued from previous page)

```
37          when Init_Some_Arr_Chk =>
38             Init_Some (A);
39             Put_Line ("Array Init_Some:");
40             for I in A'Range loop
41                Put_Line (Integer'Image (I) & " "
42                          & Integer'Image (A (I)));
43             end loop;
44          when Init_Arr_Chk =>
45             Init (A);
46             Put_Line ("Array Init:");
47             for I in A'Range loop
48                Put_Line (Integer'Image (I) & " "
49                          & Integer'Image (A (I)));
50             end loop;
51       end case;
52    end Check;
53
54 begin
55    if Argument_Count < 1 then
56       Put_Line ("ERROR: missing arguments! Exiting...");
57       return;
58    elsif Argument_Count > 1 then
59       Put_Line ("Ignoring additional arguments...");
60    end if;
61
62    Check (Test_Case_Index'Value (Argument (1)));
63 end Main;
```

7.2 Versioning

Goal: implement a simple package for source-code versioning.

Steps:

1. Implement the `Versioning` package.
    1. Declare the record type `Version`.
    2. Implement the `Convert` function that returns a string.
    3. Implement the `Convert` function that returns a floating-point number.

Requirements:

1. Record type `Version` has the following components of **`Natural`** type:
    1. `Major`,
    2. `Minor`, and
    3. `Maintenance`.
2. The first `Convert` function returns a string containing the version number.
3. The second `Convert` function returns a floating-point value.
    1. For this floating-point value:
        1. the number before the decimal point must correspond to the major number, and
        2. the number after the decimal point must correspond to the minor number.
        3. the maintenance number is ignored.
    2. For example, version "1.3.5" is converted to the floating-point value `1.3`.

3. An obvious limitation of this function is that it can only handle one-digit numbers for the minor component.
   - For example, we cannot convert version "1.10.0" to a reasonable value with the approach described above. The result of the call `Convert ((1, 10, 0))` is therefore unspecified.
   - For the scope of this exercise, only version numbers with one-digit components are checked.

Remarks:

1. We use overloading for the `Convert` functions.
2. For the function `Convert` that returns a string, you can make use of the `Image_Trim` function, as indicated in the source-code below — see package body of `Versioning`.

Listing 4: versioning.ads

```
package Versioning is

   --  type Version is record...

   --  function Convert ...

   --  function Convert

end Versioning;
```

Listing 5: versioning.adb

```
with Ada.Strings; use Ada.Strings;
with Ada.Strings.Fixed; use Ada.Strings.Fixed;

package body Versioning is

   function Image_Trim (N : Natural) return String is
      S_N : constant String := Trim (Natural'Image (N), Left);
   begin
      return S_N;
   end Image_Trim;

   --  function Convert ...
   --     S_Major : constant String := Image_Trim (V.Major);
   --     S_Minor : constant String := Image_Trim (V.Minor);
   --     S_Maint : constant String := Image_Trim (V.Maintenance);
   --  begin
   --  end Convert;

   --  function Convert ...
   --  begin
   --  end Convert;

end Versioning;
```

Listing 6: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Versioning;        use Versioning;

procedure Main is
```

(continues on next page)

(continued from previous page)

```
   type Test_Case_Index is
     (Ver_String_Chk,
      Ver_Float_Chk);

   procedure Check (TC : Test_Case_Index) is
      V : constant Version := (1, 3, 23);
   begin
      case TC is
         when Ver_String_Chk =>
            Put_Line (Convert (V));
         when Ver_Float_Chk =>
            Put_Line (Float'Image (Convert (V)));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

7.3 Simple todo list

Goal: implement a simple to-do list system.

Steps:

1. Implement the `Todo_Lists` package.
    1. Declare the `Todo_Item` type.
    2. Declare the `Todo_List` type.
    3. Implement the `Add` procedure.
    4. Implement the `Display` procedure.

Requirements:

1. `Todo_Item` type is used to store a to-do item.
    1. It should be implemented as an access type to strings.
2. `Todo_Items` type is an array of to-do items.
    1. It should be implemented as an unconstrained array with positive range.
3. `Todo_List` type is the container for all to-do items.
    1. This record type must have a discriminant for the maximum number of elements of the list.
    2. In order to store the to-do items, it must contain a component named `Items` of `Todo_Items` type.
    3. Don't forget to keep track of the last element added to the list!
        - You should declare a `Last` component in the record.
4. Procedure `Add` adds items (of `Todo_Item` type) to the list (of `Todo_List` type).

    1. This requires allocating a string for the access type.
    2. An item can only be added to the list if the list isn't full yet — see next point for details on error handling.
5. Since the number of items that can be stored on the list is limited, the list might eventually become full in a call to Add.
    1. You must write code in the implementation of the Add procedure that verifies this condition.
    2. If the procedure detects that the list is full, it must display the following message: "ERROR: list is full!".
6. Procedure Display is used to display all to-do items.
    1. The header (first line) must be TO-DO LIST.
    2. It must display one item per line.

Remarks:

1. We use access types and unconstrained arrays in the implementation of the Todo_Lists package.

Listing 7: todo_lists.ads

```
package Todo_Lists is

   --  Replace by actual type declaration
   type Todo_Item is null record;

   --  Replace by actual type declaration
   type Todo_Items is null record;

   --  Replace by actual type declaration
   type Todo_List is null record;

   procedure Add (Todos : in out Todo_List;
                  Item  : String);

   procedure Display (Todos : Todo_List);

end Todo_Lists;
```

Listing 8: todo_lists.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Todo_Lists is

   procedure Add (Todos : in out Todo_List;
                  Item  : String) is
   begin
      Put_Line ("ERROR: list is full!");
   end Add;

   procedure Display (Todos : Todo_List) is
   begin
      null;
   end Display;

end Todo_Lists;
```

Listing 9: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Todo_Lists;        use Todo_Lists;

procedure Main is
   type Test_Case_Index is
     (Todo_List_Chk);

   procedure Check (TC : Test_Case_Index) is
      T : Todo_List (10);
   begin
      case TC is
         when Todo_List_Chk =>
            Add (T, "Buy milk");
            Add (T, "Buy tea");
            Add (T, "Buy present");
            Add (T, "Buy tickets");
            Add (T, "Pay electricity bill");
            Add (T, "Schedule dentist appointment");
            Add (T, "Call sister");
            Add (T, "Revise spreasheet");
            Add (T, "Edit entry page");
            Add (T, "Select new design");
            Add (T, "Create upgrade plan");
            Display (T);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

7.4 Price list

Goal: implement a list containing prices

Steps:

1. Implement the `Price_Lists` package.
    1. Declare the `Price_Type` type.
    2. Declare the `Price_List` record.
    3. Implement the `Reset` procedure.
    4. Implement the `Add` procedure.
    5. Implement the `Get` function.
    6. Implement the `Display` procedure.

Requirements:

1. `Price_Type` is a decimal fixed-point data type with a delta of two digits (e.g. `0.01`) and twelve digits in total.
2. `Price_List` is a record type that contains the price list.
    1. This record type must have a discriminant for the maximum number of elements of the list.
3. Procedure `Reset` resets the list.
4. Procedure `Add` adds a price to the list.
    1. You should keep track of the last element added to the list.
5. Function `Get` retrieves a price from the list using an index.
    1. This function returns a record instance of `Price_Result` type.
    2. `Price_Result` is a variant record containing:
        1. the Boolean component `Ok`, and
        2. the component `Price` (of `Price_Type`).
    3. The returned value of `Price_Result` type is one of the following:
        1. If the index specified in a call to `Get` contains a valid (initialized) price, then
            - `Ok` is set to **`True`**, and
            - the `Price` component contains the price for that index.
        2. Otherwise:
            - `Ok` is set to **`False`**, and
            - the `Price` component is not available.
6. Procedure `Display` shows all prices from the list.
    1. The header (first line) must be `PRICE LIST`.
    2. The remaining lines contain one price per line.
    3. For example:
        - For the following code:

```
procedure Test is
   L : Price_List (10);
begin
   Reset (L);
   Add (L, 1.45);
   Add (L, 2.37);
   Display (L);
end Test;
```

        - The output is:

```
PRICE LIST
 1.45
 2.37
```

Remarks:

1. To implement the package, you'll use the following features of the Ada language:
    1. decimal fixed-point types;
    2. records with discriminants;
    3. dynamically-sized record types;

4. variant records.

2. For record type `Price_List`, you may use an unconstrained array as a component of the record and use the discriminant in the component declaration.

Listing 10: price_lists.ads

```
package Price_Lists is

   --  Replace by actual type declaration
   type Price_Type is new Float;

   --  Replace by actual type declaration
   type Price_List is null record;

   --  Replace by actual type declaration
   type Price_Result is null record;

   procedure Reset (Prices : in out Price_List);

   procedure Add (Prices : in out Price_List;
                  Item   : Price_Type);

   function Get (Prices : Price_List;
                 Idx    : Positive) return Price_Result;

   procedure Display (Prices : Price_List);

end Price_Lists;
```

Listing 11: price_lists.adb

```
package body Price_Lists is

   procedure Reset (Prices : in out Price_List) is
   begin
      null;
   end Reset;

   procedure Add (Prices : in out Price_List;
                  Item   : Price_Type) is
   begin
      null;
   end Add;

   function Get (Prices : Price_List;
                 Idx    : Positive) return Price_Result is
   begin
      null;
   end Get;

   procedure Display (Prices : Price_List) is
   begin
      null;
   end Display;

end Price_Lists;
```

Listing 12: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;
```

(continues on next page)

(continued from previous page)

```
3
4  with Price_Lists;       use Price_Lists;
5
6  procedure Main is
7     type Test_Case_Index is
8       (Price_Type_Chk,
9        Price_List_Chk,
10       Price_List_Get_Chk);
11
12    procedure Check (TC : Test_Case_Index) is
13       L : Price_List (10);
14
15       procedure Local_Init_List is
16       begin
17          Reset (L);
18          Add (L, 1.45);
19          Add (L, 2.37);
20          Add (L, 3.21);
21          Add (L, 4.14);
22          Add (L, 5.22);
23          Add (L, 6.69);
24          Add (L, 7.77);
25          Add (L, 8.14);
26          Add (L, 9.99);
27          Add (L, 10.01);
28       end Local_Init_List;
29
30       procedure Get_Display (Idx : Positive) is
31          R : constant Price_Result := Get (L, Idx);
32       begin
33          Put_Line ("Attempt Get # " & Positive'Image (Idx));
34          if R.Ok then
35             Put_Line ("Element # " & Positive'Image (Idx)
36                       & " => "     & Price_Type'Image (R.Price));
37          else
38             declare
39             begin
40                Put_Line ("Element # " & Positive'Image (Idx)
41                          & " => "     & Price_Type'Image (R.Price));
42             exception
43                when others =>
44                   Put_Line ("Element not available (as expected)");
45             end;
46          end if;
47
48       end Get_Display;
49
50    begin
51       case TC is
52          when Price_Type_Chk =>
53             Put_Line ("The delta    value of Price_Type is "
54                       & Price_Type'Image (Price_Type'Delta) & ";");
55             Put_Line ("The minimum  value of Price_Type is "
56                       & Price_Type'Image (Price_Type'First) & ";");
57             Put_Line ("The maximum  value of Price_Type is "
58                       & Price_Type'Image (Price_Type'Last)  & ";");
59          when Price_List_Chk =>
60             Local_Init_List;
61             Display (L);
62          when Price_List_Get_Chk =>
63             Local_Init_List;
```

(continues on next page)

(continued from previous page)

```
64             Get_Display (5);
65             Get_Display (40);
66       end case;
67    end Check;
68
69 begin
70    if Argument_Count < 1 then
71       Put_Line ("ERROR: missing arguments! Exiting...");
72       return;
73    elsif Argument_Count > 1 then
74       Put_Line ("Ignoring additional arguments...");
75    end if;
76
77    Check (Test_Case_Index'Value (Argument (1)));
78 end Main;
```

CHAPTER

EIGHT

PRIVACY

8.1 Directions

Goal: create a package that handles directions and geometric angles using a previous implementation.

Steps:

1. Fix the implementation of the `Test_Directions` procedure.

Requirements:

1. The implementation of the `Test_Directions` procedure must compile correctly.

Remarks:

1. This exercise is based on the *Directions* exercise from the *Records* (page 31) labs.
    1. In this version, however, `Ext_Angle` is a private type.
2. In the implementation of the `Test_Directions` procedure below, the Ada developer tried to initialize `All_Directions` — an array of `Ext_Angle` type — with aggregates.
    1. Since we now have a private type, the compiler complains about this initialization.
3. To fix the implementation of the `Test_Directions` procedure, you should use the appropriate function from the `Directions` package.
4. The initialization of `All_Directions` in the code below contains a consistency error where the angle doesn't match the assessed direction.
    1. See if you can spot this error!
    2. This kind of errors can happen when record components that have correlated information are initialized individually without consistency checks — using private types helps to avoid the problem by requiring initialization routines that can enforce consistency.

Listing 1: directions.ads

```
1  package Directions is
2
3     type Angle_Mod is mod 360;
4
5     type Direction is
6       (North,
7        Northwest,
8        West,
9        Southwest,
10       South,
11       Southeast,
12       East);
13
```

(continues on next page)

(continued from previous page)

```
14    function To_Direction (N : Angle_Mod) return Direction;
15
16    type Ext_Angle is private;
17
18    function To_Ext_Angle (N : Angle_Mod) return Ext_Angle;
19
20    procedure Display (N : Ext_Angle);
21
22 private
23
24    type Ext_Angle is record
25       Angle_Elem     : Angle_Mod;
26       Direction_Elem : Direction;
27    end record;
28
29 end Directions;
```

Listing 2: directions.adb

```
1  with Ada.Text_IO; use Ada.Text_IO;
2
3  package body Directions is
4
5     procedure Display (N : Ext_Angle) is
6     begin
7        Put_Line ("Angle: "
8                  & Angle_Mod'Image (N.Angle_Elem)
9                  & " => "
10                 & Direction'Image (N.Direction_Elem)
11                 & ".");
12    end Display;
13
14    function To_Direction (N : Angle_Mod) return Direction is
15    begin
16       case N is
17          when   0        => return East;
18          when   1 ..  89 => return Northwest;
19          when  90        => return North;
20          when  91 .. 179 => return Northwest;
21          when 180        => return West;
22          when 181 .. 269 => return Southwest;
23          when 270        => return South;
24          when 271 .. 359 => return Southeast;
25       end case;
26    end To_Direction;
27
28    function To_Ext_Angle (N : Angle_Mod) return Ext_Angle is
29    begin
30       return (Angle_Elem     => N,
31               Direction_Elem => To_Direction (N));
32    end To_Ext_Angle;
33
34 end Directions;
```

Listing 3: test_directions.adb

```
1  with Directions; use Directions;
2
3  procedure Test_Directions is
4     type Ext_Angle_Array is array (Positive range <>) of Ext_Angle;
```

(continues on next page)

(continued from previous page)

```
5
6     All_Directions : constant Ext_Angle_Array (1 .. 6)
7       := ((0,   East),
8           (45,  Northwest),
9           (90,  North),
10          (91,  North),
11          (180, West),
12          (270, South));
13
14 begin
15    for I in All_Directions'Range loop
16       Display (All_Directions (I));
17    end loop;
18
19 end Test_Directions;
```

Listing 4: main.adb

```
1  with Ada.Command_Line;  use Ada.Command_Line;
2  with Ada.Text_IO;       use Ada.Text_IO;
3
4  with Test_Directions;
5
6  procedure Main is
7       type Test_Case_Index is
8       (Direction_Chk);
9
10    procedure Check (TC : Test_Case_Index) is
11    begin
12       case TC is
13       when Direction_Chk =>
14          Test_Directions;
15       end case;
16    end Check;
17
18 begin
19    if Argument_Count < 1 then
20       Put_Line ("ERROR: missing arguments! Exiting...");
21       return;
22    elsif Argument_Count > 1 then
23       Put_Line ("Ignoring additional arguments...");
24    end if;
25
26    Check (Test_Case_Index'Value (Argument (1)));
27 end Main;
```

8.2 Limited Strings

Goal: work with `limited private` types.

Steps:

1. Implement the `Limited_Strings` package.
    1. Implement the `Copy` function.
    2. Implement the `=` operator.

Requirements:

1. For both `Copy` and `=`, the two parameters may refer to strings with different lengths.

We'll limit the implementation to just take the minimum length:

1. In case of copying the string "Hello World" to a string with 5 characters, the copied string is "Hello":

```
   S1 : constant Lim_String := Init ("Hello World");
   S2 :          Lim_String := Init (5);
begin
   Copy (From => S1, To => S2);
   Put_Line (S2);     --  This displays "Hello".
```

2. When comparing "Hello World" to "Hello", the = operator indicates that these strings are equivalent:

```
   S1 : constant Lim_String := Init ("Hello World");
   S2 : constant Lim_String := Init ("Hello");
begin
   if S1 = S2 then
      --  True => This branch gets selected.
```

2. When copying from a short string to a longer string, the remaining characters of the longer string must be initialized with underscores (_). For example:

```
   S1 : constant Lim_String := Init ("Hello");
   S2 :          Lim_String := Init (10);
begin
   Copy (From => S1, To => S2);
   Put_Line (S2);     --  This displays "Hello_____".
```

Remarks:

1. As we've discussed in the course:
   1. Variables of limited types have the following limitations:
      - they cannot be assigned to;
      - they don't have an equality operator (=).
   2. We can, however, define our own, custom subprograms to circumvent these limitations:
      - In order to copy instances of a limited type, we can define a custom Copy procedure.
      - In order to compare instances of a limited type, we can define an = operator.
2. You can use the `Min_Last` constant — which is already declared in the implementation of these subprograms — in the code you write.
3. Some details about the `Limited_Strings` package:
   1. The `Lim_String` type acts as a container for strings.
      1. In the the private part, `Lim_String` is declared as an access type to a **`String`**.
   2. There are two versions of the `Init` function that initializes an object of `Lim_String` type:
      1. The first one takes another string.
      2. The second one receives the number of characters for a string *container*.
   3. Procedure `Put_Line` displays object of `Lim_String` type.
   4. The design and implementation of the `Limited_Strings` package is very simplistic.
      1. A good design would have better handling of access types, for example.

Listing 5: limited_strings.ads

```
1  package Limited_Strings is
2
3     type Lim_String is limited private;
4
5     function Init (S : String) return Lim_String;
6
7     function Init (Max : Positive) return Lim_String;
8
9     procedure Put_Line (LS : Lim_String);
10
11    procedure Copy (From :        Lim_String;
12                    To   : in out Lim_String);
13
14    function "=" (Ref, Dut : Lim_String) return Boolean;
15
16 private
17
18    type Lim_String is access String;
19
20 end Limited_Strings;
```

Listing 6: limited_strings.adb

```
1  with Ada.Text_IO;
2
3  package body Limited_Strings
4  is
5
6     function Init (S : String) return Lim_String is
7        LS : constant Lim_String := new String'(S);
8     begin
9        return Ls;
10    end Init;
11
12    function Init (Max : Positive) return Lim_String is
13       LS : constant Lim_String := new String (1 .. Max);
14    begin
15       LS.all := (others => '_');
16       return LS;
17    end Init;
18
19    procedure Put_Line (LS : Lim_String) is
20    begin
21       Ada.Text_IO.Put_Line (LS.all);
22    end Put_Line;
23
24    function Get_Min_Last (A, B : Lim_String) return Positive is
25    begin
26       return Positive'Min (A'Last, B'Last);
27    end Get_Min_Last;
28
29    procedure Copy (From :        Lim_String;
30                    To   : in out Lim_String) is
31       Min_Last : constant Positive := Get_Min_Last (From, To);
32    begin
33       --  Complete the implementation!
34       null;
35    end;
36
```

(continues on next page)

(continued from previous page)

```
37    function "=" (Ref, Dut : Lim_String) return Boolean is
38       Min_Last : constant Positive := Get_Min_Last (Ref, Dut);
39    begin
40       --  Complete the implementation!
41       return True;
42    end;
43
44 end Limited_Strings;
```

Listing 7: check_lim_string.adb

```
1  with Ada.Text_IO;     use Ada.Text_IO;
2
3  with Limited_Strings; use Limited_Strings;
4
5  procedure Check_Lim_String is
6     S  : constant String := "----------";
7     S1 : constant Lim_String := Init ("Hello World");
8     S2 : constant Lim_String := Init (30);
9     S3 : Lim_String := Init (5);
10    S4 : Lim_String := Init (S & S & S);
11 begin
12    Put ("S1 => ");
13    Put_Line (S1);
14    Put ("S2 => ");
15    Put_Line (S2);
16
17    if S1 = S2 then
18       Put_Line ("S1 is equal to S2.");
19    else
20       Put_Line ("S1 isn't equal to S2.");
21    end if;
22
23    Copy (From => S1, To => S3);
24    Put ("S3 => ");
25    Put_Line (S3);
26
27    if S1 = S3 then
28       Put_Line ("S1 is equal to S3.");
29    else
30       Put_Line ("S1 isn't equal to S3.");
31    end if;
32
33    Copy (From => S1, To => S4);
34    Put ("S4 => ");
35    Put_Line (S4);
36
37    if S1 = S4 then
38       Put_Line ("S1 is equal to S4.");
39    else
40       Put_Line ("S1 isn't equal to S4.");
41    end if;
42 end Check_Lim_String;
```

Listing 8: main.adb

```
1  with Ada.Command_Line; use Ada.Command_Line;
2  with Ada.Text_IO;      use Ada.Text_IO;
3
4  with Check_Lim_String;
```

(continues on next page)

(continued from previous page)

```
5
6  procedure Main is
7     type Test_Case_Index is
8       (Lim_String_Chk);
9
10    procedure Check (TC : Test_Case_Index) is
11    begin
12       case TC is
13       when Lim_String_Chk =>
14          Check_Lim_String;
15       end case;
16    end Check;
17
18 begin
19    if Argument_Count < 1 then
20       Put_Line ("ERROR: missing arguments! Exiting...");
21       return;
22    elsif Argument_Count > 1 then
23       Put_Line ("Ignoring additional arguments...");
24    end if;
25
26    Check (Test_Case_Index'Value (Argument (1)));
27 end Main;
```

8.3 Bonus exercise

In previous labs, we had many source-code snippets containing records that could be declared private. The source-code for the exercise above (*Directions*) is an example: we've modified the type declaration of `Ext_Angle`, so that the record is now private. Encapsulating the record components — by declaring record components in the private part — makes the code safer. Also, because many of the code snippets weren't making use of record components directly (but handling record types via the API instead), they continue to work fine after these modifications.

This exercise doesn't contain any source-code. In fact, the **goal** here is to modify previous labs, so that the record declarations are made private. You can look into those labs, modify the type declarations, and recompile the code. The corresponding test-cases must still pass.

If no other changes are needed apart from changes in the declaration, then that indicates we have used good programming techniques in the original code. On the other hand, if further changes are needed, then you should investigate why this is the case.

Also note that, in some cases, you can move support types into the private part of the specification without affecting its compilation. This is the case, for example, for the `People_Array` type of the *List of Names* lab mentioned below. You should, in fact, keep only relevant types and subprograms in the public part and move all support declarations to the private part of the specification whenever possible.

Below, you find the selected labs that you can work on, including changes that you should make. In case you don't have a working version of the source-code of previous labs, you can look into the corresponding solutions.

8.3.1 Colors

Chapter: *Records* (page 31)

Steps:

1. Change declaration of RGB type to **`private`**.

Requirements:

1. Implementation must compile correctly and test cases must pass.

8.3.2 List of Names

Chapter: *Arrays* (page 41)

Steps:

1. Change declaration of `Person` and `People` types to **`limited private`**.
2. Move type declaration of `People_Array` to private part.

Requirements:

1. Implementation must compile correctly and test cases must pass.

8.3.3 Price List

Chapter: *More About Types* (page 59)

Steps:

1. Change declaration of `Price_List` type to **`limited private`**.

Requirements:

1. Implementation must compile correctly and test cases must pass.

CHAPTER

NINE

GENERICS

9.1 Display Array

Goal: create a generic procedure that displays the elements of an array.

Steps:

1. Implement the generic procedure `Display_Array`.

Requirements:

1. Generic procedure `Display_Array` displays the elements of an array.
    1. It uses the following scheme:
        - First, it displays a header.
        - Then, it displays the elements of the array.
    2. When displaying the elements, it must:
        - use one line per element, and
        - include the corresponding index of the array.
    3. This is the expected format:

        ```
        <HEADER>
        <index #1>: <element #1>
        <index #2>: <element #2>
        ...
        ```

    4. For example:
        - For the following code:

            ```
            procedure Test is
               A : Int_Array (1 .. 2) := (1, 5);
            begin
               Display_Int_Array ("Elements of A", A);;
            end Test;
            ```

        - The output is:

            ```
            Elements of A
             1:  1
             2:  5
            ```

2. These are the formal parameters of the procedure:
    1. a range type `T_Range` for the the array;
    2. a formal type `T_Element` for the elements of the array;

- This type must be declared in such a way that it can be mapped to any type in the instantiation — including record types.

3. an array type `T_Array` using the `T_Range` and `T_Element` types;
4. a function `Image` that converts a variable of `T_Element` type to a **`String`**.

Listing 1: display_array.ads

```
generic
procedure Display_Array (Header : String;
                         A      : T_Array);
```

Listing 2: display_array.adb

```
with Ada.Text_IO; use Ada.Text_IO;

procedure Display_Array (Header : String;
                         A      : T_Array) is
begin
   null;
end Display_Array;
```

Listing 3: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_Array;

procedure Main is
   type Test_Case_Index is (Int_Array_Chk,
                            Point_Array_Chk);

   procedure Test_Int_Array is
      type Int_Array is array (Positive range <>) of Integer;

      procedure Display_Int_Array is new
        Display_Array (T_Range => Positive,
                       T_Element => Integer,
                       T_Array   => Int_Array,
                       Image     => Integer'Image);

      A : constant Int_Array (1 .. 5) := (1, 2, 5, 7, 10);
   begin
      Display_Int_Array ("Integers", A);
   end Test_Int_Array;

   procedure Test_Point_Array is
      type Point is record
         X : Float;
         Y : Float;
      end record;

      type Point_Array is array (Natural range <>) of Point;

      function Image (P : Point) return String is
      begin
         return "(" & Float'Image (P.X)
           & ", " & Float'Image (P.Y) & ")";
      end Image;

```

(continues on next page)

(continued from previous page)

```
38       procedure Display_Point_Array is new
39         Display_Array (T_Range   => Natural,
40                        T_Element => Point,
41                        T_Array   => Point_Array,
42                        Image     => Image);
43
44       A : constant Point_Array (0 .. 3) := ((1.0, 0.5), (2.0, -0.5),
45                                             (5.0, 2.0), (-0.5, 2.0));
46    begin
47       Display_Point_Array ("Points", A);
48    end Test_Point_Array;
49
50    procedure Check (TC : Test_Case_Index) is
51    begin
52       case TC is
53          when Int_Array_Chk =>
54             Test_Int_Array;
55          when Point_Array_Chk =>
56             Test_Point_Array;
57       end case;
58    end Check;
59
60 begin
61    if Argument_Count < 1 then
62       Put_Line ("ERROR: missing arguments! Exiting...");
63       return;
64    elsif Argument_Count > 1 then
65       Put_Line ("Ignoring additional arguments...");
66    end if;
67
68    Check (Test_Case_Index'Value (Argument (1)));
69 end Main;
```

9.2 Average of Array of Float

Goal: create a generic function that calculates the average of an array of floating-point elements.

Steps:

1. Declare and implement the generic function `Average`.

Requirements:

1. Generic function `Average` calculates the average of an array containing floating-point values of arbitrary precision.
2. Generic function `Average` must contain the following formal parameters:
    1. a range type `T_Range` for the array;
    2. a formal type `T_Element` that can be mapped to floating-point types of arbitrary precision;
    3. an array type `T_Array` using `T_Range` and `T_Element`;

Remarks:

1. You should use the `Float` type for the accumulator.

Listing 4: average.ads

```
generic
function Average (A : T_Array) return T_Element;
```

Listing 5: average.adb

```
function Average (A : T_Array) return T_Element is
begin
   return 0.0;
end Average;
```

Listing 6: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Average;

procedure Main is
   type Test_Case_Index is (Float_Array_Chk,
                            Digits_7_Float_Array_Chk);

   procedure Test_Float_Array is
      type Float_Array is array (Positive range <>) of Float;

      function Average_Float is new
        Average (T_Range   => Positive,
                 T_Element => Float,
                 T_Array   => Float_Array);

      A : constant Float_Array (1 .. 5) := (1.0, 3.0, 5.0, 7.5, -12.5);
   begin
      Put_Line ("Average: " & Float'Image (Average_Float (A)));
   end Test_Float_Array;

   procedure Test_Digits_7_Float_Array is
      type Custom_Float is digits 7 range 0.0 .. 1.0;

      type Float_Array is
        array (Integer range <>) of Custom_Float;

      function Average_Float is new
        Average (T_Range   => Integer,
                 T_Element => Custom_Float,
                 T_Array   => Float_Array);

      A : constant Float_Array (-1 .. 3) := (0.5, 0.0, 1.0, 0.6, 0.5);
   begin
      Put_Line ("Average: "
                & Custom_Float'Image (Average_Float (A)));
   end Test_Digits_7_Float_Array;

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Float_Array_Chk =>
            Test_Float_Array;
         when Digits_7_Float_Array_Chk =>
            Test_Digits_7_Float_Array;
      end case;
```

(continues on next page)

(continued from previous page)

```
48    end Check;
49
50 begin
51    if Argument_Count < 1 then
52       Put_Line ("ERROR: missing arguments! Exiting...");
53       return;
54    elsif Argument_Count > 1 then
55       Put_Line ("Ignoring additional arguments...");
56    end if;
57
58    Check (Test_Case_Index'Value (Argument (1)));
59 end Main;
```

9.3 Average of Array of Any Type

Goal: create a generic function that calculates the average of an array of elements of any arbitrary type.

Steps:

1. Declare and implement the generic function `Average`.
2. Implement the test procedure `Test_Item`.
    1. Declare the `F_IO` package.
    2. Implement the `Get_Total` function for the `Item` type.
    3. Implement the `Get_Price` function for the `Item` type.
    4. Declare the `Average_Total` function.
    5. Declare the `Average_Price` function.

Requirements:

1. Generic function `Average` calculates the average of an array containing elements of any arbitrary type.
2. Generic function `Average` has the same formal parameters as in the previous exercise, except for:
    1. `T_Element`, which is now a formal type that can be mapped to any arbitrary type.
    2. `To_Float`, which is an *additional* formal parameter.
        - `To_Float` is a function that converts the arbitrary element of `T_Element` type to the **`Float`** type.
3. Procedure `Test_Item` is used to test the generic `Average` procedure for a record type (`Item`).
    1. Record type `Item` contains the `Quantity` and `Price` components.
4. The following functions have to implemented to be used for the formal `To_Float` function parameter:
    1. For the `Decimal` type, the function is pretty straightforward: it simply returns the floating-point value converted from the decimal type.
    2. For the `Item` type, two functions must be created to convert to floating-point type:
        1. `Get_Total`, which returns the multiplication of the quantity and the price components of the `Item` type;
        2. `Get_Price`, which returns just the price.

5. The generic function `Average` must be instantiated as follows:
    1. For the `Item` type, you must:
        1. declare the `Average_Total` function (as an instance of `Average`) using the `Get_Total` for the `To_Float` parameter;
        2. declare the `Average_Price` function (as an instance of `Average`) using the `Get_Price` for the `To_Float` parameter.
6. You must use the `Put` procedure from `Ada.Text_IO.Float_IO`.
    1. The generic standard package `Ada.Text_IO.Float_IO` must be instantiated as `F_IO` in the test procedures.
    2. This is the specification of the `Put` procedure, as described in the appendix A.10.9 of the Ada Reference Manual:

```
procedure Put(Item : in Num;
              Fore : in Field := Default_Fore;
              Aft  : in Field := Default_Aft;
              Exp  : in Field := Default_Exp);
```

    3. This is the expected format when calling `Put` from `Float_IO`:

Function	Fore	Aft	Exp
Test_Item	3	2	0

Remarks:

1. In this exercise, you'll abstract the `Average` function from the previous exercises a step further.
    1. In this case, the function shall be able to calculate the average of any arbitrary type — including arrays containing elements of record types.
    2. Since record types can be composed by many components of different types, we need to provide a way to indicate which component (or components) of the record will be used when calculating the average of the array.
    3. This problem is solved by specifying a `To_Float` function as a formal parameter, which converts the arbitrary element of `T_Element` type to the **`Float`** type.
    4. In the implementation of the `Average` function, we use the `To_Float` function and calculate the average using a floating-point variable.

Listing 7: average.ads

```
generic
function Average (A : T_Array) return Float;
```

Listing 8: average.adb

```
function Average (A : T_Array) return Float is
begin
   null;
end Average;
```

Listing 9: test_item.ads

```
procedure Test_Item;
```

Listing 10: test_item.adb

```
with Ada.Text_IO;      use Ada.Text_IO;

with Average;

procedure Test_Item is
   type Amount is delta 0.01 digits 12;

   type Item is record
      Quantity : Natural;
      Price    : Amount;
   end record;

   type Item_Array is
     array (Positive range <>) of Item;

   A : constant Item_Array (1 .. 4)
     := ((Quantity =>  5,   Price => 10.00),
         (Quantity => 80,   Price =>  2.50),
         (Quantity => 40,   Price =>  5.00),
         (Quantity => 20,   Price => 12.50));

begin
   Put ("Average per item & quantity: ");
   F_IO.Put (Average_Total (A));
   New_Line;

   Put ("Average price:               ");
   F_IO.Put (Average_Price (A));
   New_Line;
end Test_Item;
```

Listing 11: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Test_Item;

procedure Main is
   type Test_Case_Index is (Item_Array_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Item_Array_Chk =>
            Test_Item;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

9.4 Generic list

Goal: create a system based on a generic list to add and displays elements.

Steps:

1. Declare and implement the generic package `Gen_List`.
    1. Implement the `Init` procedure.
    2. Implement the `Add` procedure.
    3. Implement the `Display` procedure.

Requirements:

1. Generic package `Gen_List` must have the following subprograms:
    1. Procedure `Init` initializes the list.
    2. Procedure `Add` adds an item to the list.
        1. This procedure must contain a `Status` output parameter that is set to **`False`** when the list was full — i.e. if the procedure failed while trying to add the item;
    3. Procedure `Display` displays the complete list.
        1. This includes the *name* of the list and its elements — using one line per element.
        2. This is the expected format:

```
<NAME>
<element #1>
<element #2>
...
```

2. Generic package `Gen_List` has these formal parameters:
    1. an arbitrary formal type `Item`;
    2. an unconstrained array type `Items` of `Item` element with positive range;
    3. the `Name` parameter containing the name of the list;
        - This must be a formal input object of **`String`** type.
        - It must be used in the `Display` procedure.
    4. an actual array `List_Array` to store the list;
        - This must be a formal **`in out`** object of `Items` type.
    5. the variable `Last` to store the index of the last element;
        - This must be a formal **`in out`** object of **`Natural`** type.
    6. a procedure `Put` for the `Item` type.
        - This procedure is used in the `Display` procedure to display individual elements of the list.
3. The test procedure `Test_Int` is used to test a list of elements of **`Integer`** type.
4. For both test procedures, you must:
    1. add missing type declarations;
    2. declare and implement a `Put` procedure for individual elements of the list;
    3. declare instances of the `Gen_List` package.
        - For the `Test_Int` procedure, declare the `Int_List` package.

Remarks:

1. In previous labs, you've been implementing lists for a variety of types.
   - The *List of Names* exercise from the *Arrays* (page 41) labs is an example.
   - In this exercise, you have to abstract those implementations to create the generic `Gen_List` package.

Listing 12: gen_list.ads

```
generic
package Gen_List is

   procedure Init;

   procedure Add (I      :     Item;
                  Status : out Boolean);

   procedure Display;

end Gen_List;
```

Listing 13: gen_list.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Gen_List is

   procedure Init is
   begin
      null;
   end Init;

   procedure Add (I      :     Item;
                  Status : out Boolean) is
   begin
      null;
   end Add;

   procedure Display is
   begin
      null;
   end Display;

end Gen_List;
```

Listing 14: test_int.ads

```
procedure Test_Int;
```

Listing 15: test_int.adb

```
with Ada.Text_IO; use Ada.Text_IO;

with Gen_List;

procedure Test_Int is

   type Integer_Array is array (Positive range <>) of Integer;

   A : Integer_Array (1 .. 3);
```

(continues on next page)

(continued from previous page)

```
   L : Natural;

   Success : Boolean;

   procedure Display_Add_Success (Success : Boolean) is
   begin
      if Success then
         Put_Line ("Added item successfully!");
      else
         Put_Line ("Couldn't add item!");
      end if;

   end Display_Add_Success;

begin
   Int_List.Init;

   Int_List.Add (2, Success);
   Display_Add_Success (Success);

   Int_List.Add (5, Success);
   Display_Add_Success (Success);

   Int_List.Add (7, Success);
   Display_Add_Success (Success);

   Int_List.Add (8, Success);
   Display_Add_Success (Success);

   Int_List.Display;
end Test_Int;
```

Listing 16: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Test_Int;

procedure Main is
   type Test_Case_Index is (Int_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Int_Chk =>
            Test_Int;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

CHAPTER

TEN

EXCEPTIONS

10.1 Uninitialized Value

Goal: implement an enumeration to avoid the use of uninitialized values.

Steps:

1. Implement the `Options` package.
    1. Declare the `Option` enumeration type.
    2. Declare the `Uninitialized_Value` exception.
    3. Implement the `Image` function.

Requirements:

1. Enumeration `Option` contains:
    1. the `Uninitialized` value, and
    2. the actual options:
        - `Option_1`,
        - `Option_2`,
        - `Option_3`.
2. Function `Image` returns a string for the `Option` type.
    1. In case the argument to `Image` is `Uninitialized`, the function must raise the `Uninitialized_Value` exception.

Remarks:

1. In this exercise, we employ exceptions as a mechanism to avoid the use of uninitialized values for a certain type.

Listing 1: options.ads

```
package Options is

   --  Declare the Option enumeration type!
   type Option is null record;

   function Image (O : Option) return String;

end Options;
```

Listing 2: options.adb

```
package body Options is

   function Image (O : Option) return String is
   begin
      return "";
   end Image;

end Options;
```

Listing 3: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;
with Ada.Exceptions;   use Ada.Exceptions;

with Options;          use Options;

procedure Main is
   type Test_Case_Index is
     (Options_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check (O : Option) is
      begin
         Put_Line (Image (O));
      exception
         when E : Uninitialized_Value =>
            Put_Line (Exception_Message (E));
      end Check;

   begin
      case TC is
      when Options_Chk =>
         for O in Option loop
            Check (O);
         end loop;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

10.2 Numerical Exception

Goal: handle numerical exceptions in a test procedure.

Steps:

1. Add exception handling to the `Check_Exception` procedure.

Requirements:

1. The test procedure `Num_Exception_Test` from the `Tests` package below must be used in the implementation of `Check_Exception`.
2. The `Check_Exception` procedure must be extended to handle exceptions as follows:
    1. If the exception raised by `Num_Exception_Test` is `Constraint_Error`, the procedure must display the message "Constraint_Error detected!" to the user.
    2. Otherwise, it must display the message associated with the exception.

Remarks:

1. You can use the `Exception_Message` function to retrieve the message associated with an exception.

Listing 4: tests.ads

```
package Tests is

   type Test_ID is (Test_1, Test_2);

   Custom_Exception : exception;

   procedure Num_Exception_Test (ID : Test_ID);

end Tests;
```

Listing 5: tests.adb

```
package body Tests is

   pragma Warnings (Off, "variable ""C"" is assigned but never read");

   procedure Num_Exception_Test (ID : Test_ID) is
      A, B, C : Integer;
   begin
      case ID is
         when Test_1 =>
            A := Integer'Last;
            B := Integer'Last;
            C := A + B;
         when Test_2 =>
            raise Custom_Exception with "Custom_Exception raised!";
      end case;
   end Num_Exception_Test;

   pragma Warnings (On, "variable ""C"" is assigned but never read");

end Tests;
```

Listing 6: check_exception.adb

```
with Tests; use Tests;

procedure Check_Exception (ID : Test_ID) is
begin
   Num_Exception_Test (ID);
end Check_Exception;
```

Listing 7: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;
```

(continues on next page)

(continued from previous page)

```
with Ada.Exceptions;   use Ada.Exceptions;

with Tests;            use Tests;
with Check_Exception;

procedure Main is
   type Test_Case_Index is
     (Exception_1_Chk,
      Exception_2_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Handle_Exception (ID : Test_ID) is
      begin
         Check_Exception (ID);
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error"
                      & " (raised by Check_Exception) detected!");
         when E : others =>
            Put_Line (Exception_Name (E)
                      & " (raised by Check_Exception) detected!");
      end Check_Handle_Exception;

   begin
      case TC is
      when Exception_1_Chk =>
         Check_Handle_Exception (Test_1);
      when Exception_2_Chk =>
         Check_Handle_Exception (Test_2);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

10.3 Re-raising Exceptions

Goal: make use of exception re-raising in a test procedure.

Steps:

1. Declare new exception: `Another_Exception`.
2. Add exception re-raise to the `Check_Exception` procedure.

Requirements:

1. Exception `Another_Exception` must be declared in the `Tests` package.
2. Procedure `Check_Exception` must be extended to *re-raise* any exception. When an exception is detected, the procedure must:
    1. display a user message (as implemented in the previous exercise), and then

2. Raise or *re-raise* exception depending on the exception that is being handled:
    1. In case of `Constraint_Error` exception, *re-raise* the exception.
    2. In all other cases, raise `Another_Exception`.

Remarks:

1. In this exercise, you should extend the implementation of the `Check_Exception` procedure from the previous exercise.
    1. Naturally, you can use the code for the `Check_Exception` procedure from the previous exercise as a starting point.

Listing 8: tests.ads

```
package Tests is

   type Test_ID is (Test_1, Test_2);

   Custom_Exception : exception;

   procedure Num_Exception_Test (ID : Test_ID);

end Tests;
```

Listing 9: tests.adb

```
package body Tests is

   pragma Warnings (Off, "variable ""C"" is assigned but never read");

   procedure Num_Exception_Test (ID : Test_ID) is
      A, B, C : Integer;
   begin
      case ID is
         when Test_1 =>
            A := Integer'Last;
            B := Integer'Last;
            C := A + B;
         when Test_2 =>
            raise Custom_Exception with "Custom_Exception raised!";
      end case;
   end Num_Exception_Test;

   pragma Warnings (On, "variable ""C"" is assigned but never read");

end Tests;
```

Listing 10: check_exception.ads

```
with Tests; use Tests;

procedure Check_Exception (ID : Test_ID);
```

Listing 11: check_exception.adb

```
procedure Check_Exception (ID : Test_ID) is
begin
   Num_Exception_Test (ID);
end Check_Exception;
```

Listing 12: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;
with Ada.Exceptions;   use Ada.Exceptions;

with Tests;            use Tests;
with Check_Exception;

procedure Main is
   type Test_Case_Index is
     (Exception_1_Chk,
      Exception_2_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Handle_Exception (ID : Test_ID) is
      begin
         Check_Exception (ID);
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error"
                      & " (raised by Check_Exception) detected!");
         when E : others =>
            Put_Line (Exception_Name (E)
                      & " (raised by Check_Exception) detected!");
      end Check_Handle_Exception;

   begin
      case TC is
      when Exception_1_Chk =>
         Check_Handle_Exception (Test_1);
      when Exception_2_Chk =>
         Check_Handle_Exception (Test_2);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

CHAPTER

ELEVEN

TASKING

11.1 Display Service

Goal: create a simple service that displays messages to the user.

Steps:

1. Implement the `Display_Services` package.
    1. Declare the task type `Display_Service`.
    2. Implement the `Display` entry for strings.
    3. Implement the `Display` entry for integers.

Requirements:

1. Task type `Display_Service` uses the `Display` entry to display messages to the user.
2. There are two versions of the `Display` entry:
    1. One that receives messages as a string parameter.
    2. One that receives messages as an `Integer` parameter.
3. When a message is received via a `Display` entry, it must be displayed immediately to the user.

Listing 1: display_services.ads

```
package Display_Services is

end Display_Services;
```

Listing 2: display_services.adb

```
package body Display_Services is

end Display_Services;
```

Listing 3: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_Services; use Display_Services;

procedure Main is
   type Test_Case_Index is (Display_Service_Chk);

   procedure Check (TC : Test_Case_Index) is
      Display : Display_Service;
```

(continues on next page)

(continued from previous page)

```
   begin
      case TC is
         when Display_Service_Chk =>
            Display.Display ("Hello");
            delay 0.5;
            Display.Display ("Hello again");
            delay 0.5;
            Display.Display (55);
            delay 0.5;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

11.2 Event Manager

Goal: implement a simple event manager.

Steps:

1. Implement the `Event_Managers` package.
    1. Declare the task type `Event_Manager`.
    2. Implement the `Start` entry.
    3. Implement the `Event` entry.

Requirements:

1. The event manager has a similar behavior as an alarm
    1. The sole purpose of this event manager is to display the event ID at the correct time.
    2. After the event ID is displayed, the task must finish.
2. The event manager (`Event_Manager` type) must have two entries:
    1. `Start`, which starts the event manager with an event ID;
    2. `Event`, which delays the task until a certain time and then displays the event ID as a user message.
3. The format of the user message displayed by the event manager is `Event #<event_id>`.
    1. You should use `Natural'Image` to display the ID (as indicated in the body of the `Event_Managers` package below).

Remarks:

1. In the `Start` entry, you can use the `Natural` type for the ID.
2. In the `Event` entry, you should use the `Time` type from the `Ada.Real_Time` package for the time parameter.

3. Note that the test application below creates an array of event managers with different delays.

Listing 4: event_managers.ads

```
package Event_Managers is

end Event_Managers;
```

Listing 5: event_managers.adb

```
package body Event_Managers is

      --   Don't forget to display the event ID:
      --
      --   Put_Line ("Event #" & Natural'Image (Event_ID));

end Event_Managers;
```

Listing 6: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Event_Managers;   use Event_Managers;
with Ada.Real_Time;    use Ada.Real_Time;

procedure Main is
   type Test_Case_Index is (Event_Manager_Chk);

   procedure Check (TC : Test_Case_Index) is
      Ev_Mng : array (1 .. 5) of Event_Manager;
   begin
      case TC is
         when Event_Manager_Chk =>
            for I in Ev_Mng'Range loop
               Ev_Mng (I).Start (I);
            end loop;
            Ev_Mng (1).Event (Clock + Seconds (5));
            Ev_Mng (2).Event (Clock + Seconds (3));
            Ev_Mng (3).Event (Clock + Seconds (1));
            Ev_Mng (4).Event (Clock + Seconds (2));
            Ev_Mng (5).Event (Clock + Seconds (4));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

11.3 Generic Protected Queue

Goal: create a queue container using a protected type.

Steps:

1. Implement the generic package `Gen_Queues`.
    1. Declare the protected type `Queue`.
    2. Implement the `Empty` function.
    3. Implement the `Full` function.
    4. Implement the `Push` entry.
    5. Implement the `Pop` entry.

Requirements:

1. These are the formal parameters for the generic package `Gen_Queues`:
    1. a formal modular type;
        - This modular type should be used by the `Queue` to declare an array that stores the elements of the queue.
        - The modulus of the modular type must correspond to the maximum number of elements of the queue.
    2. the data type of the elements of the queue.
        - Select a formal parameter that allows you to store elements of any data type in the queue.
2. These are the operations of the `Queue` type:
    1. Function `Empty` indicates whether the queue is empty.
    2. Function `Full` indicates whether the queue is full.
    3. Entry `Push` stores an element in the queue.
    4. Entry `Pop` removes an element from the queue and returns the element via output parameter.

Remarks:

1. In this exercise, we create a queue container by declaring and implementing a protected type (`Queue`) as part of a generic package (`Gen_Queues`).
2. As a bonus exercise, you can analyze the body of the `Queue_Tests` package and understand how the `Queue` type is used there.
    1. In particular, the procedure `Concurrent_Test` implements two tasks: `T_Producer` and `T_Consumer`. They make use of the queue concurrently.

Listing 7: gen_queues.ads

```
1 package Gen_Queues is
2
3 end Gen_Queues;
```

Listing 8: gen_queues.adb

```
1 package body Gen_Queues is
2
3 end Gen_Queues;
```

Listing 9: queue_tests.ads

```
package Queue_Tests is

   procedure Simple_Test;

   procedure Concurrent_Test;

end Queue_Tests;
```

Listing 10: queue_tests.adb

```
with Ada.Text_IO; use Ada.Text_IO;

with Gen_Queues;

package body Queue_Tests is

   Max : constant := 10;
   type Queue_Mod is mod Max;

   procedure Simple_Test is
      package Queues_Float is new Gen_Queues (Queue_Mod, Float);

      Q_F : Queues_Float.Queue;
      V   : Float;
   begin
      V := 10.0;
      while not Q_F.Full loop
         Q_F.Push (V);
         V := V + 1.5;
      end loop;

      while not Q_F.Empty loop
         Q_F.Pop (V);
         Put_Line ("Value from queue: " & Float'Image (V));
      end loop;
   end Simple_Test;

   procedure Concurrent_Test is
      package Queues_Integer is new Gen_Queues (Queue_Mod, Integer);

      Q_I : Queues_Integer.Queue;

      task T_Producer;
      task T_Consumer;

      task body T_Producer is
         V : Integer := 100;
      begin
         for I in 1 .. 2 * Max loop
            Q_I.Push (V);
            V := V + 1;
         end loop;
      end T_Producer;

      task body T_Consumer is
         V : Integer;
      begin
         delay 1.5;

```

(continues on next page)

(continued from previous page)

```
50          while not Q_I.Empty loop
51             Q_I.Pop (V);
52             Put_Line ("Value from queue: " & Integer'Image (V));
53             delay 0.2;
54          end loop;
55       end T_Consumer;
56    begin
57       null;
58    end Concurrent_Test;
59
60 end Queue_Tests;
```

Listing 11: main.adb

```
1  with Ada.Command_Line; use Ada.Command_Line;
2  with Ada.Text_IO;      use Ada.Text_IO;
3
4  with Queue_Tests;      use Queue_Tests;
5
6  procedure Main is
7     type Test_Case_Index is (Simple_Queue_Chk,
8                              Concurrent_Queue_Chk);
9
10    procedure Check (TC : Test_Case_Index) is
11
12    begin
13       case TC is
14          when Simple_Queue_Chk =>
15             Simple_Test;
16          when Concurrent_Queue_Chk =>
17             Concurrent_Test;
18       end case;
19    end Check;
20
21 begin
22    if Argument_Count < 1 then
23       Put_Line ("ERROR: missing arguments! Exiting...");
24       return;
25    elsif Argument_Count > 1 then
26       Put_Line ("Ignoring additional arguments...");
27    end if;
28
29    Check (Test_Case_Index'Value (Argument (1)));
30 end Main;
```

CHAPTER

TWELVE

DESIGN BY CONTRACTS

12.1 Price Range

Goal: use predicates to indicate the correct range of prices.

Steps:

1. Complete the `Prices` package.
    1. Rewrite the type declaration of `Price`.

Requirements:

1. Type `Price` must use a predicate instead of a range.

Remarks:

1. As discussed in the course, ranges are a form of contract.
    1. For example, the subtype `Price` below indicates that a value of this subtype must always be positive:

        ```
        subtype Price is Amount range 0.0 .. Amount'Last;
        ```

    2. Interestingly, you can replace ranges by predicates, which is the goal of this exercise.

Listing 1: prices.ads

```
package Prices is

   type Amount is delta 10.0 ** (-2) digits 12;

   subtype Price is Amount range 0.0 .. Amount'Last;

end Prices;
```

Listing 2: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;
with System.Assertions; use System.Assertions;

with Prices;            use Prices;

procedure Main is

   type Test_Case_Index is
     (Price_Range_Chk);

   procedure Check (TC : Test_Case_Index) is
```

(continues on next page)

(continued from previous page)

```
13
14          procedure Check_Range (A : Amount) is
15             P : constant Price := A;
16          begin
17             Put_Line ("Price: " & Price'Image (P));
18          end Check_Range;
19
20       begin
21          case TC is
22          when Price_Range_Chk =>
23             Check_Range (-2.0);
24          end case;
25       exception
26          when Constraint_Error =>
27             Put_Line ("Constraint_Error detected (NOT as expected).");
28          when Assert_Failure =>
29             Put_Line ("Assert_Failure detected (as expected).");
30       end Check;
31
32    begin
33       if Argument_Count < 1 then
34          Put_Line ("ERROR: missing arguments! Exiting...");
35          return;
36       elsif Argument_Count > 1 then
37          Put_Line ("Ignoring additional arguments...");
38       end if;
39
40       Check (Test_Case_Index'Value (Argument (1)));
41    end Main;
```

12.2 Pythagorean Theorem: Predicate

Goal: use the Pythagorean theorem as a predicate.

Steps:

1. Complete the `Triangles` package.
    1. Add a predicate to the `Right_Triangle` type.

Requirements:

1. The `Right_Triangle` type must use the Pythagorean theorem as a predicate to ensure that its components are consistent.

Remarks:

1. As you probably remember, the Pythagoras' theorem[2] states that the square of the hypotenuse of a right triangle is equal to the sum of the squares of the other two sides.

Listing 3: triangles.ads

```
1  package Triangles is
2
3     subtype Length is Integer;
4
5     type Right_Triangle is record
6        H      : Length := 0;
7        --  Hypotenuse
```

(continues on next page)

[2] https://en.wikipedia.org/wiki/Pythagorean_theorem

(continued from previous page)

```
      C1, C2 : Length := 0;
      --  Catheti / legs
   end record;

   function Init (H, C1, C2 : Length) return Right_Triangle is
     ((H, C1, C2));

end Triangles;
```

Listing 4: triangles-io.ads

```
package Triangles.IO is

   function Image (T : Right_Triangle) return String;

end Triangles.IO;
```

Listing 5: triangles-io.adb

```
package body Triangles.IO is

   function Image (T : Right_Triangle) return String is
     ("("    & Length'Image (T.H)
      & ", " & Length'Image (T.C1)
      & ", " & Length'Image (T.C2)
      & ")");

end Triangles.IO;
```

Listing 6: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;
with System.Assertions; use System.Assertions;

with Triangles;         use Triangles;
with Triangles.IO;      use Triangles.IO;

procedure Main is

   type Test_Case_Index is
     (Triangle_8_6_Pass_Chk,
      Triangle_8_6_Fail_Chk,
      Triangle_10_24_Pass_Chk,
      Triangle_10_24_Fail_Chk,
      Triangle_18_24_Pass_Chk,
      Triangle_18_24_Fail_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Triangle (H, C1, C2 : Length) is
         T : Right_Triangle;
      begin
         T := Init (H, C1, C2);
         Put_Line (Image (T));
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error detected (NOT as expected).");
         when Assert_Failure =>
            Put_Line ("Assert_Failure detected (as expected).");
```

(continues on next page)

(continued from previous page)

```
      end Check_Triangle;

   begin
      case TC is
         when Triangle_8_6_Pass_Chk   => Check_Triangle (10,  8,  6);
         when Triangle_8_6_Fail_Chk   => Check_Triangle (12,  8,  6);
         when Triangle_10_24_Pass_Chk => Check_Triangle (26, 10, 24);
         when Triangle_10_24_Fail_Chk => Check_Triangle (12, 10, 24);
         when Triangle_18_24_Pass_Chk => Check_Triangle (30, 18, 24);
         when Triangle_18_24_Fail_Chk => Check_Triangle (32, 18, 24);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

12.3 Pythagorean Theorem: Precondition

Goal: use the Pythagorean theorem as a precondition.

Steps:

1. Complete the `Triangles` package.
    1. Add a precondition to the `Init` function.

Requirements:

1. The `Init` function must use the Pythagorean theorem as a precondition to ensure that the input values are consistent.

Remarks:

1. In this exercise, you'll work again with the `Right_Triangle` type.
    1. This time, your job is to use a precondition instead of a predicate.
    2. The precondition is applied to the `Init` function, not to the `Right_Triangle` type.

Listing 7: triangles.ads

```
package Triangles is

   subtype Length is Integer;

   type Right_Triangle is record
      H      : Length := 0;
      --  Hypotenuse
      C1, C2 : Length := 0;
      --  Catheti / legs
   end record;

   function Init (H, C1, C2 : Length) return Right_Triangle is
     ((H, C1, C2));
```

(continues on next page)

(continued from previous page)

```
14
15 end Triangles;
```

Listing 8: triangles-io.ads

```
1  package Triangles.IO is
2
3     function Image (T : Right_Triangle) return String;
4
5  end Triangles.IO;
```

Listing 9: triangles-io.adb

```
1  package body Triangles.IO is
2
3     function Image (T : Right_Triangle) return String is
4       ("("    & Length'Image (T.H)
5        & ", " & Length'Image (T.C1)
6        & ", " & Length'Image (T.C2)
7        & ")");
8
9  end Triangles.IO;
```

Listing 10: main.adb

```
1  with Ada.Command_Line;  use Ada.Command_Line;
2  with Ada.Text_IO;       use Ada.Text_IO;
3  with System.Assertions; use System.Assertions;
4
5  with Triangles;         use Triangles;
6  with Triangles.IO;      use Triangles.IO;
7
8  procedure Main is
9
10    type Test_Case_Index is
11      (Triangle_8_6_Pass_Chk,
12       Triangle_8_6_Fail_Chk,
13       Triangle_10_24_Pass_Chk,
14       Triangle_10_24_Fail_Chk,
15       Triangle_18_24_Pass_Chk,
16       Triangle_18_24_Fail_Chk);
17
18    procedure Check (TC : Test_Case_Index) is
19
20       procedure Check_Triangle (H, C1, C2 : Length) is
21          T : Right_Triangle;
22       begin
23          T := Init (H, C1, C2);
24          Put_Line (Image (T));
25       exception
26          when Constraint_Error =>
27             Put_Line ("Constraint_Error detected (NOT as expected).");
28          when Assert_Failure =>
29             Put_Line ("Assert_Failure detected (as expected).");
30       end Check_Triangle;
31
32    begin
33       case TC is
34          when Triangle_8_6_Pass_Chk   => Check_Triangle (10,  8,  6);
35          when Triangle_8_6_Fail_Chk   => Check_Triangle (12,  8,  6);
```

(continues on next page)

(continued from previous page)

```
36          when Triangle_10_24_Pass_Chk => Check_Triangle (26, 10, 24);
37          when Triangle_10_24_Fail_Chk => Check_Triangle (12, 10, 24);
38          when Triangle_18_24_Pass_Chk => Check_Triangle (30, 18, 24);
39          when Triangle_18_24_Fail_Chk => Check_Triangle (32, 18, 24);
40       end case;
41    end Check;
42
43 begin
44    if Argument_Count < 1 then
45       Put_Line ("ERROR: missing arguments! Exiting...");
46       return;
47    elsif Argument_Count > 1 then
48       Put_Line ("Ignoring additional arguments...");
49    end if;
50
51    Check (Test_Case_Index'Value (Argument (1)));
52 end Main;
```

12.4 Pythagorean Theorem: Postcondition

Goal: use the Pythagorean theorem as a postcondition.

Steps:

1. Complete the `Triangles` package.
    1. Add a postcondition to the `Init` function.

Requirements:

1. The `Init` function must use the Pythagorean theorem as a postcondition to ensure that the returned object is consistent.

Remarks:

1. In this exercise, you'll work again with the `Triangles` package.
    1. This time, your job is to apply a postcondition instead of a precondition to the `Init` function.

Listing 11: triangles.ads

```
1  package Triangles is
2
3     subtype Length is Integer;
4
5     type Right_Triangle is record
6        H      : Length := 0;
7        --  Hypotenuse
8        C1, C2 : Length := 0;
9        --  Catheti / legs
10    end record;
11
12    function Init (H, C1, C2 : Length) return Right_Triangle is
13      ((H, C1, C2));
14
15 end Triangles;
```

Listing 12: triangles-io.ads

```
package Triangles.IO is

   function Image (T : Right_Triangle) return String;

end Triangles.IO;
```

Listing 13: triangles-io.adb

```
package body Triangles.IO is

   function Image (T : Right_Triangle) return String is
     ("("    & Length'Image (T.H)
      & ", " & Length'Image (T.C1)
      & ", " & Length'Image (T.C2)
      & ")");

end Triangles.IO;
```

Listing 14: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;
with System.Assertions; use System.Assertions;

with Triangles;         use Triangles;
with Triangles.IO;      use Triangles.IO;

procedure Main is

   type Test_Case_Index is
     (Triangle_8_6_Pass_Chk,
      Triangle_8_6_Fail_Chk,
      Triangle_10_24_Pass_Chk,
      Triangle_10_24_Fail_Chk,
      Triangle_18_24_Pass_Chk,
      Triangle_18_24_Fail_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Triangle (H, C1, C2 : Length) is
         T : Right_Triangle;
      begin
         T := Init (H, C1, C2);
         Put_Line (Image (T));
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error detected (NOT as expected).");
         when Assert_Failure =>
            Put_Line ("Assert_Failure detected (as expected).");
      end Check_Triangle;

   begin
      case TC is
         when Triangle_8_6_Pass_Chk   => Check_Triangle (10,  8,  6);
         when Triangle_8_6_Fail_Chk   => Check_Triangle (12,  8,  6);
         when Triangle_10_24_Pass_Chk => Check_Triangle (26, 10, 24);
         when Triangle_10_24_Fail_Chk => Check_Triangle (12, 10, 24);
         when Triangle_18_24_Pass_Chk => Check_Triangle (30, 18, 24);
         when Triangle_18_24_Fail_Chk => Check_Triangle (32, 18, 24);
      end case;
```

(continues on next page)

(continued from previous page)

```
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

12.5 Pythagorean Theorem: Type Invariant

Goal: use the Pythagorean theorem as a type invariant.

Steps:

1. Complete the `Triangles` package.
    1. Add a type invariant to the `Right_Triangle` type.

Requirements:

1. `Right_Triangle` is a private type.
    1. It must use the Pythagorean theorem as a type invariant to ensure that its encapsulated components are consistent.

Remarks:

1. In this exercise, `Right_Triangle` is declared as a private type.
    1. In this case, we use a type invariant for `Right_Triangle` to check the Pythagorean theorem.
2. As a bonus, after completing the exercise, you may analyze the effect that default values have on type invariants.
    1. For example, the declaration of `Right_Triangle` uses zero as the default values of the three triangle lengths.
    2. If you replace those default values with `Length'Last`, you'll get different results.
    3. Make sure you understand why this is happening.

Listing 15: triangles.ads

```
package Triangles is

   subtype Length is Integer;

   type Right_Triangle is private;

   function Init (H, C1, C2 : Length) return Right_Triangle;

private

   type Right_Triangle is record
      H      : Length := 0;
      --  Hypotenuse
      C1, C2 : Length := 0;
```

(continues on next page)

(continued from previous page)

```
      --  Catheti / legs
   end record;

   function Init (H, C1, C2 : Length) return Right_Triangle is
     ((H, C1, C2));

end Triangles;
```

Listing 16: triangles-io.ads

```
package Triangles.IO is

   function Image (T : Right_Triangle) return String;

end Triangles.IO;
```

Listing 17: triangles-io.adb

```
package body Triangles.IO is

   function Image (T : Right_Triangle) return String is
     ("("    & Length'Image (T.H)
      & ", " & Length'Image (T.C1)
      & ", " & Length'Image (T.C2)
      & ")");

end Triangles.IO;
```

Listing 18: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;
with System.Assertions; use System.Assertions;

with Triangles;         use Triangles;
with Triangles.IO;      use Triangles.IO;

procedure Main is

   type Test_Case_Index is
     (Triangle_8_6_Pass_Chk,
      Triangle_8_6_Fail_Chk,
      Triangle_10_24_Pass_Chk,
      Triangle_10_24_Fail_Chk,
      Triangle_18_24_Pass_Chk,
      Triangle_18_24_Fail_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Triangle (H, C1, C2 : Length) is
         T : Right_Triangle;
      begin
         T := Init (H, C1, C2);
         Put_Line (Image (T));
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error detected (NOT as expected).");
         when Assert_Failure =>
            Put_Line ("Assert_Failure detected (as expected).");
      end Check_Triangle;
```

(continues on next page)

(continued from previous page)

```
31
32    begin
33       case TC is
34          when Triangle_8_6_Pass_Chk   => Check_Triangle (10,  8,  6);
35          when Triangle_8_6_Fail_Chk   => Check_Triangle (12,  8,  6);
36          when Triangle_10_24_Pass_Chk => Check_Triangle (26, 10, 24);
37          when Triangle_10_24_Fail_Chk => Check_Triangle (12, 10, 24);
38          when Triangle_18_24_Pass_Chk => Check_Triangle (30, 18, 24);
39          when Triangle_18_24_Fail_Chk => Check_Triangle (32, 18, 24);
40       end case;
41    end Check;
42
43 begin
44    if Argument_Count < 1 then
45       Put_Line ("ERROR: missing arguments! Exiting...");
46       return;
47    elsif Argument_Count > 1 then
48       Put_Line ("Ignoring additional arguments...");
49    end if;
50
51    Check (Test_Case_Index'Value (Argument (1)));
52 end Main;
```

12.6 Primary Color

Goal: extend a package for HTML colors so that it can handle primary colors.

Steps:

1. Complete the `Color_Types` package.
    1. Declare the `HTML_RGB_Color` subtype.
    2. Implement the `To_Int_Color` function.

Requirements:

1. The `HTML_Color` type is an enumeration that contains a list of HTML colors.
2. The `To_RGB_Lookup_Table` array implements a lookup-table to convert the colors into a hexadecimal value using RGB color components (i.e. `Red`, `Green` and `Blue`)
3. Function `To_Int_Color` extracts one of the RGB components of an HTML color and returns its hexadecimal value.
    1. The function has two parameters:
        - First parameter is the HTML color (`HTML_Color` type).
        - Second parameter indicates which RGB component is to be extracted from the HTML color (`HTML_RGB_Color` subtype).
    2. For example, if we call `To_Int_Color (Salmon, Red)`, the function returns #FA,
        - This is the hexadecimal value of the red component of the `Salmon` color.
        - You can find further remarks below about this color as an example.
4. The `HTML_RGB_Color` subtype is limited to the primary RGB colors components (i.e. `Red`, `Green` and `Blue`).
    1. This subtype is used to select the RGB component in calls to `To_Int_Color`.
    2. You must use a predicate in the type declaration.

Remarks:

1. In this exercise, we reuse the code of the `Colors: Lookup-Table` exercise from the *Arrays* (page 41) labs.
2. These are the hexadecimal values of the colors that we used in the original exercise:

Color	Value
Salmon	#FA8072
Firebrick	#B22222
Red	#FF0000
Darkred	#8B0000
Lime	#00FF00
Forestgreen	#228B22
Green	#008000
Darkgreen	#006400
Blue	#0000FF
Mediumblue	#0000CD
Darkblue	#00008B

3. You can extract the hexadecimal value of each primary color by splitting the values from the table above into three hexadecimal values with two digits each.
   - For example, the hexadecimal value of `Salmon` is `#FA8072`, where:
     - the first part of this hexadecimal value (`#FA`) corresponds to the red component,
     - the second part (`#80`) corresponds to the green component, and
     - the last part (`#72`) corresponds to the blue component.

Listing 19: color_types.ads

```
1  package Color_Types is
2
3     type HTML_Color is
4       (Salmon,
5        Firebrick,
6        Red,
7        Darkred,
8        Lime,
9        Forestgreen,
10       Green,
11       Darkgreen,
12       Blue,
13       Mediumblue,
14       Darkblue);
15
16    subtype Int_Color is Integer range 0 .. 255;
17
18    function Image (I : Int_Color) return String;
19
20    type RGB is record
21       Red   : Int_Color;
22       Green : Int_Color;
23       Blue  : Int_Color;
24    end record;
25
26    function To_RGB (C : HTML_Color) return RGB;
27
28    function Image (C : RGB) return String;
29
```

(continues on next page)

(continued from previous page)

```
   type HTML_Color_RGB_Array is array (HTML_Color) of RGB;

   To_RGB_Lookup_Table : constant HTML_Color_RGB_Array
     := (Salmon      => (16#FA#, 16#80#, 16#72#),
         Firebrick   => (16#B2#, 16#22#, 16#22#),
         Red         => (16#FF#, 16#00#, 16#00#),
         Darkred     => (16#8B#, 16#00#, 16#00#),
         Lime        => (16#00#, 16#FF#, 16#00#),
         Forestgreen => (16#22#, 16#8B#, 16#22#),
         Green       => (16#00#, 16#80#, 16#00#),
         Darkgreen   => (16#00#, 16#64#, 16#00#),
         Blue        => (16#00#, 16#00#, 16#FF#),
         Mediumblue  => (16#00#, 16#00#, 16#CD#),
         Darkblue    => (16#00#, 16#00#, 16#8B#));

   subtype HTML_RGB_Color is HTML_Color;

   function To_Int_Color (C : HTML_Color;
                          S : HTML_RGB_Color) return Int_Color;
   --  Convert to hexadecimal value for the selected RGB component S

end Color_Types;
```

Listing 20: color_types.adb

```
with Ada.Integer_Text_IO;

package body Color_Types is

   function To_RGB (C : HTML_Color) return RGB is
   begin
      return To_RGB_Lookup_Table (C);
   end To_RGB;

   function To_Int_Color (C : HTML_Color;
                          S : HTML_RGB_Color) return Int_Color is
   begin
      --  Implement function!
      return 0;
   end To_Int_Color;

   function Image (I : Int_Color) return String is
      subtype Str_Range is Integer range 1 .. 10;
      S : String (Str_Range);
   begin
      Ada.Integer_Text_IO.Put (To    => S,
                               Item  => I,
                               Base  => 16);
      return S;
   end Image;

   function Image (C : RGB) return String is
   begin
      return ("(Red => "      & Image (C.Red)
              & ", Green => " & Image (C.Green)
              & ", Blue => "  & Image (C.Blue)
              &")");
   end Image;

end Color_Types;
```

Listing 21: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Color_Types;      use Color_Types;

procedure Main is
   type Test_Case_Index is
     (HTML_Color_Red_Chk,
      HTML_Color_Green_Chk,
      HTML_Color_Blue_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_HTML_Colors (S : HTML_RGB_Color) is
      begin
         Put_Line ("Selected: " & HTML_RGB_Color'Image (S));
         for I in HTML_Color'Range loop
            Put_Line (HTML_Color'Image (I) & " => "
                      & Image (To_Int_Color (I, S)) & ".");
         end loop;
      end Check_HTML_Colors;

   begin
      case TC is
         when HTML_Color_Red_Chk =>
            Check_HTML_Colors (Red);
         when HTML_Color_Green_Chk =>
            Check_HTML_Colors (Green);
         when HTML_Color_Blue_Chk =>
            Check_HTML_Colors (Blue);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

CHAPTER

THIRTEEN

OBJECT-ORIENTED PROGRAMMING

13.1 Simple type extension

Goal: work with type extensions using record types containing numeric components.

Steps:

1. Implement the `Type_Extensions` package.
    1. Declare the record type `T_Float`.
    2. Declare the record type `T_Mixed`
    3. Implement the `Init` function for the `T_Float` type with a floating-point input parameter.
    4. Implement the `Init` function for the `T_Float` type with an integer input parameter.
    5. Implement the `Image` function for the `T_Float` type.
    6. Implement the `Init` function for the `T_Mixed` type with a floating-point input parameter.
    7. Implement the `Init` function for the `T_Mixed` type with an integer input parameter.
    8. Implement the `Image` function for the `T_Mixed` type.

Requirements:

1. Record type `T_Float` contains the following component:
    1. `F`, a floating-point type.
2. Record type `T_Mixed` is derived from the `T_Float` type.
    1. `T_Mixed` extends `T_Float` with the following component:
        1. `I`, an integer component.
    2. Both components must be numerically *synchronized*:
        - For example, if the floating-point component contains the value 2.0, the value of the integer component must be 2.
        - In order to simplify the implementation, you can simply use `Integer (F)` to convert a floating-point variable F to integer.
3. Function `Init` returns an object of the corresponding type (`T_Float` or `T_Mixed`).
    1. For each type, two versions of `Init` must be declared:
        1. one with a floating-point input parameter,
        2. another with an integer input parameter.
    2. The parameter to `Init` is used to initialize the record components.
4. Function `Image` returns a string for the components of the record type.

1. In case of the Image function for the T_Float type, the string must have the format "{ F => <float value> }".
   - For example, the call Image (T_Float'(Init (8.0))) should return the string "{ F => 8.00000E+00 }".
2. In case of the Image function for the T_Mixed type, the string must have the format "{ F => <float value>, I => <integer value> }".
   - For example, the call Image (T_Mixed'(Init (8.0))) should return the string "{ F => 8.00000E+00, I => 8 }".

Listing 1: type_extensions.ads

```
package Type_Extensions is

   --  Create declaration of T_Float type!
   type T_Float is null record;

   --  function Init ...

   --  function Image ...

   --  Create declaration of T_Mixed type!
   type T_Mixed is null record;

end Type_Extensions;
```

Listing 2: type_extensions.adb

```
package body Type_Extensions is

end Type_Extensions;
```

Listing 3: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Type_Extensions;  use Type_Extensions;

procedure Main is

   type Test_Case_Index is
     (Type_Extension_Chk);

   procedure Check (TC : Test_Case_Index) is
      F1, F2 : T_Float;
      M1, M2 : T_Mixed;
   begin
      case TC is
      when Type_Extension_Chk =>
         F1 := Init (2.0);
         F2 := Init (3);
         M1 := Init (4.0);
         M2 := Init (5);

         if M2 in T_Float'Class then
           Put_Line ("T_Mixed is in T_Float'Class as expected");
         end if;

         Put_Line ("F1: " & Image (F1));
```

(continues on next page)

(continued from previous page)

```
27          Put_Line ("F2: " & Image (F2));
28          Put_Line ("M1: " & Image (M1));
29          Put_Line ("M2: " & Image (M2));
30       end case;
31    end Check;
32
33 begin
34    if Argument_Count < 1 then
35       Put_Line ("ERROR: missing arguments! Exiting...");
36       return;
37    elsif Argument_Count > 1 then
38       Put_Line ("Ignoring additional arguments...");
39    end if;
40
41    Check (Test_Case_Index'Value (Argument (1)));
42 end Main;
```

13.2 Online Store

Goal: create an online store for the members of an association.

Steps:

1. Implement the `Online_Store` package.
    1. Declare the `Member` type.
    2. Declare the `Full_Member` type.
    3. Implement the `Get_Status` function for the `Member` type.
    4. Implement the `Get_Price` function for the `Member` type.
    5. Implement the `Get_Status` function for the `Full_Member` type.
    6. Implement the `Get_Price` function for the `Full_Member` type.
2. Implement the `Online_Store.Tests` child package.
    1. Implement the `Simple_Test` procedure.

Requirements:

1. Package `Online_Store` implements an online store application for the members of an association.
    1. In this association, members can have one of the following status:
        - associate member, or
        - full member.
2. Function `Get_Price` returns the correct price of an item.
    1. Associate members must pay the full price when they buy items from the online store.
    2. Full members can get a discount.
        1. The discount rate can be different for each full member — depending on factors that are irrelevant for this exercise.
3. Package `Online_Store` has following types:
    1. `Percentage` type, which represents a percentage ranging from 0.0 to 1.0.
    2. `Member` type for associate members containing following components:

- `Start`, which indicates the starting year of the membership.
  - This information is common for both associate and full members.
  - You can use the `Year_Number` type from the standard `Ada.Calendar` package for this component.

3. `Full_Member` type for full members.
   1. This type must extend the `Member` type above.
   2. It contains the following additional component:
      - `Discount`, which indicates the discount rate that the full member gets in the online store.
        - This component must be of `Percentage` type.

4. For the `Member` and `Full_Member` types, you must implement the following functions:
   1. `Get_Status`, which returns a string with the membership status.
      - The string must be `"Associate Member"` or `"Full Member"`, respectively.
   2. `Get_Price`, which returns the *adapted price* of an item — indicating the actual due amount.
      - For example, for a full member with a 10% discount rate, the actual due amount of an item with a price of 100.00 is 90.00.
      - Associated members don't get a discount, so they always pay the full price.
5. Procedure `Simple_Test` (from the `Online_Store.Tests` package) is used for testing.
   1. Based on a list of members that bought on the online store and the corresponding full price of the item, `Simple_Test` must display information about each member and the actual due amount after discounts.
   2. Information about the members must be displayed in the following format:

```
Member # <number>
Status: <status>
Since:  <year>
Due Amount:  <value>
--------
```

   3. For this exercise, `Simple_Test` must use the following list:

#	Membership status	Start (year)	Discount	Full Price
1	Associate	2010	*N/A*	250.00
2	Full	1998	10.0 %	160.00
3	Full	1987	20.0 %	400.00
4	Associate	2013	*N/A*	110.00

   4. In order to pass the tests, the information displayed by a call to `Simple_Test` must conform to the format described above.
      - You can find another example in the remarks below.

Remarks:

1. In previous labs, we could have implemented a simplified version of the system described above by simply using an enumeration type to specify the membership status. For example:

```
type Member_Status is (Associate_Member, Full_Member);
```

1. In this case, the `Get_Price` function would then evaluate the membership status and adapt the item price — assuming a fixed discount rate for all full members. This could be the corresponding function declaration:

```
type Amount is delta 10.0**(-2) digits 10;

function Get_Price (M : Member_Status;
                    P : Amount) return Amount;
```

2. In this exercise, however, we'll use type extension to represent the membership status in our application.

2. For the procedure `Simple_Test`, let's consider the following list of members as an example:

#	Membership status	Start (year)	Discount	Full Price
1	Associate	2002	*N/A*	100.00
2	Full	2005	10.0 %	100.00

- For this list, the test procedure displays the following information (in this exact format):

```
Member # 1
Status: Associate Member
Since:  2002
Due Amount:  100.00
--------
Member # 2
Status: Full Member
Since:  2005
Due Amount:  90.00
--------
```

- Here, although both members had the same full price (as indicated by the last column), member #2 gets a reduced due amount of 90.00 because of the full membership status.

Listing 4: online_store.ads

```
1  with Ada.Calendar; use Ada.Calendar;
2
3  package Online_Store is
4
5     type Amount is delta 10.0**(-2) digits 10;
6
7     subtype Percentage is Amount range 0.0 .. 1.0;
8
9     --  Create declaration of Member type!
10    --
11    --  You can use Year_Number from Ada.Calendar for the membership
12    --  starting year.
13    --
14    type Member is null record;
15
16    function Get_Status (M : Member) return String;
17
18    function Get_Price (M : Member;
19                        P : Amount) return Amount;
20
21    --  Create declaration of Full_Member type!
22    --
```

(continues on next page)

(continued from previous page)

```
   --  Use the Percentage type for storing the membership discount.
   --
   type Full_Member is null record;

   function Get_Status (M : Full_Member) return String;

   function Get_Price (M : Full_Member;
                       P : Amount) return Amount;

end Online_Store;
```

Listing 5: online_store.adb

```
package body Online_Store is

   function Get_Status (M : Member) return String is
     ("");

   function Get_Status (M : Full_Member) return String is
     ("");

   function Get_Price (M : Member;
                       P : Amount) return Amount is (0.0);

   function Get_Price (M : Full_Member;
                       P : Amount) return Amount is
     (0.0);

end Online_Store;
```

Listing 6: online_store-tests.ads

```
package Online_Store.Tests is

   procedure Simple_Test;

end Online_Store.Tests;
```

Listing 7: online_store-tests.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Online_Store.Tests is

   procedure Simple_Test is
   begin
      null;
   end Simple_Test;

end Online_Store.Tests;
```

Listing 8: main.adb

```
with Ada.Command_Line;   use Ada.Command_Line;
with Ada.Text_IO;        use Ada.Text_IO;

with Online_Store;       use Online_Store;
with Online_Store.Tests; use Online_Store.Tests;

procedure Main is
```

(continues on next page)

(continued from previous page)

```
8
9     type Test_Case_Index is
10      (Type_Chk,
11       Unit_Test_Chk);
12
13    procedure Check (TC : Test_Case_Index) is
14
15       function Result_Image (Result : Boolean) return String is
16         (if Result then "OK" else "not OK");
17
18    begin
19       case TC is
20       when Type_Chk =>
21          declare
22             AM : constant Member      := (Start    => 2002);
23             FM : constant Full_Member := (Start    => 1990,
24                                           Discount => 0.2);
25          begin
26             Put_Line ("Testing Status of Associate Member Type => "
27                       & Result_Image (AM.Get_Status = "Associate Member"));
28             Put_Line ("Testing Status of Full Member Type => "
29                       & Result_Image (FM.Get_Status = "Full Member"));
30             Put_Line ("Testing Discount of Associate Member Type => "
31                       & Result_Image (AM.Get_Price (100.0) = 100.0));
32             Put_Line ("Testing Discount of Full Member Type => "
33                       & Result_Image (FM.Get_Price (100.0) = 80.0));
34          end;
35          when Unit_Test_Chk =>
36             Simple_Test;
37       end case;
38    end Check;
39
40 begin
41    if Argument_Count < 1 then
42       Put_Line ("ERROR: missing arguments! Exiting...");
43       return;
44    elsif Argument_Count > 1 then
45       Put_Line ("Ignoring additional arguments...");
46    end if;
47
48    Check (Test_Case_Index'Value (Argument (1)));
49 end Main;
```

CHAPTER

FOURTEEN

STANDARD LIBRARY: CONTAINERS

14.1 Simple todo list

Goal: implement a simple to-do list system using vectors.

Steps:

1. Implement the `Todo_Lists` package.
    1. Declare the `Todo_Item` type.
    2. Declare the `Todo_List` type.
    3. Implement the `Add` procedure.
    4. Implement the `Display` procedure.
2. `Todo_Item` type is used to store to-do items.
    1. It should be implemented as an access type to strings.
3. `Todo_List` type is the container for all to-do items.
    1. It should be implemented as a **vector**.
4. Procedure `Add` adds items (of `Todo_Item` type) to the list (of `Todo_List` type).
    1. This requires allocating a string for the access type.
5. Procedure `Display` is used to display all to-do items.
    1. It must display one item per line.

Remarks:

1. This exercise is based on the *Simple todo list* exercise from the *More About Types* (page 59).
    1. Your goal is to rewrite that exercise using vectors instead of arrays.
    2. You may reuse the code you've already implemented as a starting point.

Listing 1: todo_lists.ads

```
1  package Todo_Lists is
2
3     type Todo_Item is access String;
4
5     type Todo_List is null record;
6
7     procedure Add (Todos : in out Todo_List;
8                    Item  : String);
9
10    procedure Display (Todos : Todo_List);
```

(continues on next page)

(continued from previous page)

```
11
12 end Todo_Lists;
```

Listing 2: todo_lists.adb

```
1  with Ada.Text_IO; use Ada.Text_IO;
2
3  package body Todo_Lists is
4
5     procedure Add (Todos : in out Todo_List;
6                    Item  : String) is
7     begin
8        null;
9     end Add;
10
11    procedure Display (Todos : Todo_List) is
12    begin
13       Put_Line ("TO-DO LIST");
14    end Display;
15
16 end Todo_Lists;
```

Listing 3: main.adb

```
1  with Ada.Command_Line;  use Ada.Command_Line;
2  with Ada.Text_IO;       use Ada.Text_IO;
3
4  with Todo_Lists;        use Todo_Lists;
5
6  procedure Main is
7     type Test_Case_Index is
8       (Todo_List_Chk);
9
10    procedure Check (TC : Test_Case_Index) is
11       T : Todo_List;
12    begin
13       case TC is
14          when Todo_List_Chk =>
15             Add (T, "Buy milk");
16             Add (T, "Buy tea");
17             Add (T, "Buy present");
18             Add (T, "Buy tickets");
19             Add (T, "Pay electricity bill");
20             Add (T, "Schedule dentist appointment");
21             Add (T, "Call sister");
22             Add (T, "Revise spreasheet");
23             Add (T, "Edit entry page");
24             Add (T, "Select new design");
25             Add (T, "Create upgrade plan");
26             Display (T);
27       end case;
28    end Check;
29
30 begin
31    if Argument_Count < 1 then
32       Put_Line ("ERROR: missing arguments! Exiting...");
33       return;
34    elsif Argument_Count > 1 then
35       Put_Line ("Ignoring additional arguments...");
36    end if;
```

(continues on next page)

(continued from previous page)

```
37
38    Check (Test_Case_Index'Value (Argument (1)));
39 end Main;
```

14.2 List of unique integers

Goal: create function that removes duplicates from and orders a collection of elements.

Steps:

1. Implement package `Ops`.
    1. Declare the `Int_Array` type.
    2. Declare the `Integer_Sets` type.
    3. Implement the `Get_Unique` function that returns a set.
    4. Implement the `Get_Unique` function that returns an array of integer values.

Requirements:

1. The `Int_Array` type is an unconstrained array of positive range.
2. The `Integer_Sets` package is an instantiation of the `Ordered_Sets` package for the **`Integer`** type.
3. The `Get_Unique` function must remove duplicates from an input array of integer values and order the elements.
    1. For example:
        - if the input array contains `(7, 7, 1)`
        - the function must return `(1, 7)`.
    2. You must implement this function by using sets from the `Ordered_Sets` package.
    3. `Get_Unique` must be implemented in two versions:
        - one version that returns a set — `Set` type from the `Ordered_Sets` package.
        - one version that returns an array of integer values — `Int_Array` type.

Remarks:

1. Sets — as the one found in the generic `Ordered_Sets` package — are useful for quickly and easily creating an algorithm that removes duplicates from a list of elements.

Listing 4: ops.ads

```
1  with Ada.Containers.Ordered_Sets;
2
3  package Ops is
4
5     --  type Int_Array is ...
6
7     --  package Integer_Sets is ...
8
9     subtype Int_Set is Integer_Sets.Set;
10
11    function Get_Unique (A : Int_Array) return Int_Set;
12
13    function Get_Unique (A : Int_Array) return Int_Array;
14
15 end Ops;
```

Listing 5: ops.adb

```
package body Ops is

   function Get_Unique (A : Int_Array) return Int_Set is
   begin
      null;
   end Get_Unique;

   function Get_Unique (A : Int_Array) return Int_Array is
   begin
      null;
   end Get_Unique;

end Ops;
```

Listing 6: main.adb

```
with Ada.Command_Line;        use Ada.Command_Line;
with Ada.Text_IO;             use Ada.Text_IO;

with Ops;                     use Ops;

procedure Main is
   type Test_Case_Index is
     (Get_Unique_Set_Chk,
      Get_Unique_Array_Chk);

   procedure Check (TC : Test_Case_Index;
                    A  : Int_Array) is

      procedure Display_Unique_Set (A : Int_Array) is
         S  : constant Int_Set := Get_Unique (A);
      begin
         for E of S loop
            Put_Line (Integer'Image (E));
         end loop;
      end Display_Unique_Set;

      procedure Display_Unique_Array (A : Int_Array) is
         AU : constant Int_Array := Get_Unique (A);
      begin
         for E of AU loop
            Put_Line (Integer'Image (E));
         end loop;
      end Display_Unique_Array;

   begin
      case TC is
         when Get_Unique_Set_Chk   => Display_Unique_Set (A);
         when Get_Unique_Array_Chk => Display_Unique_Array (A);
      end case;
   end Check;

begin
   if Argument_Count < 3 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   else
      declare
         A : Int_Array (1 .. Argument_Count - 1);
```

(continues on next page)

(continued from previous page)

```
      begin
         for I in A'Range loop
            A (I) := Integer'Value (Argument (1 + I));
         end loop;
         Check (Test_Case_Index'Value (Argument (1)), A);
      end;
   end if;
end Main;
```

CHAPTER

FIFTEEN

STANDARD LIBRARY: DATES & TIMES

15.1 Holocene calendar

Goal: create a function that returns the year in the Holocene calendar.

Steps:

1. Implement the `To_Holocene_Year` function.

Requirements:

1. The `To_Holocene_Year` extracts the year from a time object (`Time` type) and returns the corresponding year for the Holocene calendar[3].
    1. For positive (AD) years, the Holocene year is calculated by adding 10,000 to the year number.

Remarks:

1. In this exercise, we don't deal with BC years.
2. Note that the year component of the `Time` type from the `Ada.Calendar` package is limited to years starting with 1901.

Listing 1: to_holocene_year.adb

```
with Ada.Calendar; use Ada.Calendar;

function To_Holocene_Year (T : Time) return Integer is
begin
   return 0;
end To_Holocene_Year;
```

Listing 2: main.adb

```
with Ada.Command_Line;        use Ada.Command_Line;
with Ada.Text_IO;             use Ada.Text_IO;
with Ada.Calendar;            use Ada.Calendar;

with To_Holocene_Year;

procedure Main is
   type Test_Case_Index is
     (Holocene_Chk);

   procedure Display_Holocene_Year (Y : Year_Number) is
      HY : Integer;
   begin
      HY := To_Holocene_Year (Time_Of (Y, 1, 1));
```

(continues on next page)

[3] https://en.wikipedia.org/wiki/Holocene_calendar

(continued from previous page)

```
15       Put_Line ("Year (Gregorian): " & Year_Number'Image (Y));
16       Put_Line ("Year (Holocene):  " & Integer'Image (HY));
17    end Display_Holocene_Year;
18
19    procedure Check (TC : Test_Case_Index) is
20    begin
21       case TC is
22          when Holocene_Chk =>
23             Display_Holocene_Year (2012);
24             Display_Holocene_Year (2020);
25       end case;
26    end Check;
27
28 begin
29    if Argument_Count < 1 then
30       Put_Line ("ERROR: missing arguments! Exiting...");
31       return;
32    elsif Argument_Count > 1 then
33       Put_Line ("Ignoring additional arguments...");
34    end if;
35
36    Check (Test_Case_Index'Value (Argument (1)));
37 end Main;
```

15.2 List of events

Goal: create a system to manage a list of events.

Steps:

1. Implement the `Events` package.
    1. Declare the `Event_Item` type.
    2. Declare the `Event_Items` type.
2. Implement the `Events.Lists` package.
    1. Declare the `Event_List` type.
    2. Implement the `Add` procedure.
    3. Implement the `Display` procedure.

Requirements:

1. The `Event_Item` type (from the `Events` package) contains the *description of an event*.
    1. This description shall be stored in an access-to-string type.
2. The `Event_Items` type stores a list of events.
    1. This will be used later to represent multiple events for a specific date.
    2. You shall use a vector for this type.
3. The `Events.Lists` package contains the subprograms that are used in the test application.
4. The `Event_List` type (from the `Events.Lists` package) maps a list of events to a specific date.
    1. You must use the `Event_Items` type for the list of events.
    2. You shall use the `Time` type from the `Ada.Calendar` package for the dates.

3. Since we expect the events to be ordered by the date, you shall use ordered maps for the `Event_List` type.

5. Procedure `Add` adds an event into the list of events for a specific date.
6. Procedure `Display` must display all events for each date (ordered by date) using the following format:

```
<event_date #1>
    <description of item #1a>
    <description of item #1b>
<event_date #2>
    <description of item #2a>
    <description of item #2b>
```

1. You should use the auxiliary `Date_Image` function — available in the body of the `Events.Lists` package — to display the date in the `YYYY-MM-DD` format.

Remarks:

1. Let's briefly illustrate the expected output of this system.
   1. Consider the following example:

```
with Ada.Calendar;
with Ada.Calendar.Formatting; use Ada.Calendar.Formatting;

with Events.Lists;            use Events.Lists;

procedure Test is
   EL : Event_List;
begin
   EL.Add (Time_Of (2019, 4, 16),
           "Item #2");
   EL.Add (Time_Of (2019, 4, 15),
           "Item #1");
   EL.Add (Time_Of (2019, 4, 16),
           "Item #3");
   EL.Display;
end Test;
```

   2. The expected output of the `Test` procedure must be:

```
EVENTS LIST
- 2019-04-15
    - Item #1
- 2019-04-16
    - Item #2
    - Item #3
```

Listing 3: events.ads

```
1  package Events is
2
3     type Event_Item is null record;
4
5     type Event_Items is null record;
6
7  end Events;
```

Listing 4: events-lists.ads

```
with Ada.Calendar; use Ada.Calendar;

package Events.Lists is

   type Event_List is tagged private;

   procedure Add (Events     : in out Event_List;
                  Event_Time :        Time;
                  Event      :        String);

   procedure Display (Events : Event_List);

private

   type Event_List is tagged null record;

end Events.Lists;
```

Listing 5: events-lists.adb

```
with Ada.Text_IO;              use Ada.Text_IO;
with Ada.Calendar.Formatting; use Ada.Calendar.Formatting;

package body Events.Lists is

   procedure Add (Events     : in out Event_List;
                  Event_Time : Time;
                  Event      : String) is
   begin
      null;
   end Add;

   function Date_Image (T : Time) return String is
      Date_Img : constant String := Image (T);
   begin
      return Date_Img (1 .. 10);
   end;

   procedure Display (Events : Event_List) is
      T : Time;
   begin
      Put_Line ("EVENTS LIST");
      --  You should use Date_Image (T) here!
   end Display;

end Events.Lists;
```

Listing 6: main.adb

```
with Ada.Command_Line;         use Ada.Command_Line;
with Ada.Text_IO;              use Ada.Text_IO;
with Ada.Calendar;
with Ada.Calendar.Formatting; use Ada.Calendar.Formatting;

with Events.Lists;             use Events.Lists;

procedure Main is
   type Test_Case_Index is
     (Event_List_Chk);
```

(continues on next page)

(continued from previous page)

```
11
12    procedure Check (TC : Test_Case_Index) is
13       EL : Event_List;
14    begin
15       case TC is
16          when Event_List_Chk =>
17             EL.Add (Time_Of (2018, 2, 16),
18                     "Final check");
19             EL.Add (Time_Of (2018, 2, 16),
20                     "Release");
21             EL.Add (Time_Of (2018, 12, 3),
22                     "Brother's birthday");
23             EL.Add (Time_Of (2018, 1, 1),
24                     "New Year's Day");
25             EL.Display;
26       end case;
27    end Check;
28
29 begin
30    if Argument_Count < 1 then
31       Put_Line ("ERROR: missing arguments! Exiting...");
32       return;
33    elsif Argument_Count > 1 then
34       Put_Line ("Ignoring additional arguments...");
35    end if;
36
37    Check (Test_Case_Index'Value (Argument (1)));
38 end Main;
```

CHAPTER

SIXTEEN

STANDARD LIBRARY: STRINGS

16.1 Concatenation

Goal: implement functions to concatenate an array of unbounded strings.

Steps:

1. Implement the `Str_Concat` package.
    1. Implement the `Concat` function for `Unbounded_String`.
    2. Implement the `Concat` function for **`String`**.

Requirements:

1. The first `Concat` function receives an unconstrained array of unbounded strings and returns the concatenation of those strings as an unbounded string.
    1. The second `Concat` function has the same parameters, but returns a standard string (**`String`** type).
2. Both `Concat` functions have the following parameters:
    1. An unconstrained array of `Unbounded_String` strings (`Unbounded_Strings` type).
    2. `Trim_Str`, a Boolean parameter indicating whether each unbounded string must be trimmed.
    3. `Add_Whitespace`, a Boolean parameter indicating whether a whitespace shall be added between each unbounded string and the next one.
        1. No whitespace shall be added after the last string of the array.

Remarks:

1. You can use the `Trim` function from the `Ada.Strings.Unbounded` package.

Listing 1: str_concat.ads

```
with Ada.Strings.Unbounded; use Ada.Strings.Unbounded;

package Str_Concat is

   type Unbounded_Strings is array (Positive range <>) of Unbounded_String;

   function Concat (USA             : Unbounded_Strings;
                    Trim_Str        : Boolean;
                    Add_Whitespace : Boolean) return Unbounded_String;

   function Concat (USA             : Unbounded_Strings;
                    Trim_Str        : Boolean;
                    Add_Whitespace : Boolean) return String;

end Str_Concat;
```

Listing 2: str_concat.adb

```
with Ada.Strings; use Ada.Strings;

package body Str_Concat is

   function Concat (USA            : Unbounded_Strings;
                    Trim_Str       : Boolean;
                    Add_Whitespace : Boolean) return Unbounded_String is
   begin
      return "";
   end Concat;

   function Concat (USA            : Unbounded_Strings;
                    Trim_Str       : Boolean;
                    Add_Whitespace : Boolean) return String is
   begin
      return "";
   end Concat;

end Str_Concat;
```

Listing 3: main.adb

```
with Ada.Command_Line;        use Ada.Command_Line;
with Ada.Text_IO;             use Ada.Text_IO;
with Ada.Strings.Unbounded;   use Ada.Strings.Unbounded;

with Str_Concat;              use Str_Concat;

procedure Main is
   type Test_Case_Index is
     (Unbounded_Concat_No_Trim_No_WS_Chk,
      Unbounded_Concat_Trim_No_WS_Chk,
      String_Concat_Trim_WS_Chk,
      Concat_Single_Element);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Unbounded_Concat_No_Trim_No_WS_Chk =>
            declare
               S : constant Unbounded_Strings := (
                  To_Unbounded_String ("Hello"),
                  To_Unbounded_String (" World"),
                  To_Unbounded_String ("!"));
            begin
               Put_Line (To_String (Concat (S, False, False)));
            end;
         when Unbounded_Concat_Trim_No_WS_Chk =>
            declare
               S : constant Unbounded_Strings := (
                  To_Unbounded_String (" This "),
                  To_Unbounded_String (" _is_ "),
                  To_Unbounded_String ("  a   "),
                  To_Unbounded_String (" _check "));
            begin
               Put_Line (To_String (Concat (S, True, False)));
            end;
         when String_Concat_Trim_WS_Chk =>
            declare
```

(continues on next page)

(continued from previous page)

```
38                S : constant Unbounded_Strings := (
39                    To_Unbounded_String ("  This  "),
40                    To_Unbounded_String ("  is a  "),
41                    To_Unbounded_String ("  test.  "));
42             begin
43                Put_Line (Concat (S, True, True));
44             end;
45          when Concat_Single_Element =>
46             declare
47                S : constant Unbounded_Strings := (
48                    1 => To_Unbounded_String ("  Hi "));
49             begin
50                Put_Line (Concat (S, True, True));
51             end;
52       end case;
53    end Check;
54
55 begin
56    if Argument_Count < 1 then
57       Put_Line ("ERROR: missing arguments! Exiting...");
58       return;
59    elsif Argument_Count > 1 then
60       Put_Line ("Ignoring additional arguments...");
61    end if;
62
63    Check (Test_Case_Index'Value (Argument (1)));
64 end Main;
```

16.2 List of events

Goal: create a system to manage a list of events.

Steps:

1. Implement the `Events` package.
    1. Declare the `Event_Item` subtype.
2. Implement the `Events.Lists` package.
    1. Adapt the `Add` procedure.
    2. Adapt the `Display` procedure.

Requirements:

1. The `Event_Item` type (from the `Events` package) contains the *description of an event*.
    1. This description is declared as a subtype of unbounded string.
2. Procedure `Add` adds an event into the list of events for a specific date.
    1. The declaration of `E` needs to be adapted to use unbounded strings.
3. Procedure `Display` must display all events for each date (ordered by date) using the following format:
    1. The arguments to `Put_Line` need to be adapted to use unbounded strings.

Remarks:

1. We use the lab on the list of events from the previous chapter (*Standard library: Dates & Times* (page 129)) as a starting point.

Listing 4: events.ads

```
with Ada.Containers.Vectors;

package Events is

   --  subtype Event_Item is

   package Event_Item_Containers is new
     Ada.Containers.Vectors
       (Index_Type   => Positive,
        Element_Type => Event_Item);

   subtype Event_Items is Event_Item_Containers.Vector;

end Events;
```

Listing 5: events-lists.ads

```
with Ada.Calendar;                use Ada.Calendar;
with Ada.Containers.Ordered_Maps;

package Events.Lists is

   type Event_List is tagged private;

   procedure Add (Events     : in out Event_List;
                  Event_Time :        Time;
                  Event      :        String);

   procedure Display (Events : Event_List);

private

   package Event_Time_Item_Containers is new
     Ada.Containers.Ordered_Maps
       (Key_Type         => Time,
        Element_Type     => Event_Items,
        "="              => Event_Item_Containers."=");

   type Event_List is new Event_Time_Item_Containers.Map with null record;

end Events.Lists;
```

Listing 6: events-lists.adb

```
with Ada.Text_IO;             use Ada.Text_IO;
with Ada.Calendar.Formatting; use Ada.Calendar.Formatting;

package body Events.Lists is

   procedure Add (Events     : in out Event_List;
                  Event_Time : Time;
                  Event      : String) is
      use Event_Item_Containers;
      E : constant Event_Item := new String'(Event);
   begin
      if not Events.Contains (Event_Time) then
         Events.Include (Event_Time, Empty_Vector);
      end if;
      Events (Event_Time).Append (E);
```

(continues on next page)

(continued from previous page)

```
   end Add;

   function Date_Image (T : Time) return String is
      Date_Img : constant String := Image (T);
   begin
      return Date_Img (1 .. 10);
   end;

   procedure Display (Events : Event_List) is
      use Event_Time_Item_Containers;
      T : Time;
   begin
      Put_Line ("EVENTS LIST");
      for C in Events.Iterate loop
         T := Key (C);
         Put_Line ("- " & Date_Image (T));
         for I of Events (C) loop
            Put_Line ("    - " & I.all);
         end loop;
      end loop;
   end Display;

end Events.Lists;
```

Listing 7: main.adb

```
with Ada.Command_Line;        use Ada.Command_Line;
with Ada.Text_IO;             use Ada.Text_IO;
with Ada.Calendar;
with Ada.Calendar.Formatting; use Ada.Calendar.Formatting;
with Ada.Strings.Unbounded;   use Ada.Strings.Unbounded;

with Events;
with Events.Lists;            use Events.Lists;

procedure Main is
   type Test_Case_Index is
     (Unbounded_String_Chk,
      Event_List_Chk);

   procedure Check (TC : Test_Case_Index) is
      EL : Event_List;
   begin
      case TC is
         when Unbounded_String_Chk =>
            declare
               S : constant Events.Event_Item := To_Unbounded_String ("Checked");
            begin
               Put_Line (To_String (S));
            end;
         when Event_List_Chk =>
            EL.Add (Time_Of (2018, 2, 16),
                    "Final check");
            EL.Add (Time_Of (2018, 2, 16),
                    "Release");
            EL.Add (Time_Of (2018, 12, 3),
                    "Brother's birthday");
            EL.Add (Time_Of (2018, 1, 1),
                    "New Year's Day");
            EL.Display;
      end case;
```

(continues on next page)

(continued from previous page)

```
36    end Check;
37
38 begin
39    if Argument_Count < 1 then
40       Put_Line ("ERROR: missing arguments! Exiting...");
41       return;
42    elsif Argument_Count > 1 then
43       Put_Line ("Ignoring additional arguments...");
44    end if;
45
46    Check (Test_Case_Index'Value (Argument (1)));
47 end Main;
```

CHAPTER

SEVENTEEN

STANDARD LIBRARY: NUMERICS

17.1 Decibel Factor

Goal: implement functions to convert from Decibel values to factors and vice-versa.

Steps:

1. Implement the `Decibels` package.
    1. Implement the `To_Decibel` function.
    2. Implement the `To_Factor` function.

Requirements:

1. The subtypes `Decibel` and `Factor` are based on a floating-point type.
2. Function `To_Decibel` converts a multiplication factor (or ratio) to decibels.
    - For the implementation, use $20 * log_{10}(F)$, where *F* is the factor/ratio.
3. Function `To_Factor` converts a value in decibels to a multiplication factor (or ratio).
    - For the implementation, use $10^{D/20}$, where *D* is the value in Decibel.

Remarks:

1. The Decibel[4] is used to express the ratio of two values on a logarithmic scale.
    1. For example, an increase of 6 dB corresponds roughly to a multiplication by two (or an increase by 100 % of the original value).
2. You can find the functions that you'll need for the calculation in the `Ada.Numerics.Elementary_Functions` package.

Listing 1: decibels.ads

```
package Decibels is

   subtype Decibel is Float;
   subtype Factor  is Float;

   function To_Decibel (F : Factor) return Decibel;

   function To_Factor (D : Decibel) return Factor;

end Decibels;
```

[4] https://en.wikipedia.org/wiki/Decibel

Listing 2: decibels.adb

```
package body Decibels is

   function To_Decibel (F : Factor) return Decibel is
   begin
      return 0.0;
   end To_Decibel;

   function To_Factor (D : Decibel) return Factor is
   begin
      return 0.0;
   end To_Factor;

end Decibels;
```

Listing 3: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Decibels;         use Decibels;

procedure Main is
   type Test_Case_Index is
     (Db_Chk,
      Factor_Chk);

   procedure Check (TC : Test_Case_Index; V : Float) is

      package F_IO is new Ada.Text_IO.Float_IO (Factor);
      package D_IO is new Ada.Text_IO.Float_IO (Decibel);

      procedure Put_Decibel_Cnvt (D : Decibel) is
         F : constant Factor := To_Factor (D);
      begin
         D_IO.Put (D, 0, 2, 0);
         Put (" dB => Factor of ");
         F_IO.Put (F, 0, 2, 0);
         New_Line;
      end;

      procedure Put_Factor_Cnvt (F : Factor) is
         D : constant Decibel := To_Decibel (F);
      begin
         Put ("Factor of ");
         F_IO.Put (F, 0, 2, 0);
         Put (" => ");
         D_IO.Put (D, 0, 2, 0);
         Put_Line (" dB");
      end;
   begin
      case TC is
         when Db_Chk =>
            Put_Decibel_Cnvt (Decibel (V));
         when Factor_Chk =>
            Put_Factor_Cnvt (Factor (V));
      end case;
   end Check;

begin
   if Argument_Count < 2 then
```

(continues on next page)

(continued from previous page)

```
45       Put_Line ("ERROR: missing arguments! Exiting...");
46       return;
47    elsif Argument_Count > 2 then
48       Put_Line ("Ignoring additional arguments...");
49    end if;
50
51    Check (Test_Case_Index'Value (Argument (1)), Float'Value (Argument (2)));
52 end Main;
```

17.2 Root-Mean-Square

Goal: implement a function to calculate the root-mean-square of a sequence of values.

Steps:

1. Implement the `Signals` package.
    1. Implement the `Rms` function.

Requirements:

1. Subtype `Sig_Value` is based on a floating-point type.
2. Type `Signal` is an unconstrained array of `Sig_Value` elements.
3. Function `Rms` calculates the RMS of a sequence of values stored in an array of type `Signal`.
    1. See the remarks below for a description of the RMS calculation.

Remarks:

1. The root-mean-square[5] (RMS) value is an important information associated with sequences of values.
    1. It's used, for example, as a measurement for signal processing.
    2. It is calculated by:
        1. Creating a sequence S with the square of each value of an input sequence S_{in}.
        2. Calculating the mean value M of the sequence S.
        3. Calculating the square-root R of M.
    3. You can optimize the algorithm above by combining steps #1 and #2 into a single step.

Listing 4: signals.ads

```
1 package Signals is
2
3    subtype Sig_Value is Float;
4
5    type Signal is array (Natural range <>) of Sig_Value;
6
7    function Rms (S : Signal) return Sig_Value;
8
9 end Signals;
```

[5] https://en.wikipedia.org/wiki/Root_mean_square

Listing 5: signals.adb

```
with Ada.Numerics.Elementary_Functions; use Ada.Numerics.Elementary_Functions;

package body Signals is

   function Rms (S : Signal) return Sig_Value is
   begin
      return 0.0;
   end;

end Signals;
```

Listing 6: signals-std.ads

```
package Signals.Std is

   Sample_Rate : Float := 8000.0;

   function Generate_Sine (N : Positive; Freq : Float) return Signal;

   function Generate_Square (N : Positive) return Signal;

   function Generate_Triangular (N : Positive) return Signal;

end Signals.Std;
```

Listing 7: signals-std.adb

```
with Ada.Numerics;                      use Ada.Numerics;
with Ada.Numerics.Elementary_Functions; use Ada.Numerics.Elementary_Functions;

package body Signals.Std is

   function Generate_Sine (N : Positive; Freq : Float) return Signal is
      S : Signal (0 .. N - 1);
   begin
      for I in S'First .. S'Last loop
         S (I) := 1.0 * Sin (2.0 * Pi * (Freq * Float (I) / Sample_Rate));
      end loop;

      return S;
   end;

   function Generate_Square (N : Positive) return Signal is
      S : constant Signal (0 .. N - 1) := (others => 1.0);
   begin
      return S;
   end;

   function Generate_Triangular (N : Positive) return Signal is
      S      : Signal (0 .. N - 1);
      S_Half : constant Natural := S'Last / 2;
   begin
      for I in S'First .. S_Half loop
         S (I) := 1.0 * (Float (I) / Float (S_Half));
      end loop;
      for I in S_Half .. S'Last loop
         S (I) := 1.0 - (1.0 * (Float (I - S_Half) / Float (S_Half)));
      end loop;

```

(continues on next page)

(continued from previous page)

```
      return S;
   end;

end Signals.Std;
```

Listing 8: main.adb

```
with Ada.Command_Line;          use Ada.Command_Line;
with Ada.Text_IO;               use Ada.Text_IO;

with Signals;                   use Signals;
with Signals.Std;               use Signals.Std;

procedure Main is
   type Test_Case_Index is
     (Sine_Signal_Chk,
      Square_Signal_Chk,
      Triangular_Signal_Chk);

   procedure Check (TC : Test_Case_Index) is
      package Sig_IO is new Ada.Text_IO.Float_IO (Sig_Value);

      N    : constant Positive := 1024;
      S_Si : constant Signal := Generate_Sine (N, 440.0);
      S_Sq : constant Signal := Generate_Square (N);
      S_Tr : constant Signal := Generate_Triangular (N + 1);
   begin
      case TC is
         when Sine_Signal_Chk =>
            Put ("RMS of Sine Signal: ");
            Sig_IO.Put (Rms (S_Si), 0, 2, 0);
            New_Line;
         when Square_Signal_Chk =>
            Put ("RMS of Square Signal: ");
            Sig_IO.Put (Rms (S_Sq), 0, 2, 0);
            New_Line;
         when Triangular_Signal_Chk =>
            Put ("RMS of Triangular Signal: ");
            Sig_IO.Put (Rms (S_Tr), 0, 2, 0);
            New_Line;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

17.3 Rotation

Goal: use complex numbers to calculate the positions of an object in a circle after rotation.

Steps:

1. Implement the `Rotation` package.
    1. Implement the `Rotation` function.

Requirements:

1. Type `Complex_Points` is an unconstrained array of complex values.
2. Function `Rotation` returns a list of positions (represented by the `Complex_Points` type) when dividing a circle in `N` equal slices.
    1. See the remarks below for a more detailed explanation.
    2. You must use functions from `Ada.Numerics.Complex_Types` to implement `Rotation`.
3. Subtype `Angle` is based on a floating-point type.
4. Type `Angles` is an unconstrained array of angles.
5. Function `To_Angles` returns a list of angles based on an input list of positions.

Remarks:

1. Complex numbers are particularly useful in computer graphics to simplify the calculation of rotations.
    1. For example, let's assume you've drawn an object on your screen on position (1.0, 0.0).
    2. Now, you want to move this object in a circular path — i.e. make it rotate around position (0.0, 0.0) on your screen.
        - You could use *sine* and *cosine* functions to calculate each position of the path.
        - However, you could also calculate the positions using complex numbers.
2. In this exercise, you'll use complex numbers to calculate the positions of an object that starts on zero degrees — on position (1.0, 0.0) — and rotates around (0.0, 0.0) for *N* slices of a circle.
    1. For example, if we divide the circle in four slices, the object's path will consist of following points / positions:

        ```
        Point #1: ( 1.0,  0.0)
        Point #2: ( 0.0,  1.0)
        Point #3: (-1.0,  0.0)
        Point #4: ( 0.0, -1.0)
        Point #5: ( 1.0,  0.0)
        ```

        1. As expected, point #5 is equal to the starting point (point #1), since the object rotates around (0.0, 0.0) and returns to the starting point.
    2. We can also describe this path in terms of angles. The following list presents the angles for the path on a four-sliced circle:

        ```
        Point #1:    0.00 degrees
        Point #2:   90.00 degrees
        Point #3:  180.00 degrees
        Point #4:  -90.00 degrees (= 270 degrees)
        Point #5:    0.00 degrees
        ```

        1. To rotate a complex number simply multiply it by a unit vector whose arg is the radian angle to be rotated: $Z = e^{\frac{2\pi}{N}}$

Listing 9: rotation.ads

```
with Ada.Numerics.Complex_Types;
use  Ada.Numerics.Complex_Types;

package Rotation is

   type Complex_Points is array (Positive range <>) of Complex;

   function Rotation (N : Positive) return Complex_Points;

end Rotation;
```

Listing 10: rotation.adb

```
with Ada.Numerics; use Ada.Numerics;

package body Rotation is

   function Rotation (N : Positive) return Complex_Points is
      C : Complex_Points (1 .. 1) := (others => (0.0, 0.0));
   begin
      return C;
   end;

end Rotation;
```

Listing 11: angles.ads

```
with Rotation; use Rotation;

package Angles is

   subtype Angle is Float;

   type Angles is array (Positive range <>) of Angle;

   function To_Angles (C : Complex_Points) return Angles;

end Angles;
```

Listing 12: angles.adb

```
with Ada.Numerics;                use Ada.Numerics;
with Ada.Numerics.Complex_Types; use Ada.Numerics.Complex_Types;

package body Angles is

   function To_Angles (C : Complex_Points) return Angles is
   begin
      return A : Angles (C'Range) do
         for I in A'Range loop
            A (I) := Argument (C (I)) / Pi * 180.0;
         end loop;
      end return;
   end To_Angles;

end Angles;
```

Listing 13: rotation-tests.ads

```
package Rotation.Tests is

   procedure Test_Rotation (N : Positive);

   procedure Test_Angles (N : Positive);

end Rotation.Tests;
```

Listing 14: rotation-tests.adb

```
with Ada.Text_IO;            use Ada.Text_IO;
with Ada.Text_IO.Complex_IO;
with Ada.Numerics;           use Ada.Numerics;

with Angles;                 use Angles;

package body Rotation.Tests is

   package C_IO is new Ada.Text_IO.Complex_IO (Complex_Types);
   package F_IO is new Ada.Text_IO.Float_IO (Float);

   --
   --  Adapt value due to floating-point inaccuracies
   --

   function Adapt (C : Complex) return Complex is
      function Check_Zero (F : Float) return Float is
        (if F <= 0.0 and F >= -0.01 then 0.0 else F);
   begin
      return C_Out : Complex := C do
         C_Out.Re := Check_Zero (C_Out.Re);
         C_Out.Im := Check_Zero (C_Out.Im);
      end return;
   end Adapt;

   function Adapt (A : Angle) return Angle is
     (if A <= -179.99 and A >= -180.01 then 180.0 else A);

   procedure Test_Rotation (N : Positive) is
      C : constant Complex_Points := Rotation (N);
   begin
      Put_Line ("---- Points for " & Positive'Image (N) & " slices ----");
      for V of C loop
         Put ("Point: ");
         C_IO.Put (Adapt (V), 0, 1, 0);
         New_Line;
      end loop;
   end Test_Rotation;

   procedure Test_Angles (N : Positive) is
      C : constant Complex_Points := Rotation (N);
      A : constant Angles.Angles  := To_Angles (C);
   begin
      Put_Line ("---- Angles for " & Positive'Image (N) & " slices ----");
      for V of A loop
         Put ("Angle: ");
         F_IO.Put (Adapt (V), 0, 2, 0);
         Put_Line (" degrees");
      end loop;
```

(continues on next page)

(continued from previous page)

```
50    end Test_Angles;
51
52 end Rotation.Tests;
```

Listing 15: main.adb

```
1  with Ada.Command_Line;          use Ada.Command_Line;
2  with Ada.Text_IO;               use Ada.Text_IO;
3
4  with Rotation.Tests;            use Rotation.Tests;
5
6  procedure Main is
7     type Test_Case_Index is
8       (Rotation_Chk,
9        Angles_Chk);
10
11    procedure Check (TC : Test_Case_Index; N : Positive) is
12    begin
13       case TC is
14          when Rotation_Chk =>
15             Test_Rotation (N);
16          when Angles_Chk =>
17             Test_Angles (N);
18       end case;
19    end Check;
20
21 begin
22    if Argument_Count < 2 then
23       Put_Line ("ERROR: missing arguments! Exiting...");
24       return;
25    elsif Argument_Count > 2 then
26       Put_Line ("Ignoring additional arguments...");
27    end if;
28
29    Check (Test_Case_Index'Value (Argument (1)), Positive'Value (Argument (2)));
30 end Main;
```

CHAPTER

EIGHTEEN

SOLUTIONS

18.1 Imperative Language

18.1.1 Hello World

Listing 1: main.adb

```
with Ada.Text_IO; use Ada.Text_IO;

procedure Main is
begin
   Put_Line ("Hello World!");
end Main;
```

18.1.2 Greetings

Listing 2: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

procedure Main is

   procedure Greet (Name : String) is
   begin
      Put_Line ("Hello " & Name & "!");
   end Greet;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Greet (Argument (1));
end Main;
```

18.1.3 Positive Or Negative

Listing 3: classify_number.ads

```
procedure Classify_Number (X : Integer);
```

Listing 4: classify_number.adb

```
with Ada.Text_IO; use Ada.Text_IO;

procedure Classify_Number (X : Integer) is
begin
   if X > 0 then
      Put_Line ("Positive");
   elsif X < 0 then
      Put_Line ("Negative");
   else
      Put_Line ("Zero");
   end if;
end Classify_Number;
```

Listing 5: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Classify_Number;

procedure Main is
   A : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   A := Integer'Value (Argument (1));

   Classify_Number (A);
end Main;
```

18.1.4 Numbers

Listing 6: display_numbers.ads

```
procedure Display_Numbers (A, B : Integer);
```

Listing 7: display_numbers.adb

```
with Ada.Text_IO; use Ada.Text_IO;

procedure Display_Numbers (A, B : Integer) is
   X, Y : Integer;
begin
   if A <= B then
      X := A;
      Y := B;
   else
      X := B;
      Y := A;
   end if;

   for I in X .. Y loop
```

(continues on next page)

(continued from previous page)

```
      Put_Line (Integer'Image (I));
   end loop;
end Display_Numbers;
```

Listing 8: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_Numbers;

procedure Main is
   A, B : Integer;
begin
   if Argument_Count < 2 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 2 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   A := Integer'Value (Argument (1));
   B := Integer'Value (Argument (2));

   Display_Numbers (A, B);
end Main;
```

18.2 Subprograms

18.2.1 Subtract Procedure

Listing 9: subtract.ads

```
procedure Subtract (A, B   :     Integer;
                    Result : out Integer);
```

Listing 10: subtract.adb

```
procedure Subtract (A, B   :     Integer;
                    Result : out Integer) is
begin
   Result := A - B;
end Subtract;
```

Listing 11: main.adb

```
with Ada.Command_Line;     use Ada.Command_Line;
with Ada.Text_IO;          use Ada.Text_IO;

with Subtract;

procedure Main is
   type Test_Case_Index is
     (Sub_10_1_Chk,
      Sub_10_100_Chk,
      Sub_0_5_Chk,
      Sub_0_Minus_5_Chk);
```

(continues on next page)

(continued from previous page)

```

   procedure Check (TC : Test_Case_Index) is
      Result : Integer;
   begin
      case TC is
      when Sub_10_1_Chk =>
         Subtract (10, 1, Result);
         Put_Line ("Result: " & Integer'Image (Result));
      when Sub_10_100_Chk =>
         Subtract (10, 100, Result);
         Put_Line ("Result: " & Integer'Image (Result));
      when Sub_0_5_Chk =>
         Subtract (0, 5, Result);
         Put_Line ("Result: " & Integer'Image (Result));
      when Sub_0_Minus_5_Chk =>
         Subtract (0, -5, Result);
         Put_Line ("Result: " & Integer'Image (Result));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.2.2 Subtract Function

Listing 12: subtract.ads

```
function Subtract (A, B : Integer) return Integer;
```

Listing 13: subtract.adb

```
function Subtract (A, B : Integer) return Integer is
begin
   return A - B;
end Subtract;
```

Listing 14: main.adb

```
with Ada.Command_Line;     use Ada.Command_Line;
with Ada.Text_IO;          use Ada.Text_IO;

with Subtract;

procedure Main is
   type Test_Case_Index is
     (Sub_10_1_Chk,
      Sub_10_100_Chk,
      Sub_0_5_Chk,
      Sub_0_Minus_5_Chk);

   procedure Check (TC : Test_Case_Index) is
```

(continues on next page)

(continued from previous page)

```
      Result : Integer;
   begin
      case TC is
      when Sub_10_1_Chk =>
         Result := Subtract (10, 1);
         Put_Line ("Result: " & Integer'Image (Result));
      when Sub_10_100_Chk =>
         Result := Subtract (10, 100);
         Put_Line ("Result: " & Integer'Image (Result));
      when Sub_0_5_Chk =>
         Result := Subtract (0, 5);
         Put_Line ("Result: " & Integer'Image (Result));
      when Sub_0_Minus_5_Chk =>
         Result := Subtract (0, -5);
         Put_Line ("Result: " & Integer'Image (Result));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.2.3 Equality function

Listing 15: is_equal.ads

```
function Is_Equal (A, B : Integer) return Boolean;
```

Listing 16: is_equal.adb

```
function Is_Equal (A, B : Integer) return Boolean is
begin
   return A = B;
end Is_Equal;
```

Listing 17: main.adb

```
with Ada.Command_Line;     use Ada.Command_Line;
with Ada.Text_IO;          use Ada.Text_IO;

with Is_Equal;

procedure Main is
   type Test_Case_Index is
     (Equal_Chk,
      Inequal_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Display_Equal (A, B  : Integer;
                               Equal : Boolean) is
      begin
```

(continues on next page)

(continued from previous page)

```
         Put (Integer'Image (A));
         if Equal then
            Put (" is equal to ");
         else
            Put (" isn't equal to ");
         end if;
         Put_Line (Integer'Image (B) & ".");
      end Display_Equal;

      Result : Boolean;
   begin
      case TC is
      when Equal_Chk =>
         for I in 0 .. 10 loop
            Result := Is_Equal (I, I);
            Display_Equal (I, I, Result);
         end loop;
      when Inequal_Chk =>
         for I in 0 .. 10 loop
            Result := Is_Equal (I, I - 1);
            Display_Equal (I, I - 1, Result);
         end loop;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.2.4 States

Listing 18: display_state.ads

```
procedure Display_State (State : Integer);
```

Listing 19: display_state.adb

```
with Ada.Text_IO; use Ada.Text_IO;

procedure Display_State (State : Integer) is
begin
   case State is
      when 0 =>
         Put_Line ("Off");
      when 1 =>
         Put_Line ("On: Simple Processing");
      when 2 =>
         Put_Line ("On: Advanced Processing");
      when others =>
         null;
   end case;
end Display_State;
```

Listing 20: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_State;

procedure Main is
   State : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   State := Integer'Value (Argument (1));

   Display_State (State);
end Main;
```

18.2.5 States #2

Listing 21: get_state.ads

```
function Get_State (State : Integer) return String;
```

Listing 22: get_state.adb

```
function Get_State (State : Integer) return String is
begin
   return (case State is
            when 0 => "Off",
            when 1 => "On: Simple Processing",
            when 2 => "On: Advanced Processing",
            when others => "");
end Get_State;
```

Listing 23: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Get_State;

procedure Main is
   State : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   State := Integer'Value (Argument (1));

   Put_Line (Get_State (State));
end Main;
```

18.2.6 States #3

Listing 24: is_on.ads

```
function Is_On (State : Integer) return Boolean;
```

Listing 25: is_on.adb

```
function Is_On (State : Integer) return Boolean is
begin
   return not (State = 0);
end Is_On;
```

Listing 26: display_on_off.ads

```
procedure Display_On_Off (State : Integer);
```

Listing 27: display_on_off.adb

```
with Ada.Text_IO; use Ada.Text_IO;
with Is_On;

procedure Display_On_Off (State : Integer) is
begin
   Put_Line (if Is_On (State) then "On" else "Off");
end Display_On_Off;
```

Listing 28: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_On_Off;
with Is_On;

procedure Main is
   State : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   State := Integer'Value (Argument (1));

   Display_On_Off (State);
   Put_Line (Boolean'Image (Is_On (State)));
end Main;
```

18.2.7 States #4

Listing 29: set_next.ads

```
procedure Set_Next (State : in out Integer);
```

Listing 30: set_next.adb

```
procedure Set_Next (State : in out Integer) is
begin
   State := (if State < 2 then State + 1 else 0);
end Set_Next;
```

Listing 31: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Set_Next;

procedure Main is
   State : Integer;
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   State := Integer'Value (Argument (1));

   Set_Next (State);
   Put_Line (Integer'Image (State));
end Main;
```

18.3 Modular Programming

18.3.1 Months

Listing 32: months.ads

```
package Months is

   Jan : constant String := "January";
   Feb : constant String := "February";
   Mar : constant String := "March";
   Apr : constant String := "April";
   May : constant String := "May";
   Jun : constant String := "June";
   Jul : constant String := "July";
   Aug : constant String := "August";
   Sep : constant String := "September";
   Oct : constant String := "October";
   Nov : constant String := "November";
   Dec : constant String := "December";

   procedure Display_Months;

end Months;
```

Listing 33: months.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Months is

   procedure Display_Months is
   begin
      Put_Line ("Months:");
      Put_Line ("- " & Jan);
      Put_Line ("- " & Feb);
      Put_Line ("- " & Mar);
      Put_Line ("- " & Apr);
      Put_Line ("- " & May);
      Put_Line ("- " & Jun);
      Put_Line ("- " & Jul);
      Put_Line ("- " & Aug);
      Put_Line ("- " & Sep);
      Put_Line ("- " & Oct);
      Put_Line ("- " & Nov);
      Put_Line ("- " & Dec);
   end Display_Months;

end Months;
```

Listing 34: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Months;           use Months;

procedure Main is

   type Test_Case_Index is
     (Months_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Months_Chk =>
            Display_Months;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.3.2 Operations

Listing 35: operations.ads

```
package Operations is

   function Add (A, B : Integer) return Integer;

   function Subtract (A, B : Integer) return Integer;

   function Multiply (A, B : Integer) return Integer;

   function Divide (A, B : Integer) return Integer;

end Operations;
```

Listing 36: operations.adb

```
package body Operations is

   function Add (A, B : Integer) return Integer is
   begin
      return A + B;
   end Add;

   function Subtract (A, B : Integer) return Integer is
   begin
      return A - B;
   end Subtract;

   function Multiply (A, B : Integer) return Integer is
   begin
      return A * B;
   end Multiply;

   function Divide (A, B : Integer) return Integer is
   begin
      return A / B;
   end Divide;

end Operations;
```

Listing 37: operations-test.ads

```
package Operations.Test is

   procedure Display (A, B : Integer);

end Operations.Test;
```

Listing 38: operations-test.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Operations.Test is

   procedure Display (A, B : Integer) is
      A_Str : constant String := Integer'Image (A);
      B_Str : constant String := Integer'Image (B);
   begin
      Put_Line ("Operations:");
```

(continues on next page)

(continued from previous page)

```
      Put_Line (A_Str & " + " & B_Str & " = "
                & Integer'Image (Add (A, B))
                & ",");
      Put_Line (A_Str & " - " & B_Str & " = "
                & Integer'Image (Subtract (A, B))
                & ",");
      Put_Line (A_Str & " * " & B_Str & " = "
                & Integer'Image (Multiply (A, B))
                & ",");
      Put_Line (A_Str & " / " & B_Str & " = "
                & Integer'Image (Divide (A, B))
                & ",");
   end Display;

end Operations.Test;
```

Listing 39: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Operations;
with Operations.Test;  use Operations.Test;

procedure Main is

   type Test_Case_Index is
     (Operations_Chk,
      Operations_Display_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Operations_Chk =>
            Put_Line ("Add (100, 2) = "
                      & Integer'Image (Operations.Add (100, 2)));
            Put_Line ("Subtract (100, 2) = "
                      & Integer'Image (Operations.Subtract (100, 2)));
            Put_Line ("Multiply (100, 2) = "
                      & Integer'Image (Operations.Multiply (100, 2)));
            Put_Line ("Divide (100, 2) = "
                      & Integer'Image (Operations.Divide (100, 2)));
         when Operations_Display_Chk =>
            Display (10, 5);
            Display ( 1, 2);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.4 Strongly typed language

18.4.1 Colors

Listing 40: color_types.ads

```
package Color_Types is

   type HTML_Color is
     (Salmon,
      Firebrick,
      Red,
      Darkred,
      Lime,
      Forestgreen,
      Green,
      Darkgreen,
      Blue,
      Mediumblue,
      Darkblue);

   function To_Integer (C : HTML_Color) return Integer;

   type Basic_HTML_Color is
     (Red,
      Green,
      Blue);

   function To_HTML_Color (C : Basic_HTML_Color) return HTML_Color;

end Color_Types;
```

Listing 41: color_types.adb

```
package body Color_Types is

   function To_Integer (C : HTML_Color) return Integer is
   begin
      case C is
         when Salmon      => return 16#FA8072#;
         when Firebrick   => return 16#B22222#;
         when Red         => return 16#FF0000#;
         when Darkred     => return 16#8B0000#;
         when Lime        => return 16#00FF00#;
         when Forestgreen => return 16#228B22#;
         when Green       => return 16#008000#;
         when Darkgreen   => return 16#006400#;
         when Blue        => return 16#0000FF#;
         when Mediumblue  => return 16#0000CD#;
         when Darkblue    => return 16#00008B#;
      end case;

   end To_Integer;

   function To_HTML_Color (C : Basic_HTML_Color) return HTML_Color is
   begin
      case C is
         when Red   => return Red;
         when Green => return Green;
         when Blue  => return Blue;
      end case;
```

(continues on next page)

(continued from previous page)

```
28    end To_HTML_Color;
29
30 end Color_Types;
```

Listing 42: main.adb

```
1  with Ada.Command_Line; use Ada.Command_Line;
2  with Ada.Text_IO;      use Ada.Text_IO;
3  with Ada.Integer_Text_IO;
4
5  with Color_Types;       use Color_Types;
6
7  procedure Main is
8     type Test_Case_Index is
9       (HTML_Color_Range,
10       HTML_Color_To_Integer,
11       Basic_HTML_Color_To_HTML_Color);
12
13    procedure Check (TC : Test_Case_Index) is
14    begin
15       case TC is
16          when HTML_Color_Range =>
17             for I in HTML_Color'Range loop
18                Put_Line (HTML_Color'Image (I));
19             end loop;
20          when HTML_Color_To_Integer =>
21             for I in HTML_Color'Range loop
22                Ada.Integer_Text_IO.Put (Item  => To_Integer (I),
23                                         Width => 1,
24                                         Base  => 16);
25                New_Line;
26             end loop;
27          when Basic_HTML_Color_To_HTML_Color =>
28             for I in Basic_HTML_Color'Range loop
29                Put_Line (HTML_Color'Image (To_HTML_Color (I)));
30             end loop;
31       end case;
32    end Check;
33
34 begin
35    if Argument_Count < 1 then
36       Put_Line ("ERROR: missing arguments! Exiting...");
37       return;
38    elsif Argument_Count > 1 then
39       Put_Line ("Ignoring additional arguments...");
40    end if;
41
42    Check (Test_Case_Index'Value (Argument (1)));
43 end Main;
```

18.4.2 Integers

Listing 43: int_types.ads

```
1  package Int_Types is
2
3     type I_100 is range 0 .. 100;
4
5     type U_100 is mod 101;
```

(continues on next page)

(continued from previous page)

```
6
7     function To_I_100 (V : U_100) return I_100;
8
9     function To_U_100 (V : I_100) return U_100;
10
11    type D_50 is new I_100 range 10 .. 50;
12
13    subtype S_50 is I_100 range 10 .. 50;
14
15    function To_D_50 (V : I_100) return D_50;
16
17    function To_S_50 (V : I_100) return S_50;
18
19    function To_I_100 (V : D_50) return I_100;
20
21 end Int_Types;
```

Listing 44: int_types.adb

```
1  package body Int_Types is
2
3     function To_I_100 (V : U_100) return I_100 is
4     begin
5        return I_100 (V);
6     end To_I_100;
7
8     function To_U_100 (V : I_100) return U_100 is
9     begin
10       return U_100 (V);
11    end To_U_100;
12
13    function To_D_50 (V : I_100) return D_50 is
14       Min : constant I_100 := I_100 (D_50'First);
15       Max : constant I_100 := I_100 (D_50'Last);
16    begin
17       if V > Max then
18          return D_50'Last;
19       elsif V < Min then
20          return D_50'First;
21       else
22          return D_50 (V);
23       end if;
24    end To_D_50;
25
26    function To_S_50 (V : I_100) return S_50 is
27    begin
28       if V > S_50'Last then
29          return S_50'Last;
30       elsif V < S_50'First then
31          return S_50'First;
32       else
33          return V;
34       end if;
35    end To_S_50;
36
37    function To_I_100 (V : D_50) return I_100 is
38    begin
39       return I_100 (V);
40    end To_I_100;
41
42 end Int_Types;
```

Listing 45: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Int_Types;        use Int_Types;

procedure Main is
   package I_100_IO is new Ada.Text_IO.Integer_IO (I_100);
   package U_100_IO is new Ada.Text_IO.Modular_IO (U_100);
   package D_50_IO  is new Ada.Text_IO.Integer_IO (D_50);

   use I_100_IO;
   use U_100_IO;
   use D_50_IO;

   type Test_Case_Index is
     (I_100_Range,
      U_100_Range,
      U_100_Wraparound,
      U_100_To_I_100,
      I_100_To_U_100,
      D_50_Range,
      S_50_Range,
      I_100_To_D_50,
      I_100_To_S_50,
      D_50_To_I_100,
      S_50_To_I_100);

   procedure Check (TC : Test_Case_Index) is
   begin
      I_100_IO.Default_Width := 1;
      U_100_IO.Default_Width := 1;
      D_50_IO.Default_Width  := 1;

      case TC is
         when I_100_Range =>
            Put (I_100'First);
            New_Line;
            Put (I_100'Last);
            New_Line;
         when U_100_Range =>
            Put (U_100'First);
            New_Line;
            Put (U_100'Last);
            New_Line;
         when U_100_Wraparound =>
            Put (U_100'First - 1);
            New_Line;
            Put (U_100'Last + 1);
            New_Line;
         when U_100_To_I_100 =>
            for I in U_100'Range loop
               I_100_IO.Put (To_I_100 (I));
               New_Line;
            end loop;
         when I_100_To_U_100 =>
            for I in I_100'Range loop
               Put (To_U_100 (I));
               New_Line;
            end loop;
```

(continues on next page)

(continued from previous page)

```
60          when D_50_Range =>
61             Put (D_50'First);
62             New_Line;
63             Put (D_50'Last);
64             New_Line;
65          when S_50_Range =>
66             Put (S_50'First);
67             New_Line;
68             Put (S_50'Last);
69             New_Line;
70          when I_100_To_D_50 =>
71             for I in I_100'Range loop
72                Put (To_D_50 (I));
73                New_Line;
74             end loop;
75          when I_100_To_S_50 =>
76             for I in I_100'Range loop
77                Put (To_S_50 (I));
78                New_Line;
79             end loop;
80          when D_50_To_I_100 =>
81             for I in D_50'Range loop
82                Put (To_I_100 (I));
83                New_Line;
84             end loop;
85          when S_50_To_I_100 =>
86             for I in S_50'Range loop
87                Put (I);
88                New_Line;
89             end loop;
90       end case;
91    end Check;
92
93 begin
94    if Argument_Count < 1 then
95       Put_Line ("ERROR: missing arguments! Exiting...");
96       return;
97    elsif Argument_Count > 1 then
98       Put_Line ("Ignoring additional arguments...");
99    end if;
100
101   Check (Test_Case_Index'Value (Argument (1)));
102 end Main;
```

18.4.3 Temperatures

Listing 46: temperature_types.ads

```
1  package Temperature_Types is
2
3     type Celsius is digits 6 range -273.15 .. 5504.85;
4
5     type Int_Celsius is range -273 .. 5505;
6
7     function To_Celsius (T : Int_Celsius) return Celsius;
8
9     function To_Int_Celsius (T : Celsius) return Int_Celsius;
10
11    type Kelvin is digits 6 range 0.0 .. 5778.00;
12
```

(continues on next page)

(continued from previous page)

```
   function To_Celsius (T : Kelvin) return Celsius;

   function To_Kelvin (T : Celsius) return Kelvin;

end Temperature_Types;
```

Listing 47: temperature_types.adb

```
package body Temperature_Types is

   function To_Celsius (T : Int_Celsius) return Celsius is
      Min : constant Float := Float (Celsius'First);
      Max : constant Float := Float (Celsius'Last);

      F   : constant Float := Float (T);
   begin
      if F > Max then
         return Celsius (Max);
      elsif F < Min then
         return Celsius (Min);
      else
         return Celsius (F);
      end if;
   end To_Celsius;

   function To_Int_Celsius (T : Celsius) return Int_Celsius is
   begin
      return Int_Celsius (T);
   end To_Int_Celsius;

   function To_Celsius (T : Kelvin) return Celsius is
      F : constant Float := Float (T);
   begin
      return Celsius (F - 273.15);
   end To_Celsius;

   function To_Kelvin (T : Celsius) return Kelvin is
      F : constant Float := Float (T);
   begin
      return Kelvin (F + 273.15);
   end To_Kelvin;

end Temperature_Types;
```

Listing 48: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Temperature_Types; use Temperature_Types;

procedure Main is
   package Celsius_IO     is new Ada.Text_IO.Float_IO (Celsius);
   package Kelvin_IO      is new Ada.Text_IO.Float_IO (Kelvin);
   package Int_Celsius_IO is new Ada.Text_IO.Integer_IO (Int_Celsius);

   use Celsius_IO;
   use Kelvin_IO;
   use Int_Celsius_IO;

```

(continues on next page)

(continued from previous page)

```
15    type Test_Case_Index is
16      (Celsius_Range,
17       Celsius_To_Int_Celsius,
18       Int_Celsius_To_Celsius,
19       Kelvin_To_Celsius,
20       Celsius_To_Kelvin);
21
22    procedure Check (TC : Test_Case_Index) is
23    begin
24       Celsius_IO.Default_Fore := 1;
25       Kelvin_IO.Default_Fore  := 1;
26       Int_Celsius_IO.Default_Width := 1;
27
28       case TC is
29          when Celsius_Range =>
30             Put (Celsius'First);
31             New_Line;
32             Put (Celsius'Last);
33             New_Line;
34          when Celsius_To_Int_Celsius =>
35             Put (To_Int_Celsius (Celsius'First));
36             New_Line;
37             Put (To_Int_Celsius (0.0));
38             New_Line;
39             Put (To_Int_Celsius (Celsius'Last));
40             New_Line;
41          when Int_Celsius_To_Celsius =>
42             Put (To_Celsius (Int_Celsius'First));
43             New_Line;
44             Put (To_Celsius (0));
45             New_Line;
46             Put (To_Celsius (Int_Celsius'Last));
47             New_Line;
48          when Kelvin_To_Celsius =>
49             Put (To_Celsius (Kelvin'First));
50             New_Line;
51             Put (To_Celsius (0));
52             New_Line;
53             Put (To_Celsius (Kelvin'Last));
54             New_Line;
55          when Celsius_To_Kelvin =>
56             Put (To_Kelvin (Celsius'First));
57             New_Line;
58             Put (To_Kelvin (Celsius'Last));
59             New_Line;
60       end case;
61    end Check;
62
63 begin
64    if Argument_Count < 1 then
65       Put_Line ("ERROR: missing arguments! Exiting...");
66       return;
67    elsif Argument_Count > 1 then
68       Put_Line ("Ignoring additional arguments...");
69    end if;
70
71    Check (Test_Case_Index'Value (Argument (1)));
72 end Main;
```

18.5 Records

18.5.1 Directions

Listing 49: directions.ads

```
package Directions is

   type Angle_Mod is mod 360;

   type Direction is
     (North,
      Northeast,
      East,
      Southeast,
      South,
      Southwest,
      West,
      Northwest);

   function To_Direction (N: Angle_Mod) return Direction;

   type Ext_Angle is record
      Angle_Elem     : Angle_Mod;
      Direction_Elem : Direction;
   end record;

   function To_Ext_Angle (N : Angle_Mod) return Ext_Angle;

   procedure Display (N : Ext_Angle);

end Directions;
```

Listing 50: directions.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Directions is

   procedure Display (N : Ext_Angle) is
   begin
      Put_Line ("Angle: "
                & Angle_Mod'Image (N.Angle_Elem)
                & " => "
                & Direction'Image (N.Direction_Elem)
                & ".");
   end Display;

   function To_Direction (N : Angle_Mod) return Direction is
   begin
      case N is
         when   0        => return North;
         when   1 ..  89 => return Northeast;
         when  90        => return East;
         when  91 .. 179 => return Southeast;
         when 180        => return South;
         when 181 .. 269 => return Southwest;
         when 270        => return West;
         when 271 .. 359 => return Northwest;
      end case;
   end To_Direction;
```

(continues on next page)

(continued from previous page)

```
27
28    function To_Ext_Angle (N : Angle_Mod) return Ext_Angle is
29    begin
30       return (Angle_Elem     => N,
31               Direction_Elem => To_Direction (N));
32    end To_Ext_Angle;
33
34 end Directions;
```

Listing 51: main.adb

```
1  with Ada.Command_Line;  use Ada.Command_Line;
2  with Ada.Text_IO;       use Ada.Text_IO;
3
4  with Directions;        use Directions;
5
6  procedure Main is
7     type Test_Case_Index is
8       (Direction_Chk);
9
10    procedure Check (TC : Test_Case_Index) is
11    begin
12       case TC is
13       when Direction_Chk =>
14          Display (To_Ext_Angle (0));
15          Display (To_Ext_Angle (30));
16          Display (To_Ext_Angle (45));
17          Display (To_Ext_Angle (90));
18          Display (To_Ext_Angle (91));
19          Display (To_Ext_Angle (120));
20          Display (To_Ext_Angle (180));
21          Display (To_Ext_Angle (250));
22          Display (To_Ext_Angle (270));
23       end case;
24    end Check;
25
26 begin
27    if Argument_Count < 1 then
28       Put_Line ("ERROR: missing arguments! Exiting...");
29       return;
30    elsif Argument_Count > 1 then
31       Put_Line ("Ignoring additional arguments...");
32    end if;
33
34    Check (Test_Case_Index'Value (Argument (1)));
35 end Main;
```

18.5.2 Colors

Listing 52: color_types.ads

```
1  package Color_Types is
2
3     type HTML_Color is
4       (Salmon,
5        Firebrick,
6        Red,
7        Darkred,
8        Lime,
```

(continues on next page)

(continued from previous page)

```
      Forestgreen,
      Green,
      Darkgreen,
      Blue,
      Mediumblue,
      Darkblue);

   function To_Integer (C : HTML_Color) return Integer;

   type Basic_HTML_Color is
     (Red,
      Green,
      Blue);

   function To_HTML_Color (C : Basic_HTML_Color) return HTML_Color;

   subtype Int_Color is Integer range 0 .. 255;

   type RGB is record
      Red   : Int_Color;
      Green : Int_Color;
      Blue  : Int_Color;
   end record;

   function To_RGB (C : HTML_Color) return RGB;

   function Image (C : RGB) return String;

end Color_Types;
```

Listing 53: color_types.adb

```
with Ada.Integer_Text_IO;

package body Color_Types is

   function To_Integer (C : HTML_Color) return Integer is
   begin
      case C is
         when Salmon      => return 16#FA8072#;
         when Firebrick   => return 16#B22222#;
         when Red         => return 16#FF0000#;
         when Darkred     => return 16#8B0000#;
         when Lime        => return 16#00FF00#;
         when Forestgreen => return 16#228B22#;
         when Green       => return 16#008000#;
         when Darkgreen   => return 16#006400#;
         when Blue        => return 16#0000FF#;
         when Mediumblue  => return 16#0000CD#;
         when Darkblue    => return 16#00008B#;
      end case;

   end To_Integer;

   function To_HTML_Color (C : Basic_HTML_Color) return HTML_Color is
   begin
      case C is
         when Red   => return Red;
         when Green => return Green;
         when Blue  => return Blue;
      end case;
```

(continues on next page)

(continued from previous page)

```
30    end To_HTML_Color;
31
32    function To_RGB (C : HTML_Color) return RGB is
33    begin
34       case C is
35          when Salmon      => return (16#FA#, 16#80#, 16#72#);
36          when Firebrick   => return (16#B2#, 16#22#, 16#22#);
37          when Red         => return (16#FF#, 16#00#, 16#00#);
38          when Darkred     => return (16#8B#, 16#00#, 16#00#);
39          when Lime        => return (16#00#, 16#FF#, 16#00#);
40          when Forestgreen => return (16#22#, 16#8B#, 16#22#);
41          when Green       => return (16#00#, 16#80#, 16#00#);
42          when Darkgreen   => return (16#00#, 16#64#, 16#00#);
43          when Blue        => return (16#00#, 16#00#, 16#FF#);
44          when Mediumblue  => return (16#00#, 16#00#, 16#CD#);
45          when Darkblue    => return (16#00#, 16#00#, 16#8B#);
46       end case;
47
48    end To_RGB;
49
50    function Image (C : RGB) return String is
51       subtype Str_Range is Integer range 1 .. 10;
52       SR : String (Str_Range);
53       SG : String (Str_Range);
54       SB : String (Str_Range);
55    begin
56       Ada.Integer_Text_IO.Put (To    => SR,
57                                Item  => C.Red,
58                                Base  => 16);
59       Ada.Integer_Text_IO.Put (To    => SG,
60                                Item  => C.Green,
61                                Base  => 16);
62       Ada.Integer_Text_IO.Put (To    => SB,
63                                Item  => C.Blue,
64                                Base  => 16);
65       return ("(Red => " & SR
66               & ", Green => " & SG
67               & ", Blue => "  & SB
68               &")");
69    end Image;
70
71 end Color_Types;
```

Listing 54: main.adb

```
1  with Ada.Command_Line; use Ada.Command_Line;
2  with Ada.Text_IO;      use Ada.Text_IO;
3
4  with Color_Types;      use Color_Types;
5
6  procedure Main is
7     type Test_Case_Index is
8       (HTML_Color_To_RGB);
9
10    procedure Check (TC : Test_Case_Index) is
11    begin
12       case TC is
13          when HTML_Color_To_RGB =>
14             for I in HTML_Color'Range loop
15                Put_Line (HTML_Color'Image (I) & " => "
16                          & Image (To_RGB (I)) & ".");
```

(continues on next page)

(continued from previous page)

```
            end loop;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.5.3 Inventory

Listing 55: inventory_pkg.ads

```
package Inventory_Pkg is

   type Item_Name is
     (Ballpoint_Pen, Oil_Based_Pen_Marker, Feather_Quill_Pen);

   function To_String (I : Item_Name) return String;

   type Item is record
      Name     : Item_Name;
      Quantity : Natural;
      Price    : Float;
   end record;

   function Init (Name     : Item_Name;
                  Quantity : Natural;
                  Price    : Float) return Item;

   procedure Add (Assets : in out Float;
                  I      : Item);

end Inventory_Pkg;
```

Listing 56: inventory_pkg.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Inventory_Pkg is

   function To_String (I : Item_Name) return String is
   begin
      case I is
         when Ballpoint_Pen        => return "Ballpoint Pen";
         when Oil_Based_Pen_Marker => return "Oil-based Pen Marker";
         when Feather_Quill_Pen    => return "Feather Quill Pen";
      end case;
   end To_String;

   function Init (Name     : Item_Name;
                  Quantity : Natural;
                  Price    : Float) return Item is
```

(continues on next page)

(continued from previous page)

```
   begin
      Put_Line ("Item: " & To_String (Name) & ".");

      return (Name     => Name,
              Quantity => Quantity,
              Price    => Price);
   end Init;

   procedure Add (Assets : in out Float;
                  I      : Item) is
   begin
      Assets := Assets + Float (I.Quantity) * I.Price;
   end Add;

end Inventory_Pkg;
```

Listing 57: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Inventory_Pkg;     use Inventory_Pkg;

procedure Main is
   --  Remark: the following line is not relevant.
   F   : array (1 .. 10) of Float := (others => 42.42);

   type Test_Case_Index is
     (Inventory_Chk);

   procedure Display (Assets : Float) is
      package F_IO is new Ada.Text_IO.Float_IO (Float);

      use F_IO;
   begin
      Put ("Assets: $");
      Put (Assets, 1, 2, 0);
      Put (".");
      New_Line;
   end Display;

   procedure Check (TC : Test_Case_Index) is
      I      : Item;
      Assets : Float := 0.0;

      --  Please ignore the following three lines!
      pragma Warnings (Off, "default initialization");
      for Assets'Address use F'Address;
      pragma Warnings (On, "default initialization");
   begin
      case TC is
      when Inventory_Chk =>
         I := Init (Ballpoint_Pen,        185,  0.15);
         Add (Assets, I);
         Display (Assets);

         I := Init (Oil_Based_Pen_Marker, 100,  9.0);
         Add (Assets, I);
         Display (Assets);

         I := Init (Feather_Quill_Pen,      2, 40.0);
```

(continues on next page)

(continued from previous page)

```
         Add (Assets, I);
         Display (Assets);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.6 Arrays

18.6.1 Constrained Array

Listing 58: constrained_arrays.ads

```
package Constrained_Arrays is

   type My_Index is range 1 .. 10;

   type My_Array is array (My_Index) of Integer;

   function Init return My_Array;

   procedure Double (A : in out My_Array);

   function First_Elem (A : My_Array) return Integer;

   function Last_Elem (A : My_Array) return Integer;

   function Length (A : My_Array) return Integer;

   A : My_Array := (1, 2, others => 42);

end Constrained_Arrays;
```

Listing 59: constrained_arrays.adb

```
package body Constrained_Arrays is

   function Init return My_Array is
      A : My_Array;
   begin
      for I in My_Array'Range loop
         A (I) := Integer (I);
      end loop;

      return A;
   end Init;

   procedure Double (A : in out My_Array) is
   begin
```

(continues on next page)

(continued from previous page)

```
      for I in A'Range loop
         A (I) := A (I) * 2;
      end loop;
   end Double;

   function First_Elem (A : My_Array) return Integer is
   begin
      return A (A'First);
   end First_Elem;

   function Last_Elem (A : My_Array) return Integer is
   begin
      return A (A'Last);
   end Last_Elem;

   function Length (A : My_Array) return Integer is
   begin
      return A'Length;
   end Length;

end Constrained_Arrays;
```

Listing 60: main.adb

```
with Ada.Command_Line;   use Ada.Command_Line;
with Ada.Text_IO;        use Ada.Text_IO;

with Constrained_Arrays; use Constrained_Arrays;

procedure Main is
   type Test_Case_Index is
     (Range_Chk,
      Array_Range_Chk,
      A_Obj_Chk,
      Init_Chk,
      Double_Chk,
      First_Elem_Chk,
      Last_Elem_Chk,
      Length_Chk);

   procedure Check (TC : Test_Case_Index) is
      AA : My_Array;

      procedure Display (A : My_Array) is
      begin
         for I in A'Range loop
            Put_Line (Integer'Image (A (I)));
         end loop;
      end Display;

      procedure Local_Init (A : in out My_Array) is
      begin
         A := (100, 90, 80, 10, 20, 30, 40, 60, 50, 70);
      end Local_Init;
   begin
      case TC is
      when Range_Chk =>
         for I in My_Index loop
            Put_Line (My_Index'Image (I));
         end loop;
      when Array_Range_Chk =>
```

(continues on next page)

(continued from previous page)

```
38          for I in My_Array'Range loop
39             Put_Line (My_Index'Image (I));
40          end loop;
41       when A_Obj_Chk =>
42          Display (A);
43       when Init_Chk =>
44          AA := Init;
45          Display (AA);
46       when Double_Chk =>
47          Local_Init (AA);
48          Double (AA);
49          Display (AA);
50       when First_Elem_Chk =>
51          Local_Init (AA);
52          Put_Line (Integer'Image (First_Elem (AA)));
53       when Last_Elem_Chk =>
54          Local_Init (AA);
55          Put_Line (Integer'Image (Last_Elem (AA)));
56       when Length_Chk =>
57          Put_Line (Integer'Image (Length (AA)));
58       end case;
59    end Check;
60
61 begin
62    if Argument_Count < 1 then
63       Put_Line ("ERROR: missing arguments! Exiting...");
64       return;
65    elsif Argument_Count > 1 then
66       Put_Line ("Ignoring additional arguments...");
67    end if;
68
69    Check (Test_Case_Index'Value (Argument (1)));
70 end Main;
```

18.6.2 Colors: Lookup-Table

Listing 61: color_types.ads

```
1  package Color_Types is
2
3     type HTML_Color is
4       (Salmon,
5        Firebrick,
6        Red,
7        Darkred,
8        Lime,
9        Forestgreen,
10       Green,
11       Darkgreen,
12       Blue,
13       Mediumblue,
14       Darkblue);
15
16    subtype Int_Color is Integer range 0 .. 255;
17
18    type RGB is record
19       Red   : Int_Color;
20       Green : Int_Color;
21       Blue  : Int_Color;
22    end record;
```

(continues on next page)

(continued from previous page)

```
23
24    function To_RGB (C : HTML_Color) return RGB;
25
26    function Image (C : RGB) return String;
27
28    type HTML_Color_RGB is array (HTML_Color) of RGB;
29
30    To_RGB_Lookup_Table : constant HTML_Color_RGB
31      := (Salmon      => (16#FA#, 16#80#, 16#72#),
32          Firebrick   => (16#B2#, 16#22#, 16#22#),
33          Red         => (16#FF#, 16#00#, 16#00#),
34          Darkred     => (16#8B#, 16#00#, 16#00#),
35          Lime        => (16#00#, 16#FF#, 16#00#),
36          Forestgreen => (16#22#, 16#8B#, 16#22#),
37          Green       => (16#00#, 16#80#, 16#00#),
38          Darkgreen   => (16#00#, 16#64#, 16#00#),
39          Blue        => (16#00#, 16#00#, 16#FF#),
40          Mediumblue  => (16#00#, 16#00#, 16#CD#),
41          Darkblue    => (16#00#, 16#00#, 16#8B#));
42
43 end Color_Types;
```

Listing 62: color_types.adb

```
1  with Ada.Integer_Text_IO;
2  package body Color_Types is
3
4     function To_RGB (C : HTML_Color) return RGB is
5     begin
6        return To_RGB_Lookup_Table (C);
7     end To_RGB;
8
9     function Image (C : RGB) return String is
10       subtype Str_Range is Integer range 1 .. 10;
11       SR : String (Str_Range);
12       SG : String (Str_Range);
13       SB : String (Str_Range);
14    begin
15       Ada.Integer_Text_IO.Put (To    => SR,
16                                Item  => C.Red,
17                                Base  => 16);
18       Ada.Integer_Text_IO.Put (To    => SG,
19                                Item  => C.Green,
20                                Base  => 16);
21       Ada.Integer_Text_IO.Put (To    => SB,
22                                Item  => C.Blue,
23                                Base  => 16);
24       return ("(Red => " & SR
25               & ", Green => " & SG
26               & ", Blue => "  & SB
27               &")");
28    end Image;
29
30 end Color_Types;
```

Listing 63: main.adb

```
1  with Ada.Command_Line;     use Ada.Command_Line;
2  with Ada.Text_IO;          use Ada.Text_IO;
3
```

(continues on next page)

(continued from previous page)

```
with Color_Types;          use Color_Types;

procedure Main is
   type Test_Case_Index is
     (Color_Table_Chk,
      HTML_Color_To_Integer_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Color_Table_Chk =>
            Put_Line ("Size of HTML_Color_RGB: "
                      & Integer'Image (HTML_Color_RGB'Length));
            Put_Line ("Firebrick: "
                      & Image (To_RGB_Lookup_Table (Firebrick)));
         when HTML_Color_To_Integer_Chk =>
            for I in HTML_Color'Range loop
               Put_Line (HTML_Color'Image (I) & " => "
                         & Image (To_RGB (I)) & ".");
            end loop;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.6.3 Unconstrained Array

Listing 64: unconstrained_arrays.ads

```
package Unconstrained_Arrays is

   type My_Array is array (Positive range <>) of Integer;

   procedure Init (A : in out My_Array);

   function Init (I, L : Positive) return My_Array;

   procedure Double (A : in out My_Array);

   function Diff_Prev_Elem (A : My_Array) return My_Array;

end Unconstrained_Arrays;
```

Listing 65: unconstrained_arrays.adb

```
package body Unconstrained_Arrays is

   procedure Init (A : in out My_Array) is
      Y : Natural := A'Last;
   begin
```

(continues on next page)

(continued from previous page)

```
      for I in A'Range loop
         A (I) := Y;
         Y := Y - 1;
      end loop;
   end Init;

   function Init (I, L : Positive) return My_Array is
      A : My_Array (I .. I + L - 1);
   begin
      Init (A);
      return A;
   end Init;

   procedure Double (A : in out My_Array) is
   begin
      for I in A'Range loop
         A (I) := A (I) * 2;
      end loop;
   end Double;

   function Diff_Prev_Elem (A : My_Array) return My_Array is
      A_Out : My_Array (A'Range);
   begin
      A_Out (A'First) := 0;
      for I in A'First + 1 .. A'Last loop
         A_Out (I) := A (I) - A (I - 1);
      end loop;

      return A_Out;
   end Diff_Prev_Elem;

end Unconstrained_Arrays;
```

Listing 66: main.adb

```
with Ada.Command_Line;     use Ada.Command_Line;
with Ada.Text_IO;          use Ada.Text_IO;

with Unconstrained_Arrays; use Unconstrained_Arrays;

procedure Main is
   type Test_Case_Index is
     (Init_Chk,
      Init_Proc_Chk,
      Double_Chk,
      Diff_Prev_Chk,
      Diff_Prev_Single_Chk);

   procedure Check (TC : Test_Case_Index) is
      AA : My_Array (1 .. 5);
      AB : My_Array (5 .. 9);

      procedure Display (A : My_Array) is
      begin
         for I in A'Range loop
            Put_Line (Integer'Image (A (I)));
         end loop;
      end Display;

      procedure Local_Init (A : in out My_Array) is
      begin
```

(continues on next page)

(continued from previous page)

```
27          A := (1, 2, 5, 10, -10);
28       end Local_Init;
29
30    begin
31       case TC is
32       when Init_Chk =>
33          AA := Init (AA'First, AA'Length);
34          AB := Init (AB'First, AB'Length);
35          Display (AA);
36          Display (AB);
37       when Init_Proc_Chk =>
38          Init (AA);
39          Init (AB);
40          Display (AA);
41          Display (AB);
42       when Double_Chk =>
43          Local_Init (AB);
44          Double (AB);
45          Display (AB);
46       when Diff_Prev_Chk =>
47          Local_Init (AB);
48          AB := Diff_Prev_Elem (AB);
49          Display (AB);
50       when Diff_Prev_Single_Chk =>
51          declare
52             A1 : My_Array (1 .. 1) := (1 => 42);
53          begin
54             A1 := Diff_Prev_Elem (A1);
55             Display (A1);
56          end;
57       end case;
58    end Check;
59
60 begin
61    if Argument_Count < 1 then
62       Put_Line ("ERROR: missing arguments! Exiting...");
63       return;
64    elsif Argument_Count > 1 then
65       Put_Line ("Ignoring additional arguments...");
66    end if;
67
68    Check (Test_Case_Index'Value (Argument (1)));
69 end Main;
```

18.6.4 Product info

Listing 67: product_info_pkg.ads

```
1  package Product_Info_Pkg is
2
3     subtype Quantity is Natural;
4
5     subtype Currency is Float;
6
7     type Product_Info is record
8        Units : Quantity;
9        Price : Currency;
10    end record;
11
12    type Product_Infos is array (Positive range <>) of Product_Info;
```

(continues on next page)

(continued from previous page)

```
13
14    type Currency_Array is array (Positive range <>) of Currency;
15
16    procedure Total (P   : Product_Infos;
17                     Tot : out Currency_Array);
18
19    function Total (P : Product_Infos) return Currency_Array;
20
21    function Total (P : Product_Infos) return Currency;
22
23 end Product_Info_Pkg;
```

Listing 68: product_info_pkg.adb

```
1  package body Product_Info_Pkg is
2
3     --  Get total for single product
4     function Total (P : Product_Info) return Currency is
5        (Currency (P.Units) * P.Price);
6
7     procedure Total (P   : Product_Infos;
8                      Tot : out Currency_Array) is
9     begin
10       for I in P'Range loop
11          Tot (I) := Total (P (I));
12       end loop;
13    end Total;
14
15    function Total (P : Product_Infos) return Currency_Array
16    is
17       Tot : Currency_Array (P'Range);
18    begin
19       Total (P, Tot);
20       return Tot;
21    end Total;
22
23    function Total (P : Product_Infos) return Currency
24    is
25       Tot : Currency := 0.0;
26    begin
27      for I in P'Range loop
28          Tot := Tot + Total (P (I));
29       end loop;
30       return Tot;
31    end Total;
32
33 end Product_Info_Pkg;
```

Listing 69: main.adb

```
1  with Ada.Command_Line;   use Ada.Command_Line;
2  with Ada.Text_IO;        use Ada.Text_IO;
3
4  with Product_Info_Pkg;   use Product_Info_Pkg;
5
6  procedure Main is
7     package Currency_IO is new Ada.Text_IO.Float_IO (Currency);
8
9     type Test_Case_Index is
10      (Total_Func_Chk,
```

(continues on next page)

(continued from previous page)

```
      Total_Proc_Chk,
      Total_Value_Chk);

   procedure Check (TC : Test_Case_Index) is
      subtype Test_Range is Positive range 1 .. 5;

      P    : Product_Infos (Test_Range);
      Tots : Currency_Array (Test_Range);
      Tot  : Currency;

      procedure Display (Tots : Currency_Array) is
      begin
         for I in Tots'Range loop
            Currency_IO.Put (Tots (I));
            New_Line;
         end loop;
      end Display;

      procedure Local_Init (P : in out Product_Infos) is
      begin
         P := ((1,   0.5),
               (2,  10.0),
               (5,  40.0),
               (10, 10.0),
               (10, 20.0));
      end Local_Init;

   begin
      Currency_IO.Default_Fore := 1;
      Currency_IO.Default_Aft  := 2;
      Currency_IO.Default_Exp  := 0;

      case TC is
      when Total_Func_Chk =>
         Local_Init (P);
         Tots := Total (P);
         Display (Tots);
      when Total_Proc_Chk =>
         Local_Init (P);
         Total (P, Tots);
         Display (Tots);
      when Total_Value_Chk =>
         Local_Init (P);
         Tot := Total (P);
         Currency_IO.Put (Tot);
         New_Line;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.6.5 String_10

Listing 70: strings_10.ads

```
package Strings_10 is

   subtype String_10 is String (1 .. 10);

   --  Using "type String_10 is..." is possible, too.

   function To_String_10 (S : String) return String_10;

end Strings_10;
```

Listing 71: strings_10.adb

```
package body Strings_10 is

   function To_String_10 (S : String) return String_10 is
      S_Out : String_10;
   begin
      for I in String_10'First .. Integer'Min (String_10'Last, S'Last) loop
         S_Out (I) := S (I);
      end loop;

      for I in Integer'Min (String_10'Last + 1, S'Last + 1) .. String_10'Last loop
         S_Out (I) := ' ';
      end loop;

      return S_Out;
   end To_String_10;

end Strings_10;
```

Listing 72: main.adb

```
with Ada.Command_Line;   use Ada.Command_Line;
with Ada.Text_IO;        use Ada.Text_IO;

with Strings_10;         use Strings_10;

procedure Main is
   type Test_Case_Index is
     (String_10_Long_Chk,
      String_10_Short_Chk);

   procedure Check (TC : Test_Case_Index) is
      SL   : constant String := "And this is a long string just for testing...";
      SS   : constant String := "Hey!";
      S_10 : String_10;

   begin
      case TC is
      when String_10_Long_Chk =>
         S_10 := To_String_10 (SL);
         Put_Line (String (S_10));
      when String_10_Short_Chk =>
         S_10 := (others => ' ');
         S_10 := To_String_10 (SS);
         Put_Line (String (S_10));
      end case;
   end Check;
```

(continues on next page)

(continued from previous page)

```

begin
   if Argument_Count < 1 then
      Ada.Text_IO.Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Ada.Text_IO.Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.6.6 List of Names

Listing 73: names_ages.ads

```
package Names_Ages is

   Max_People : constant Positive := 10;

   subtype Name_Type is String (1 .. 50);

   type Age_Type is new Natural;

   type Person is record
      Name  : Name_Type;
      Age   : Age_Type;
   end record;

   type People_Array is array (Positive range <>) of Person;

   type People is record
      People_A   : People_Array (1 .. Max_People);
      Last_Valid : Natural;
   end record;

   procedure Reset (P : in out People);

   procedure Add (P    : in out People;
                  Name : String);

   function Get (P    : People;
                 Name : String) return Age_Type;

   procedure Update (P    : in out People;
                     Name : String;
                     Age  : Age_Type);

   procedure Display (P : People);

end Names_Ages;
```

Listing 74: names_ages.adb

```
with Ada.Text_IO;       use Ada.Text_IO;
with Ada.Strings;       use Ada.Strings;
with Ada.Strings.Fixed; use Ada.Strings.Fixed;

package body Names_Ages is
```

(continues on next page)

(continued from previous page)

```
6
7     function To_Name_Type (S : String) return Name_Type is
8        S_Out : Name_Type := (others => ' ');
9     begin
10       for I in 1 .. Integer'Min (S'Last, Name_Type'Last) loop
11          S_Out (I) := S (I);
12       end loop;
13
14       return S_Out;
15    end To_Name_Type;
16
17    procedure Init (P    : in out Person;
18                    Name :        String) is
19    begin
20       P.Name := To_Name_Type (Name);
21       P.Age := 0;
22    end Init;
23
24    function Match (P    : Person;
25                    Name : String) return Boolean is
26    begin
27       return P.Name = To_Name_Type (Name);
28    end Match;
29
30    function Get (P : Person) return Age_Type is
31    begin
32       return P.Age;
33    end Get;
34
35    procedure Update (P   : in out Person;
36                      Age :        Age_Type) is
37    begin
38       P.Age := Age;
39    end Update;
40
41    procedure Display (P : Person) is
42    begin
43       Put_Line ("NAME: " & Trim (P.Name, Right));
44       Put_Line ("AGE: "  & Age_Type'Image (P.Age));
45    end Display;
46
47    procedure Reset (P : in out People) is
48    begin
49       P.Last_Valid := 0;
50    end Reset;
51
52    procedure Add (P    : in out People;
53                   Name :        String) is
54    begin
55       P.Last_Valid := P.Last_Valid + 1;
56       Init (P.People_A (P.Last_Valid), Name);
57    end Add;
58
59    function Get (P    : People;
60                  Name : String) return Age_Type is
61    begin
62       for I in P.People_A'First .. P.Last_Valid loop
63          if Match (P.People_A (I), Name) then
64             return Get (P.People_A (I));
65          end if;
66       end loop;
```

(continues on next page)

(continued from previous page)

```

      return 0;
   end Get;

   procedure Update (P    : in out People;
                     Name :        String;
                     Age  :        Age_Type) is
   begin
      for I in P.People_A'First .. P.Last_Valid loop
         if Match (P.People_A (I), Name) then
            Update (P.People_A (I), Age);
         end if;
      end loop;
   end Update;

   procedure Display (P : People) is
   begin
      Put_Line ("LIST OF NAMES:");
      for I in P.People_A'First .. P.Last_Valid loop
         Display (P.People_A (I));
      end loop;
   end Display;

end Names_Ages;
```

Listing 75: main.adb

```
with Ada.Command_Line;   use Ada.Command_Line;
with Ada.Text_IO;        use Ada.Text_IO;

with Names_Ages;         use Names_Ages;

procedure Main is
   type Test_Case_Index is
     (Names_Ages_Chk,
      Get_Age_Chk);

   procedure Check (TC : Test_Case_Index) is
      P : People;
   begin
      case TC is
      when Names_Ages_Chk =>
         Reset (P);
         Add (P, "John");
         Add (P, "Patricia");
         Add (P, "Josh");
         Display (P);
         Update (P, "John",     18);
         Update (P, "Patricia", 35);
         Update (P, "Josh",     53);
         Display (P);
      when Get_Age_Chk =>
         Reset (P);
         Add (P, "Peter");
         Update (P, "Peter", 45);
         Put_Line ("Peter is "
                   & Age_Type'Image (Get (P, "Peter"))
                   & " years old.");
      end case;
   end Check;

```

(continues on next page)

(continued from previous page)

```
begin
   if Argument_Count < 1 then
      Ada.Text_IO.Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Ada.Text_IO.Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.7 More About Types

18.7.1 Aggregate Initialization

Listing 76: aggregates.ads

```
package Aggregates is

   type Rec is record
      W : Integer := 10;
      X : Integer := 11;
      Y : Integer := 12;
      Z : Integer := 13;
   end record;

   type Int_Arr is array (1 .. 20) of Integer;

   procedure Init (R : out Rec);

   procedure Init_Some (A : out Int_Arr);

   procedure Init (A : out Int_Arr);

end Aggregates;
```

Listing 77: aggregates.adb

```
package body Aggregates is

   procedure Init (R : out Rec) is
   begin
      R := (X      => 100,
            Y      => 200,
            others => <>);
   end Init;

   procedure Init_Some (A : out Int_Arr) is
   begin
      A := (1 .. 5 => 99,
            others => 100);
   end Init_Some;

   procedure Init (A : out Int_Arr) is
   begin
      A := (others => 5);
   end Init;

end Aggregates;
```

Listing 78: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Aggregates;        use Aggregates;

procedure Main is
   --  Remark: the following line is not relevant.
   F   : array (1 .. 10) of Float := (others => 42.42)
     with Unreferenced;

   type Test_Case_Index is
     (Default_Rec_Chk,
      Init_Rec_Chk,
      Init_Some_Arr_Chk,
      Init_Arr_Chk);

   procedure Check (TC : Test_Case_Index) is
      A : Int_Arr;
      R : Rec;
      DR : constant Rec := (others => <>);
   begin
      case TC is
         when Default_Rec_Chk =>
            R := DR;
            Put_Line ("Record Default:");
            Put_Line ("W => " & Integer'Image (R.W));
            Put_Line ("X => " & Integer'Image (R.X));
            Put_Line ("Y => " & Integer'Image (R.Y));
            Put_Line ("Z => " & Integer'Image (R.Z));
         when Init_Rec_Chk =>
            Init (R);
            Put_Line ("Record Init:");
            Put_Line ("W => " & Integer'Image (R.W));
            Put_Line ("X => " & Integer'Image (R.X));
            Put_Line ("Y => " & Integer'Image (R.Y));
            Put_Line ("Z => " & Integer'Image (R.Z));
         when Init_Some_Arr_Chk =>
            Init_Some (A);
            Put_Line ("Array Init_Some:");
            for I in A'Range loop
               Put_Line (Integer'Image (I) & " "
                         & Integer'Image (A (I)));
            end loop;
         when Init_Arr_Chk =>
            Init (A);
            Put_Line ("Array Init:");
            for I in A'Range loop
               Put_Line (Integer'Image (I) & " "
                         & Integer'Image (A (I)));
            end loop;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
```

(continues on next page)

(continued from previous page)

```
60    end if;
61
62    Check (Test_Case_Index'Value (Argument (1)));
63 end Main;
```

18.7.2 Versioning

Listing 79: versioning.ads

```
1  package Versioning is
2
3     type Version is record
4        Major       : Natural;
5        Minor       : Natural;
6        Maintenance : Natural;
7     end record;
8
9     function Convert (V : Version) return String;
10
11    function Convert (V : Version) return Float;
12
13 end Versioning;
```

Listing 80: versioning.adb

```
1  with Ada.Strings; use Ada.Strings;
2  with Ada.Strings.Fixed; use Ada.Strings.Fixed;
3
4  package body Versioning is
5
6     function Image_Trim (N : Natural) return String is
7        S_N : constant String := Trim (Natural'Image (N), Left);
8     begin
9        return S_N;
10    end Image_Trim;
11
12    function Convert (V : Version) return String is
13       S_Major : constant String := Image_Trim (V.Major);
14       S_Minor : constant String := Image_Trim (V.Minor);
15       S_Maint : constant String := Image_Trim (V.Maintenance);
16    begin
17       return (S_Major & "." & S_Minor & "." & S_Maint);
18    end Convert;
19
20    function Convert (V : Version) return Float is
21    begin
22       return Float (V.Major) + (Float (V.Minor) / 10.0);
23    end Convert;
24
25 end Versioning;
```

Listing 81: main.adb

```
1  with Ada.Command_Line;  use Ada.Command_Line;
2  with Ada.Text_IO;       use Ada.Text_IO;
3
4  with Versioning;        use Versioning;
5
6  procedure Main is
```

(continues on next page)

(continued from previous page)

```
   type Test_Case_Index is
     (Ver_String_Chk,
      Ver_Float_Chk);

   procedure Check (TC : Test_Case_Index) is
      V : constant Version := (1, 3, 23);
   begin
      case TC is
         when Ver_String_Chk =>
            Put_Line (Convert (V));
         when Ver_Float_Chk =>
            Put_Line (Float'Image (Convert (V)));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.7.3 Simple todo list

Listing 82: todo_lists.ads

```
package Todo_Lists is

   type Todo_Item is access String;

   type Todo_Items is array (Positive range <>) of Todo_Item;

   type Todo_List (Max_Len : Natural) is record
      Items : Todo_Items (1 .. Max_Len);
      Last  : Natural := 0;
   end record;

   procedure Add (Todos : in out Todo_List;
                  Item  : String);

   procedure Display (Todos : Todo_List);

end Todo_Lists;
```

Listing 83: todo_lists.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Todo_Lists is

   procedure Add (Todos : in out Todo_List;
                  Item  : String) is
   begin
      if Todos.Last < Todos.Items'Last then
         Todos.Last := Todos.Last + 1;
```

(continues on next page)

(continued from previous page)

```
         Todos.Items (Todos.Last) := new String'(Item);
      else
         Put_Line ("ERROR: list is full!");
      end if;
   end Add;

   procedure Display (Todos : Todo_List) is
   begin
      Put_Line ("TO-DO LIST");
      for I in Todos.Items'First .. Todos.Last loop
         Put_Line (Todos.Items (I).all);
      end loop;
   end Display;

end Todo_Lists;
```

Listing 84: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Todo_Lists;        use Todo_Lists;

procedure Main is
   type Test_Case_Index is
     (Todo_List_Chk);

   procedure Check (TC : Test_Case_Index) is
      T : Todo_List (10);
   begin
      case TC is
         when Todo_List_Chk =>
            Add (T, "Buy milk");
            Add (T, "Buy tea");
            Add (T, "Buy present");
            Add (T, "Buy tickets");
            Add (T, "Pay electricity bill");
            Add (T, "Schedule dentist appointment");
            Add (T, "Call sister");
            Add (T, "Revise spreasheet");
            Add (T, "Edit entry page");
            Add (T, "Select new design");
            Add (T, "Create upgrade plan");
            Display (T);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.7.4 Price list

Listing 85: price_lists.ads

```
package Price_Lists is

   type Price_Type is delta 0.01 digits 12;

   type Price_List_Array is array (Positive range <>) of Price_Type;

   type Price_List (Max : Positive) is record
      List : Price_List_Array (1 .. Max);
      Last : Natural := 0;
   end record;

   type Price_Result (Ok : Boolean) is record
      case Ok is
         when False =>
            null;
         when True =>
            Price : Price_Type;
      end case;
   end record;

   procedure Reset (Prices : in out Price_List);

   procedure Add (Prices : in out Price_List;
                  Item   : Price_Type);

   function Get (Prices : Price_List;
                 Idx    : Positive) return Price_Result;

   procedure Display (Prices : Price_List);

end Price_Lists;
```

Listing 86: price_lists.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Price_Lists is

   procedure Reset (Prices : in out Price_List) is
   begin
      Prices.Last := 0;
   end Reset;

   procedure Add (Prices : in out Price_List;
                  Item   : Price_Type) is
   begin
      if Prices.Last < Prices.List'Last then
         Prices.Last := Prices.Last + 1;
         Prices.List (Prices.Last) := Item;
      else
         Put_Line ("ERROR: list is full!");
      end if;
   end Add;

   function Get (Prices : Price_List;
                 Idx    : Positive) return Price_Result is
   begin
      if (Idx >= Prices.List'First and then
```

(continues on next page)

(continued from previous page)

```
          Idx <= Prices.Last)          then
         return Price_Result'(Ok    => True,
                              Price => Prices.List (Idx));
      else
         return Price_Result'(Ok    => False);
      end if;
   end Get;

   procedure Display (Prices : Price_List) is
   begin
      Put_Line ("PRICE LIST");
      for I in Prices.List'First .. Prices.Last loop
         Put_Line (Price_Type'Image (Prices.List (I)));
      end loop;
   end Display;

end Price_Lists;
```

Listing 87: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Price_Lists;       use Price_Lists;

procedure Main is
   type Test_Case_Index is
     (Price_Type_Chk,
      Price_List_Chk,
      Price_List_Get_Chk);

   procedure Check (TC : Test_Case_Index) is
      L : Price_List (10);

      procedure Local_Init_List is
      begin
         Reset (L);
         Add (L, 1.45);
         Add (L, 2.37);
         Add (L, 3.21);
         Add (L, 4.14);
         Add (L, 5.22);
         Add (L, 6.69);
         Add (L, 7.77);
         Add (L, 8.14);
         Add (L, 9.99);
         Add (L, 10.01);
      end Local_Init_List;

      procedure Get_Display (Idx : Positive) is
         R : constant Price_Result := Get (L, Idx);
      begin
         Put_Line ("Attempt Get # " & Positive'Image (Idx));
         if R.Ok then
            Put_Line ("Element # " & Positive'Image (Idx)
                      & " => "     & Price_Type'Image (R.Price));
         else
            declare
            begin
               Put_Line ("Element # " & Positive'Image (Idx)
                         & " => "     & Price_Type'Image (R.Price));
```

(continues on next page)

(continued from previous page)

```
            exception
               when others =>
                  Put_Line ("Element not available (as expected)");
            end;
         end if;

      end Get_Display;

   begin
      case TC is
         when Price_Type_Chk =>
            Put_Line ("The delta    value of Price_Type is "
                      & Price_Type'Image (Price_Type'Delta) & ";");
            Put_Line ("The minimum  value of Price_Type is "
                      & Price_Type'Image (Price_Type'First) & ";");
            Put_Line ("The maximum  value of Price_Type is "
                      & Price_Type'Image (Price_Type'Last)  & ";");
         when Price_List_Chk =>
            Local_Init_List;
            Display (L);
         when Price_List_Get_Chk =>
            Local_Init_List;
            Get_Display (5);
            Get_Display (40);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.8 Privacy

18.8.1 Directions

Listing 88: directions.ads

```
package Directions is

   type Angle_Mod is mod 360;

   type Direction is
     (North,
      Northwest,
      West,
      Southwest,
      South,
      Southeast,
      East);

   function To_Direction (N : Angle_Mod) return Direction;

```

(continues on next page)

(continued from previous page)

```
   type Ext_Angle is private;

   function To_Ext_Angle (N : Angle_Mod) return Ext_Angle;

   procedure Display (N : Ext_Angle);

private

   type Ext_Angle is record
      Angle_Elem     : Angle_Mod;
      Direction_Elem : Direction;
   end record;

end Directions;
```

Listing 89: directions.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Directions is

   procedure Display (N : Ext_Angle) is
   begin
      Put_Line ("Angle: "
                & Angle_Mod'Image (N.Angle_Elem)
                & " => "
                & Direction'Image (N.Direction_Elem)
                & ".");
   end Display;

   function To_Direction (N : Angle_Mod) return Direction is
   begin
      case N is
         when   0        => return East;
         when   1 ..  89 => return Northwest;
         when  90        => return North;
         when  91 .. 179 => return Northwest;
         when 180        => return West;
         when 181 .. 269 => return Southwest;
         when 270        => return South;
         when 271 .. 359 => return Southeast;
      end case;
   end To_Direction;

   function To_Ext_Angle (N : Angle_Mod) return Ext_Angle is
   begin
      return (Angle_Elem     => N,
              Direction_Elem => To_Direction (N));
   end To_Ext_Angle;

end Directions;
```

Listing 90: test_directions.adb

```
with Directions; use Directions;

procedure Test_Directions is
   type Ext_Angle_Array is array (Positive range <>) of Ext_Angle;

   All_Directions : constant Ext_Angle_Array (1 .. 6)
```

(continues on next page)

(continued from previous page)

```
     := (To_Ext_Angle (0),
         To_Ext_Angle (45),
         To_Ext_Angle (90),
         To_Ext_Angle (91),
         To_Ext_Angle (180),
         To_Ext_Angle (270));

begin
   for I in All_Directions'Range loop
      Display (All_Directions (I));
   end loop;

end Test_Directions;
```

Listing 91: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Test_Directions;

procedure Main is
     type Test_Case_Index is
     (Direction_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
      when Direction_Chk =>
         Test_Directions;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.8.2 Limited Strings

Listing 92: limited_strings.ads

```
package Limited_Strings is

   type Lim_String is limited private;

   function Init (S : String) return Lim_String;

   function Init (Max : Positive) return Lim_String;

   procedure Put_Line (LS : Lim_String);

   procedure Copy (From :        Lim_String;
```

(continues on next page)

(continued from previous page)

```
                  To   : in out Lim_String);

   function "=" (Ref, Dut : Lim_String) return Boolean;

private

   type Lim_String is access String;

end Limited_Strings;
```

Listing 93: limited_strings.adb

```
with Ada.Text_IO;

package body Limited_Strings
is

   function Init (S : String) return Lim_String is
      LS : constant Lim_String := new String'(S);
   begin
      return Ls;
   end Init;

   function Init (Max : Positive) return Lim_String is
      LS : constant Lim_String := new String (1 .. Max);
   begin
      LS.all := (others => '_');
      return LS;
   end Init;

   procedure Put_Line (LS : Lim_String) is
   begin
      Ada.Text_IO.Put_Line (LS.all);
   end Put_Line;

   function Get_Min_Last (A, B : Lim_String) return Positive is
   begin
      return Positive'Min (A'Last, B'Last);
   end Get_Min_Last;

   procedure Copy (From :        Lim_String;
                   To   : in out Lim_String) is
      Min_Last : constant Positive := Get_Min_Last (From, To);
   begin
      To (To'First .. Min_Last)    := From (To'First .. Min_Last);
      To (Min_Last + 1 .. To'Last) := (others => '_');
   end;

   function "=" (Ref, Dut : Lim_String) return Boolean is
      Min_Last : constant Positive := Get_Min_Last (Ref, Dut);
   begin
      for I in Dut'First .. Min_Last loop
         if Dut (I) /= Ref (I) then
            return False;
         end if;
      end loop;

      return True;
   end;

end Limited_Strings;
```

Listing 94: check_lim_string.adb

```
with Ada.Text_IO;     use Ada.Text_IO;

with Limited_Strings; use Limited_Strings;

procedure Check_Lim_String is
   S  : constant String := "----------";
   S1 : constant Lim_String := Init ("Hello World");
   S2 : constant Lim_String := Init (30);
   S3 : Lim_String := Init (5);
   S4 : Lim_String := Init (S & S & S);
begin
   Put ("S1 => ");
   Put_Line (S1);
   Put ("S2 => ");
   Put_Line (S2);

   if S1 = S2 then
      Put_Line ("S1 is equal to S2.");
   else
      Put_Line ("S1 isn't equal to S2.");
   end if;

   Copy (From => S1, To => S3);
   Put ("S3 => ");
   Put_Line (S3);

   if S1 = S3 then
      Put_Line ("S1 is equal to S3.");
   else
      Put_Line ("S1 isn't equal to S3.");
   end if;

   Copy (From => S1, To => S4);
   Put ("S4 => ");
   Put_Line (S4);

   if S1 = S4 then
      Put_Line ("S1 is equal to S4.");
   else
      Put_Line ("S1 isn't equal to S4.");
   end if;
end Check_Lim_String;
```

Listing 95: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Check_Lim_String;

procedure Main is
   type Test_Case_Index is
     (Lim_String_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
      when Lim_String_Chk =>
         Check_Lim_String;
```

(continues on next page)

(continued from previous page)

```
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.9 Generics

18.9.1 Display Array

Listing 96: display_array.ads

```
generic
   type T_Range is range <>;
   type T_Element is private;
   type T_Array is array (T_Range range <>) of T_Element;
   with function Image (E : T_Element) return String;
procedure Display_Array (Header : String;
                         A      : T_Array);
```

Listing 97: display_array.adb

```
with Ada.Text_IO; use Ada.Text_IO;

procedure Display_Array (Header : String;
                         A      : T_Array) is
begin
   Put_Line (Header);
   for I in A'Range loop
      Put_Line (T_Range'Image (I) & ": " & Image (A (I)));
   end loop;
end Display_Array;
```

Listing 98: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_Array;

procedure Main is
   type Test_Case_Index is (Int_Array_Chk,
                            Point_Array_Chk);

   procedure Test_Int_Array is
      type Int_Array is array (Positive range <>) of Integer;

      procedure Display_Int_Array is new
        Display_Array (T_Range => Positive,
                       T_Element => Integer,
```

(continues on next page)

(continued from previous page)

```
                        T_Array   => Int_Array,
                        Image     => Integer'Image);

      A : constant Int_Array (1 .. 5) := (1, 2, 5, 7, 10);
   begin
      Display_Int_Array ("Integers", A);
   end Test_Int_Array;

   procedure Test_Point_Array is
      type Point is record
         X : Float;
         Y : Float;
      end record;

      type Point_Array is array (Natural range <>) of Point;

      function Image (P : Point) return String is
      begin
         return "(" & Float'Image (P.X)
           & ", " & Float'Image (P.Y) & ")";
      end Image;

      procedure Display_Point_Array is new
        Display_Array (T_Range   => Natural,
                       T_Element => Point,
                       T_Array   => Point_Array,
                       Image     => Image);

      A : constant Point_Array (0 .. 3) := ((1.0, 0.5), (2.0, -0.5),
                                            (5.0, 2.0), (-0.5, 2.0));
   begin
      Display_Point_Array ("Points", A);
   end Test_Point_Array;

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Int_Array_Chk =>
            Test_Int_Array;
         when Point_Array_Chk =>
            Test_Point_Array;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.9.2 Average of Array of Float

Listing 99: average.ads

```
generic
   type T_Range is range <>;
   type T_Element is digits <>;
   type T_Array is array (T_Range range <>) of T_Element;
function Average (A : T_Array) return T_Element;
```

Listing 100: average.adb

```
function Average (A : T_Array) return T_Element is
   Acc : Float := 0.0;
begin
   for I in A'Range loop
      Acc := Acc + Float (A (I));
   end loop;

   return T_Element (Acc / Float (A'Length));
end Average;
```

Listing 101: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Average;

procedure Main is
   type Test_Case_Index is (Float_Array_Chk,
                            Digits_7_Float_Array_Chk);

   procedure Test_Float_Array is
      type Float_Array is array (Positive range <>) of Float;

      function Average_Float is new
        Average (T_Range   => Positive,
                 T_Element => Float,
                 T_Array   => Float_Array);

      A : constant Float_Array (1 .. 5) := (1.0, 3.0, 5.0, 7.5, -12.5);
   begin
      Put_Line ("Average: " & Float'Image (Average_Float (A)));
   end Test_Float_Array;

   procedure Test_Digits_7_Float_Array is
      type Custom_Float is digits 7 range 0.0 .. 1.0;

      type Float_Array is
        array (Integer range <>) of Custom_Float;

      function Average_Float is new
        Average (T_Range   => Integer,
                 T_Element => Custom_Float,
                 T_Array   => Float_Array);

      A : constant Float_Array (-1 .. 3) := (0.5, 0.0, 1.0, 0.6, 0.5);
   begin
      Put_Line ("Average: "
                & Custom_Float'Image (Average_Float (A)));
   end Test_Digits_7_Float_Array;

```

(continues on next page)

(continued from previous page)

```
40    procedure Check (TC : Test_Case_Index) is
41    begin
42       case TC is
43          when Float_Array_Chk =>
44             Test_Float_Array;
45          when Digits_7_Float_Array_Chk =>
46             Test_Digits_7_Float_Array;
47       end case;
48    end Check;
49
50 begin
51    if Argument_Count < 1 then
52       Put_Line ("ERROR: missing arguments! Exiting...");
53       return;
54    elsif Argument_Count > 1 then
55       Put_Line ("Ignoring additional arguments...");
56    end if;
57
58    Check (Test_Case_Index'Value (Argument (1)));
59 end Main;
```

18.9.3 Average of Array of Any Type

Listing 102: average.ads

```
1  generic
2     type T_Range is range <>;
3     type T_Element is private;
4     type T_Array is array (T_Range range <>) of T_Element;
5     with function To_Float (E : T_Element) return Float is <>;
6  function Average (A : T_Array) return Float;
```

Listing 103: average.adb

```
1  function Average (A : T_Array) return Float is
2     Acc : Float := 0.0;
3  begin
4     for I in A'Range loop
5        Acc := Acc + To_Float (A (I));
6     end loop;
7
8     return Acc / Float (A'Length);
9  end Average;
```

Listing 104: test_item.ads

```
1  procedure Test_Item;
```

Listing 105: test_item.adb

```
1  with Ada.Text_IO;      use Ada.Text_IO;
2
3  with Average;
4
5  procedure Test_Item is
6     package F_IO is new Ada.Text_IO.Float_IO (Float);
7
8     type Amount is delta 0.01 digits 12;
9
```

(continues on next page)

(continued from previous page)

```
   type Item is record
      Quantity : Natural;
      Price    : Amount;
   end record;

   type Item_Array is
     array (Positive range <>) of Item;

   function Get_Total (I : Item) return Float is
     (Float (I.Quantity) * Float (I.Price));

   function Get_Price (I : Item) return Float is
     (Float (I.Price));

   function Average_Total is new
     Average (T_Range   => Positive,
              T_Element => Item,
              T_Array   => Item_Array,
              To_Float  => Get_Total);

   function Average_Price is new
     Average (T_Range   => Positive,
              T_Element => Item,
              T_Array   => Item_Array,
              To_Float  => Get_Price);

   A : constant Item_Array (1 .. 4)
     := ((Quantity =>  5,   Price => 10.00),
         (Quantity => 80,   Price =>  2.50),
         (Quantity => 40,   Price =>  5.00),
         (Quantity => 20,   Price => 12.50));

begin
   Put ("Average per item & quantity: ");
   F_IO.Put (Average_Total (A), 3, 2, 0);
   New_Line;

   Put ("Average price:               ");
   F_IO.Put (Average_Price (A), 3, 2, 0);
   New_Line;
end Test_Item;
```

Listing 106: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Test_Item;

procedure Main is
   type Test_Case_Index is (Item_Array_Chk);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Item_Array_Chk =>
            Test_Item;
      end case;
   end Check;

begin
```

(continues on next page)

(continued from previous page)

```
18    if Argument_Count < 1 then
19       Put_Line ("ERROR: missing arguments! Exiting...");
20       return;
21    elsif Argument_Count > 1 then
22       Put_Line ("Ignoring additional arguments...");
23    end if;
24
25    Check (Test_Case_Index'Value (Argument (1)));
26 end Main;
```

18.9.4 Generic list

Listing 107: gen_list.ads

```
1  generic
2     type Item is private;
3     type Items is array (Positive range <>) of Item;
4     Name       :        String;
5     List_Array : in out Items;
6     Last       : in out Natural;
7     with procedure Put (I : Item) is <>;
8  package Gen_List is
9
10    procedure Init;
11
12    procedure Add (I      :     Item;
13                   Status : out Boolean);
14
15    procedure Display;
16
17 end Gen_List;
```

Listing 108: gen_list.adb

```
1  with Ada.Text_IO; use Ada.Text_IO;
2
3  package body Gen_List is
4
5     procedure Init is
6     begin
7        Last := List_Array'First - 1;
8     end Init;
9
10    procedure Add (I      :     Item;
11                   Status : out Boolean) is
12    begin
13       Status := Last < List_Array'Last;
14
15       if Status then
16          Last := Last + 1;
17          List_Array (Last) := I;
18       end if;
19    end Add;
20
21    procedure Display is
22    begin
23       Put_Line (Name);
24       for I in List_Array'First .. Last loop
25          Put (List_Array (I));
```

(continues on next page)

(continued from previous page)

```
         New_Line;
      end loop;
   end Display;

end Gen_List;
```

Listing 109: test_int.ads

```
procedure Test_Int;
```

Listing 110: test_int.adb

```
with Ada.Text_IO; use Ada.Text_IO;

with Gen_List;

procedure Test_Int is

   procedure Put (I : Integer) is
   begin
      Ada.Text_IO.Put (Integer'Image (I));
   end Put;

   type Integer_Array is array (Positive range <>) of Integer;

   A : Integer_Array (1 .. 3);
   L : Natural;

   package Int_List is new
     Gen_List (Item          => Integer,
               Items         => Integer_Array,
               Name          => "List of integers",
               List_Array    => A,
               Last          => L);

   Success : Boolean;

   procedure Display_Add_Success (Success : Boolean) is
   begin
      if Success then
         Put_Line ("Added item successfully!");
      else
         Put_Line ("Couldn't add item!");
      end if;

   end Display_Add_Success;

begin
   Int_List.Init;

   Int_List.Add (2, Success);
   Display_Add_Success (Success);

   Int_List.Add (5, Success);
   Display_Add_Success (Success);

   Int_List.Add (7, Success);
   Display_Add_Success (Success);

   Int_List.Add (8, Success);
```

(continues on next page)

(continued from previous page)

```
49    Display_Add_Success (Success);
50
51    Int_List.Display;
52 end Test_Int;
```

Listing 111: main.adb

```
1  with Ada.Command_Line; use Ada.Command_Line;
2  with Ada.Text_IO;      use Ada.Text_IO;
3
4  with Test_Int;
5
6  procedure Main is
7     type Test_Case_Index is (Int_Chk);
8
9     procedure Check (TC : Test_Case_Index) is
10    begin
11       case TC is
12          when Int_Chk =>
13             Test_Int;
14       end case;
15    end Check;
16
17 begin
18    if Argument_Count < 1 then
19       Put_Line ("ERROR: missing arguments! Exiting...");
20       return;
21    elsif Argument_Count > 1 then
22       Put_Line ("Ignoring additional arguments...");
23    end if;
24
25    Check (Test_Case_Index'Value (Argument (1)));
26 end Main;
```

18.10 Exceptions

18.10.1 Uninitialized Value

Listing 112: options.ads

```
1  package Options is
2
3     type Option is (Uninitialized,
4                     Option_1,
5                     Option_2,
6                     Option_3);
7
8     Uninitialized_Value : exception;
9
10    function Image (O : Option) return String;
11
12 end Options;
```

Listing 113: options.adb

```
1  package body Options is
2
3     function Image (O : Option) return String is
```

(continues on next page)

(continued from previous page)

```
   begin
      case O is
         when Uninitialized =>
            raise Uninitialized_Value with "Uninitialized value detected!";
         when others =>
            return Option'Image (O);
      end case;
   end Image;

end Options;
```

Listing 114: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;
with Ada.Exceptions;   use Ada.Exceptions;

with Options;          use Options;

procedure Main is
   type Test_Case_Index is
     (Options_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check (O : Option) is
      begin
         Put_Line (Image (O));
      exception
         when E : Uninitialized_Value =>
            Put_Line (Exception_Message (E));
      end Check;

   begin
      case TC is
      when Options_Chk =>
         for O in Option loop
            Check (O);
         end loop;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.10.2 Numerical Exception

Listing 115: tests.ads

```
package Tests is

```

(continues on next page)

(continued from previous page)

```
   type Test_ID is (Test_1, Test_2);

   Custom_Exception : exception;

   procedure Num_Exception_Test (ID : Test_ID);

end Tests;
```

Listing 116: tests.adb

```
package body Tests is

   pragma Warnings (Off, "variable ""C"" is assigned but never read");

   procedure Num_Exception_Test (ID : Test_ID) is
      A, B, C : Integer;
   begin
      case ID is
         when Test_1 =>
            A := Integer'Last;
            B := Integer'Last;
            C := A + B;
         when Test_2 =>
            raise Custom_Exception with "Custom_Exception raised!";
      end case;
   end Num_Exception_Test;

   pragma Warnings (On, "variable ""C"" is assigned but never read");

end Tests;
```

Listing 117: check_exception.adb

```
with Tests;          use Tests;

with Ada.Text_IO;    use Ada.Text_IO;
with Ada.Exceptions; use Ada.Exceptions;

procedure Check_Exception (ID : Test_ID) is
begin
   Num_Exception_Test (ID);
exception
   when Constraint_Error =>
      Put_Line ("Constraint_Error detected!");
   when E : others =>
      Put_Line (Exception_Message (E));
end Check_Exception;
```

Listing 118: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;
with Ada.Exceptions;   use Ada.Exceptions;

with Tests;            use Tests;
with Check_Exception;

procedure Main is
   type Test_Case_Index is
     (Exception_1_Chk,
```

(continues on next page)

(continued from previous page)

```
      Exception_2_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Handle_Exception (ID : Test_ID) is
      begin
         Check_Exception (ID);
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error"
                      & " (raised by Check_Exception) detected!");
         when E : others =>
            Put_Line (Exception_Name (E)
                      & " (raised by Check_Exception) detected!");
      end Check_Handle_Exception;

   begin
      case TC is
      when Exception_1_Chk =>
         Check_Handle_Exception (Test_1);
      when Exception_2_Chk =>
         Check_Handle_Exception (Test_2);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.10.3 Re-raising Exceptions

Listing 119: tests.ads

```
package Tests is

   type Test_ID is (Test_1, Test_2);

   Custom_Exception, Another_Exception : exception;

   procedure Num_Exception_Test (ID : Test_ID);

end Tests;
```

Listing 120: tests.adb

```
package body Tests is

   pragma Warnings (Off, "variable ""C"" is assigned but never read");

   procedure Num_Exception_Test (ID : Test_ID) is
      A, B, C : Integer;
   begin
```

(continues on next page)

(continued from previous page)

```
      case ID is
         when Test_1 =>
            A := Integer'Last;
            B := Integer'Last;
            C := A + B;
         when Test_2 =>
            raise Custom_Exception with "Custom_Exception raised!";
      end case;
   end Num_Exception_Test;

   pragma Warnings (On, "variable ""C"" is assigned but never read");

end Tests;
```

Listing 121: check_exception.ads

```
with Tests; use Tests;

procedure Check_Exception (ID : Test_ID);
```

Listing 122: check_exception.adb

```
with Ada.Text_IO;    use Ada.Text_IO;
with Ada.Exceptions; use Ada.Exceptions;

procedure Check_Exception (ID : Test_ID) is
begin
   Num_Exception_Test (ID);
exception
   when Constraint_Error =>
      Put_Line ("Constraint_Error detected!");
      raise;
   when E : others =>
      Put_Line (Exception_Message (E));
      raise Another_Exception;
end Check_Exception;
```

Listing 123: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;
with Ada.Exceptions;   use Ada.Exceptions;

with Tests;            use Tests;
with Check_Exception;

procedure Main is
   type Test_Case_Index is
     (Exception_1_Chk,
      Exception_2_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Handle_Exception (ID : Test_ID) is
      begin
         Check_Exception (ID);
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error"
                      & " (raised by Check_Exception) detected!");
```

(continues on next page)

(continued from previous page)

```
         when E : others =>
            Put_Line (Exception_Name (E)
                      & " (raised by Check_Exception) detected!");
      end Check_Handle_Exception;

   begin
      case TC is
      when Exception_1_Chk =>
         Check_Handle_Exception (Test_1);
      when Exception_2_Chk =>
         Check_Handle_Exception (Test_2);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.11 Tasking

18.11.1 Display Service

Listing 124: display_services.ads

```
package Display_Services is

   task type Display_Service is
      entry Display (S : String);
      entry Display (I : Integer);
   end Display_Service;

end Display_Services;
```

Listing 125: display_services.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Display_Services is

   task body Display_Service is
   begin
      loop
         select
            accept Display (S : String) do
               Put_Line (S);
            end Display;
         or
            accept Display (I : Integer) do
               Put_Line (Integer'Image (I));
            end Display;
         or
```

(continues on next page)

(continued from previous page)

```
            terminate;
         end select;
      end loop;
   end Display_Service;

end Display_Services;
```

Listing 126: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Display_Services; use Display_Services;

procedure Main is
   type Test_Case_Index is (Display_Service_Chk);

   procedure Check (TC : Test_Case_Index) is
      Display : Display_Service;
   begin
      case TC is
         when Display_Service_Chk =>
            Display.Display ("Hello");
            delay 0.5;
            Display.Display ("Hello again");
            delay 0.5;
            Display.Display (55);
            delay 0.5;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.11.2 Event Manager

Listing 127: event_managers.ads

```
with Ada.Real_Time; use Ada.Real_Time;

package Event_Managers is

   task type Event_Manager is
      entry Start (ID : Natural);
      entry Event (T : Time);
   end Event_Manager;

end Event_Managers;
```

Listing 128: event_managers.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Event_Managers is

   task body Event_Manager is
      Event_ID    : Natural := 0;
      Event_Delay : Time;
   begin
      accept Start (ID : Natural) do
         Event_ID := ID;
      end Start;

      accept Event (T : Time) do
         Event_Delay := T;
      end Event;

      delay until Event_Delay;

      Put_Line ("Event #" & Natural'Image (Event_ID));
   end Event_Manager;

end Event_Managers;
```

Listing 129: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Event_Managers;   use Event_Managers;
with Ada.Real_Time;    use Ada.Real_Time;

procedure Main is
   type Test_Case_Index is (Event_Manager_Chk);

   procedure Check (TC : Test_Case_Index) is
      Ev_Mng : array (1 .. 5) of Event_Manager;
   begin
      case TC is
         when Event_Manager_Chk =>
            for I in Ev_Mng'Range loop
               Ev_Mng (I).Start (I);
            end loop;
            Ev_Mng (1).Event (Clock + Seconds (5));
            Ev_Mng (2).Event (Clock + Seconds (3));
            Ev_Mng (3).Event (Clock + Seconds (1));
            Ev_Mng (4).Event (Clock + Seconds (2));
            Ev_Mng (5).Event (Clock + Seconds (4));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
```

(continues on next page)

(continued from previous page)

```
35 end Main;
```

18.11.3 Generic Protected Queue

Listing 130: gen_queues.ads

```
1  generic
2     type Queue_Index is mod <>;
3     type T is private;
4  package Gen_Queues is
5
6     type Queue_Array is array (Queue_Index) of T;
7
8     protected type Queue is
9        function Empty return Boolean;
10       function Full return Boolean;
11       entry Push (V : T);
12       entry Pop (V : out T);
13    private
14       N   : Natural     := 0;
15       Idx : Queue_Index := Queue_Array'First;
16       A   : Queue_Array;
17    end Queue;
18
19 end Gen_Queues;
```

Listing 131: gen_queues.adb

```
1  package body Gen_Queues is
2
3     protected body Queue is
4
5        function Empty return Boolean is
6          (N = 0);
7
8        function Full return Boolean is
9           (N = A'Length);
10
11       entry Push (V : T) when not Full is
12       begin
13          A (Idx) := V;
14
15          Idx := Idx + 1;
16          N   := N + 1;
17       end Push;
18
19       entry Pop (V : out T) when not Empty is
20       begin
21          N := N - 1;
22
23          V := A (Idx - Queue_Index (N) - 1);
24       end Pop;
25
26    end Queue;
27
28 end Gen_Queues;
```

Listing 132: queue_tests.ads

```
package Queue_Tests is

   procedure Simple_Test;

   procedure Concurrent_Test;

end Queue_Tests;
```

Listing 133: queue_tests.adb

```
with Ada.Text_IO; use Ada.Text_IO;

with Gen_Queues;

package body Queue_Tests is

   Max : constant := 10;
   type Queue_Mod is mod Max;

   procedure Simple_Test is
      package Queues_Float is new Gen_Queues (Queue_Mod, Float);

      Q_F : Queues_Float.Queue;
      V   : Float;
   begin
      V := 10.0;
      while not Q_F.Full loop
         Q_F.Push (V);
         V := V + 1.5;
      end loop;

      while not Q_F.Empty loop
         Q_F.Pop (V);
         Put_Line ("Value from queue: " & Float'Image (V));
      end loop;
   end Simple_Test;

   procedure Concurrent_Test is
      package Queues_Integer is new Gen_Queues (Queue_Mod, Integer);

      Q_I : Queues_Integer.Queue;

      task T_Producer;
      task T_Consumer;

      task body T_Producer is
         V : Integer := 100;
      begin
         for I in 1 .. 2 * Max loop
            Q_I.Push (V);
            V := V + 1;
         end loop;
      end T_Producer;

      task body T_Consumer is
         V : Integer;
      begin
         delay 1.5;

```

(continues on next page)

(continued from previous page)

```
50          while not Q_I.Empty loop
51             Q_I.Pop (V);
52             Put_Line ("Value from queue: " & Integer'Image (V));
53             delay 0.2;
54          end loop;
55       end T_Consumer;
56    begin
57       null;
58    end Concurrent_Test;
59
60 end Queue_Tests;
```

Listing 134: main.adb

```
1  with Ada.Command_Line; use Ada.Command_Line;
2  with Ada.Text_IO;      use Ada.Text_IO;
3
4  with Queue_Tests;      use Queue_Tests;
5
6  procedure Main is
7     type Test_Case_Index is (Simple_Queue_Chk,
8                              Concurrent_Queue_Chk);
9
10    procedure Check (TC : Test_Case_Index) is
11    begin
12       case TC is
13          when Simple_Queue_Chk =>
14             Simple_Test;
15          when Concurrent_Queue_Chk =>
16             Concurrent_Test;
17       end case;
18    end Check;
19
20 begin
21    if Argument_Count < 1 then
22       Put_Line ("ERROR: missing arguments! Exiting...");
23       return;
24    elsif Argument_Count > 1 then
25       Put_Line ("Ignoring additional arguments...");
26    end if;
27
28    Check (Test_Case_Index'Value (Argument (1)));
29 end Main;
```

18.12 Design by contracts

18.12.1 Price Range

Listing 135: prices.ads

```
1  package Prices is
2
3     type Amount is delta 10.0 ** (-2) digits 12;
4
5     --  subtype Price is Amount range 0.0 .. Amount'Last;
6
7     subtype Price is Amount
8       with Static_Predicate => Price >= 0.0;
```

(continues on next page)

(continued from previous page)

```
9
10 end Prices;
```

Listing 136: main.adb

```
1  with Ada.Command_Line;  use Ada.Command_Line;
2  with Ada.Text_IO;       use Ada.Text_IO;
3  with System.Assertions; use System.Assertions;
4
5  with Prices;            use Prices;
6
7  procedure Main is
8
9     type Test_Case_Index is
10      (Price_Range_Chk);
11
12    procedure Check (TC : Test_Case_Index) is
13
14       procedure Check_Range (A : Amount) is
15          P : constant Price := A;
16       begin
17          Put_Line ("Price: " & Price'Image (P));
18       end Check_Range;
19
20    begin
21       case TC is
22       when Price_Range_Chk =>
23          Check_Range (-2.0);
24       end case;
25    exception
26       when Constraint_Error =>
27          Put_Line ("Constraint_Error detected (NOT as expected).");
28       when Assert_Failure =>
29          Put_Line ("Assert_Failure detected (as expected).");
30    end Check;
31
32 begin
33    if Argument_Count < 1 then
34       Put_Line ("ERROR: missing arguments! Exiting...");
35       return;
36    elsif Argument_Count > 1 then
37       Put_Line ("Ignoring additional arguments...");
38    end if;
39
40    Check (Test_Case_Index'Value (Argument (1)));
41 end Main;
```

18.12.2 Pythagorean Theorem: Predicate

Listing 137: triangles.ads

```
1  package Triangles is
2
3     subtype Length is Integer;
4
5     type Right_Triangle is record
6        H      : Length := 0;
7        --  Hypotenuse
8        C1, C2 : Length := 0;
```

(continues on next page)

(continued from previous page)

```
      --  Catheti / legs
   end record
     with Dynamic_Predicate => H * H = C1 * C1 + C2 * C2;

   function Init (H, C1, C2 : Length) return Right_Triangle is
     ((H, C1, C2));

end Triangles;
```

Listing 138: triangles-io.ads

```
package Triangles.IO is

   function Image (T : Right_Triangle) return String;

end Triangles.IO;
```

Listing 139: triangles-io.adb

```
package body Triangles.IO is

   function Image (T : Right_Triangle) return String is
     ("("    & Length'Image (T.H)
      & ", " & Length'Image (T.C1)
      & ", " & Length'Image (T.C2)
      & ")");

end Triangles.IO;
```

Listing 140: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;
with System.Assertions; use System.Assertions;

with Triangles;         use Triangles;
with Triangles.IO;      use Triangles.IO;

procedure Main is

   type Test_Case_Index is
     (Triangle_8_6_Pass_Chk,
      Triangle_8_6_Fail_Chk,
      Triangle_10_24_Pass_Chk,
      Triangle_10_24_Fail_Chk,
      Triangle_18_24_Pass_Chk,
      Triangle_18_24_Fail_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Triangle (H, C1, C2 : Length) is
         T : Right_Triangle;
      begin
         T := Init (H, C1, C2);
         Put_Line (Image (T));
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error detected (NOT as expected).");
         when Assert_Failure =>
            Put_Line ("Assert_Failure detected (as expected).");
```

(continues on next page)

(continued from previous page)

```
30       end Check_Triangle;
31
32    begin
33       case TC is
34          when Triangle_8_6_Pass_Chk   => Check_Triangle (10,  8,  6);
35          when Triangle_8_6_Fail_Chk   => Check_Triangle (12,  8,  6);
36          when Triangle_10_24_Pass_Chk => Check_Triangle (26, 10, 24);
37          when Triangle_10_24_Fail_Chk => Check_Triangle (12, 10, 24);
38          when Triangle_18_24_Pass_Chk => Check_Triangle (30, 18, 24);
39          when Triangle_18_24_Fail_Chk => Check_Triangle (32, 18, 24);
40       end case;
41    end Check;
42
43 begin
44    if Argument_Count < 1 then
45       Put_Line ("ERROR: missing arguments! Exiting...");
46       return;
47    elsif Argument_Count > 1 then
48       Put_Line ("Ignoring additional arguments...");
49    end if;
50
51    Check (Test_Case_Index'Value (Argument (1)));
52 end Main;
```

18.12.3 Pythagorean Theorem: Precondition

Listing 141: triangles.ads

```
1  package Triangles is
2
3     subtype Length is Integer;
4
5     type Right_Triangle is record
6        H      : Length := 0;
7        --  Hypotenuse
8        C1, C2 : Length := 0;
9        --  Catheti / legs
10    end record;
11
12    function Init (H, C1, C2 : Length) return Right_Triangle is
13      ((H, C1, C2))
14       with Pre => H * H = C1 * C1 + C2 * C2;
15
16 end Triangles;
```

Listing 142: triangles-io.ads

```
1  package Triangles.IO is
2
3     function Image (T : Right_Triangle) return String;
4
5  end Triangles.IO;
```

Listing 143: triangles-io.adb

```
1  package body Triangles.IO is
2
3     function Image (T : Right_Triangle) return String is
4       ("("    & Length'Image (T.H)
```

(continues on next page)

(continued from previous page)

```
      & ", " & Length'Image (T.C1)
      & ", " & Length'Image (T.C2)
      & ")");

end Triangles.IO;
```

Listing 144: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;
with System.Assertions; use System.Assertions;

with Triangles;         use Triangles;
with Triangles.IO;      use Triangles.IO;

procedure Main is

   type Test_Case_Index is
     (Triangle_8_6_Pass_Chk,
      Triangle_8_6_Fail_Chk,
      Triangle_10_24_Pass_Chk,
      Triangle_10_24_Fail_Chk,
      Triangle_18_24_Pass_Chk,
      Triangle_18_24_Fail_Chk);

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Triangle (H, C1, C2 : Length) is
         T : Right_Triangle;
      begin
         T := Init (H, C1, C2);
         Put_Line (Image (T));
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error detected (NOT as expected).");
         when Assert_Failure =>
            Put_Line ("Assert_Failure detected (as expected).");
      end Check_Triangle;

   begin
      case TC is
         when Triangle_8_6_Pass_Chk   => Check_Triangle (10,  8,  6);
         when Triangle_8_6_Fail_Chk   => Check_Triangle (12,  8,  6);
         when Triangle_10_24_Pass_Chk => Check_Triangle (26, 10, 24);
         when Triangle_10_24_Fail_Chk => Check_Triangle (12, 10, 24);
         when Triangle_18_24_Pass_Chk => Check_Triangle (30, 18, 24);
         when Triangle_18_24_Fail_Chk => Check_Triangle (32, 18, 24);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.12.4 Pythagorean Theorem: Postcondition

Listing 145: triangles.ads

```
package Triangles is

   subtype Length is Integer;

   type Right_Triangle is record
      H      : Length := 0;
      --  Hypotenuse
      C1, C2 : Length := 0;
      --  Catheti / legs
   end record;

   function Init (H, C1, C2 : Length) return Right_Triangle is
     ((H, C1, C2))
      with Post => (Init'Result.H * Init'Result.H
                    = Init'Result.C1 * Init'Result.C1
                    + Init'Result.C2 * Init'Result.C2);

end Triangles;
```

Listing 146: triangles-io.ads

```
package Triangles.IO is

   function Image (T : Right_Triangle) return String;

end Triangles.IO;
```

Listing 147: triangles-io.adb

```
package body Triangles.IO is

   function Image (T : Right_Triangle) return String is
     ("("    & Length'Image (T.H)
      & ", " & Length'Image (T.C1)
      & ", " & Length'Image (T.C2)
      & ")");

end Triangles.IO;
```

Listing 148: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;
with System.Assertions; use System.Assertions;

with Triangles;         use Triangles;
with Triangles.IO;      use Triangles.IO;

procedure Main is

   type Test_Case_Index is
     (Triangle_8_6_Pass_Chk,
      Triangle_8_6_Fail_Chk,
      Triangle_10_24_Pass_Chk,
      Triangle_10_24_Fail_Chk,
      Triangle_18_24_Pass_Chk,
      Triangle_18_24_Fail_Chk);
```

(continues on next page)

(continued from previous page)

```

   procedure Check (TC : Test_Case_Index) is

      procedure Check_Triangle (H, C1, C2 : Length) is
         T : Right_Triangle;
      begin
         T := Init (H, C1, C2);
         Put_Line (Image (T));
      exception
         when Constraint_Error =>
            Put_Line ("Constraint_Error detected (NOT as expected).");
         when Assert_Failure =>
            Put_Line ("Assert_Failure detected (as expected).");
      end Check_Triangle;

   begin
      case TC is
         when Triangle_8_6_Pass_Chk   => Check_Triangle (10,  8,  6);
         when Triangle_8_6_Fail_Chk   => Check_Triangle (12,  8,  6);
         when Triangle_10_24_Pass_Chk => Check_Triangle (26, 10, 24);
         when Triangle_10_24_Fail_Chk => Check_Triangle (12, 10, 24);
         when Triangle_18_24_Pass_Chk => Check_Triangle (30, 18, 24);
         when Triangle_18_24_Fail_Chk => Check_Triangle (32, 18, 24);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.12.5 Pythagorean Theorem: Type Invariant

Listing 149: triangles.ads

```
package Triangles is

   subtype Length is Integer;

   type Right_Triangle is private
     with Type_Invariant => Check (Right_Triangle);

   function Check (T : Right_Triangle) return Boolean;

   function Init (H, C1, C2 : Length) return Right_Triangle;

private

   type Right_Triangle is record
      H      : Length := 0;
      --  Hypotenuse
      C1, C2 : Length := 0;
      --  Catheti / legs
   end record;
```

(continues on next page)

(continued from previous page)

```
20
21    function Init (H, C1, C2 : Length) return Right_Triangle is
22      ((H, C1, C2));
23
24    function Check (T : Right_Triangle) return Boolean is
25      (T.H * T.H = T.C1 * T.C1 + T.C2 * T.C2);
26
27 end Triangles;
```

Listing 150: triangles-io.ads

```
1  package Triangles.IO is
2
3     function Image (T : Right_Triangle) return String;
4
5  end Triangles.IO;
```

Listing 151: triangles-io.adb

```
1  package body Triangles.IO is
2
3     function Image (T : Right_Triangle) return String is
4       ("("    & Length'Image (T.H)
5        & ", " & Length'Image (T.C1)
6        & ", " & Length'Image (T.C2)
7        & ")");
8
9  end Triangles.IO;
```

Listing 152: main.adb

```
1  with Ada.Command_Line;  use Ada.Command_Line;
2  with Ada.Text_IO;       use Ada.Text_IO;
3  with System.Assertions; use System.Assertions;
4
5  with Triangles;         use Triangles;
6  with Triangles.IO;      use Triangles.IO;
7
8  procedure Main is
9
10    type Test_Case_Index is
11      (Triangle_8_6_Pass_Chk,
12       Triangle_8_6_Fail_Chk,
13       Triangle_10_24_Pass_Chk,
14       Triangle_10_24_Fail_Chk,
15       Triangle_18_24_Pass_Chk,
16       Triangle_18_24_Fail_Chk);
17
18    procedure Check (TC : Test_Case_Index) is
19
20       procedure Check_Triangle (H, C1, C2 : Length) is
21          T : Right_Triangle;
22       begin
23          T := Init (H, C1, C2);
24          Put_Line (Image (T));
25       exception
26          when Constraint_Error =>
27             Put_Line ("Constraint_Error detected (NOT as expected).");
28          when Assert_Failure =>
29             Put_Line ("Assert_Failure detected (as expected).");
```

(continues on next page)

(continued from previous page)

```
30       end Check_Triangle;
31
32    begin
33       case TC is
34          when Triangle_8_6_Pass_Chk   => Check_Triangle (10,  8,  6);
35          when Triangle_8_6_Fail_Chk   => Check_Triangle (12,  8,  6);
36          when Triangle_10_24_Pass_Chk => Check_Triangle (26, 10, 24);
37          when Triangle_10_24_Fail_Chk => Check_Triangle (12, 10, 24);
38          when Triangle_18_24_Pass_Chk => Check_Triangle (30, 18, 24);
39          when Triangle_18_24_Fail_Chk => Check_Triangle (32, 18, 24);
40       end case;
41    end Check;
42
43 begin
44    if Argument_Count < 1 then
45       Put_Line ("ERROR: missing arguments! Exiting...");
46       return;
47    elsif Argument_Count > 1 then
48       Put_Line ("Ignoring additional arguments...");
49    end if;
50
51    Check (Test_Case_Index'Value (Argument (1)));
52 end Main;
```

18.12.6 Primary Colors

Listing 153: color_types.ads

```
1  package Color_Types is
2
3     type HTML_Color is
4       (Salmon,
5        Firebrick,
6        Red,
7        Darkred,
8        Lime,
9        Forestgreen,
10       Green,
11       Darkgreen,
12       Blue,
13       Mediumblue,
14       Darkblue);
15
16    subtype Int_Color is Integer range 0 .. 255;
17
18    function Image (I : Int_Color) return String;
19
20    type RGB is record
21       Red   : Int_Color;
22       Green : Int_Color;
23       Blue  : Int_Color;
24    end record;
25
26    function To_RGB (C : HTML_Color) return RGB;
27
28    function Image (C : RGB) return String;
29
30    type HTML_Color_RGB_Array is array (HTML_Color) of RGB;
31
32    To_RGB_Lookup_Table : constant HTML_Color_RGB_Array
```

(continues on next page)

(continued from previous page)

```
      := (Salmon      => (16#FA#, 16#80#, 16#72#),
          Firebrick   => (16#B2#, 16#22#, 16#22#),
          Red         => (16#FF#, 16#00#, 16#00#),
          Darkred     => (16#8B#, 16#00#, 16#00#),
          Lime        => (16#00#, 16#FF#, 16#00#),
          Forestgreen => (16#22#, 16#8B#, 16#22#),
          Green       => (16#00#, 16#80#, 16#00#),
          Darkgreen   => (16#00#, 16#64#, 16#00#),
          Blue        => (16#00#, 16#00#, 16#FF#),
          Mediumblue  => (16#00#, 16#00#, 16#CD#),
          Darkblue    => (16#00#, 16#00#, 16#8B#));

   subtype HTML_RGB_Color is HTML_Color
     with Static_Predicate => HTML_RGB_Color in Red | Green | Blue;

   function To_Int_Color (C : HTML_Color;
                          S : HTML_RGB_Color) return Int_Color;
   --  Convert to hexadecimal value for the selected RGB component S

end Color_Types;
```

Listing 154: color_types.adb

```
with Ada.Integer_Text_IO;

package body Color_Types is

   function To_RGB (C : HTML_Color) return RGB is
   begin
      return To_RGB_Lookup_Table (C);
   end To_RGB;

   function To_Int_Color (C : HTML_Color;
                          S : HTML_RGB_Color) return Int_Color is
      C_RGB : constant RGB := To_RGB (C);
   begin
      case S is
         when Red   => return C_RGB.Red;
         when Green => return C_RGB.Green;
         when Blue  => return C_RGB.Blue;
      end case;
   end To_Int_Color;

   function Image (I : Int_Color) return String is
      subtype Str_Range is Integer range 1 .. 10;
      S : String (Str_Range);
   begin
      Ada.Integer_Text_IO.Put (To    => S,
                               Item  => I,
                               Base  => 16);
      return S;
   end Image;

   function Image (C : RGB) return String is
   begin
      return ("(Red => "      & Image (C.Red)
              & ", Green => " & Image (C.Green)
              & ", Blue => "  & Image (C.Blue)
              &")");
   end Image;

```

(continues on next page)

(continued from previous page)

```
39 end Color_Types;
```

Listing 155: main.adb

```
1  with Ada.Command_Line; use Ada.Command_Line;
2  with Ada.Text_IO;      use Ada.Text_IO;
3
4  with Color_Types;      use Color_Types;
5
6  procedure Main is
7     type Test_Case_Index is
8       (HTML_Color_Red_Chk,
9        HTML_Color_Green_Chk,
10       HTML_Color_Blue_Chk);
11
12    procedure Check (TC : Test_Case_Index) is
13
14       procedure Check_HTML_Colors (S : HTML_RGB_Color) is
15       begin
16          Put_Line ("Selected: " & HTML_RGB_Color'Image (S));
17          for I in HTML_Color'Range loop
18             Put_Line (HTML_Color'Image (I) & " => "
19                       & Image (To_Int_Color (I, S)) & ".");
20          end loop;
21       end Check_HTML_Colors;
22
23    begin
24       case TC is
25          when HTML_Color_Red_Chk =>
26             Check_HTML_Colors (Red);
27          when HTML_Color_Green_Chk =>
28             Check_HTML_Colors (Green);
29          when HTML_Color_Blue_Chk =>
30             Check_HTML_Colors (Blue);
31       end case;
32    end Check;
33
34 begin
35    if Argument_Count < 1 then
36       Put_Line ("ERROR: missing arguments! Exiting...");
37       return;
38    elsif Argument_Count > 1 then
39       Put_Line ("Ignoring additional arguments...");
40    end if;
41
42    Check (Test_Case_Index'Value (Argument (1)));
43 end Main;
```

18.13 Object-oriented programming

18.13.1 Simple type extension

Listing 156: type_extensions.ads

```
1  package Type_Extensions is
2
3     type T_Float is tagged record
4        F : Float;
```

(continues on next page)

(continued from previous page)

```
   end record;

   function Init (F : Float) return T_Float;

   function Init (I : Integer) return T_Float;

   function Image (T : T_Float) return String;

   type T_Mixed is new T_Float with record
      I : Integer;
   end record;

   function Init (F : Float) return T_Mixed;

   function Init (I : Integer) return T_Mixed;

   function Image (T : T_Mixed) return String;

end Type_Extensions;
```

Listing 157: type_extensions.adb

```
package body Type_Extensions is

   function Init (F : Float) return T_Float is
   begin
      return ((F => F));
   end Init;

   function Init (I : Integer) return T_Float is
   begin
      return ((F => Float (I)));
   end Init;

   function Init (F : Float) return T_Mixed is
   begin
      return ((F => F,
               I => Integer (F)));
   end Init;

   function Init (I : Integer) return T_Mixed is
   begin
      return ((F => Float (I),
               I => I));
   end Init;

   function Image (T : T_Float) return String is
   begin
      return "{ F => " & Float'Image (T.F) & " }";
   end Image;

   function Image (T : T_Mixed) return String is
   begin
      return "{ F => " & Float'Image (T.F)
        & ", I => " & Integer'Image (T.I) & " }";
   end Image;

end Type_Extensions;
```

Listing 158: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Type_Extensions;  use Type_Extensions;

procedure Main is

   type Test_Case_Index is
     (Type_Extension_Chk);

   procedure Check (TC : Test_Case_Index) is
      F1, F2 : T_Float;
      M1, M2 : T_Mixed;
   begin
      case TC is
      when Type_Extension_Chk =>
         F1 := Init (2.0);
         F2 := Init (3);
         M1 := Init (4.0);
         M2 := Init (5);

         if M2 in T_Float'Class then
           Put_Line ("T_Mixed is in T_Float'Class as expected");
         end if;

         Put_Line ("F1: " & Image (F1));
         Put_Line ("F2: " & Image (F2));
         Put_Line ("M1: " & Image (M1));
         Put_Line ("M2: " & Image (M2));
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.13.2 Online Store

Listing 159: online_store.ads

```
with Ada.Calendar; use Ada.Calendar;

package Online_Store is

   type Amount is delta 10.0**(-2) digits 10;

   subtype Percentage is Amount range 0.0 .. 1.0;

   type Member is tagged record
      Start : Year_Number;
   end record;
```

(continues on next page)

(continued from previous page)

```

   type Member_Access is access Member'Class;

   function Get_Status (M : Member) return String;

   function Get_Price (M : Member;
                       P : Amount) return Amount;

   type Full_Member is new Member with record
      Discount : Percentage;
   end record;

   function Get_Status (M : Full_Member) return String;

   function Get_Price (M : Full_Member;
                       P : Amount) return Amount;

end Online_Store;
```

Listing 160: online_store.adb

```
package body Online_Store is

   function Get_Status (M : Member) return String is
     ("Associate Member");

   function Get_Status (M : Full_Member) return String is
     ("Full Member");

   function Get_Price (M : Member;
                       P : Amount) return Amount is (P);

   function Get_Price (M : Full_Member;
                       P : Amount) return Amount is
     (P * (1.0 - M.Discount));

end Online_Store;
```

Listing 161: online_store-tests.ads

```
package Online_Store.Tests is

   procedure Simple_Test;

end Online_Store.Tests;
```

Listing 162: online_store-tests.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Online_Store.Tests is

   procedure Simple_Test is

      type Member_Due_Amount is record
         Member     : Member_Access;
         Due_Amount : Amount;
      end record;

      function Get_Price (MA : Member_Due_Amount) return Amount is
```

(continues on next page)

(continued from previous page)

```
      begin
         return MA.Member.Get_Price (MA.Due_Amount);
      end Get_Price;

      type Member_Due_Amounts is array (Positive range <>) of Member_Due_Amount;

      DB : constant Member_Due_Amounts (1 .. 4)
        := ((Member     => new Member'(Start => 2010),
             Due_Amount => 250.0),
            (Member     => new Full_Member'(Start    => 1998,
                                            Discount => 0.1),
             Due_Amount => 160.0),
            (Member     => new Full_Member'(Start    => 1987,
                                            Discount => 0.2),
             Due_Amount => 400.0),
            (Member     => new Member'(Start => 2013),
             Due_Amount => 110.0));
   begin
      for I in DB'Range loop
         Put_Line ("Member #" & Positive'Image (I));
         Put_Line ("Status: " & DB (I).Member.Get_Status);
         Put_Line ("Since: " & Year_Number'Image (DB (I).Member.Start));
         Put_Line ("Due Amount: " & Amount'Image (Get_Price (DB (I))));
         Put_Line ("--------");
      end loop;
   end Simple_Test;

end Online_Store.Tests;
```

Listing 163: main.adb

```
with Ada.Command_Line;   use Ada.Command_Line;
with Ada.Text_IO;        use Ada.Text_IO;

with Online_Store;       use Online_Store;
with Online_Store.Tests; use Online_Store.Tests;

procedure Main is

   type Test_Case_Index is
     (Type_Chk,
      Unit_Test_Chk);

   procedure Check (TC : Test_Case_Index) is

      function Result_Image (Result : Boolean) return String is
        (if Result then "OK" else "not OK");

   begin
      case TC is
      when Type_Chk =>
         declare
            AM : constant Member      := (Start    => 2002);
            FM : constant Full_Member := (Start    => 1990,
                                          Discount => 0.2);
         begin
            Put_Line ("Testing Status of Associate Member Type => "
                      & Result_Image (AM.Get_Status = "Associate Member"));
            Put_Line ("Testing Status of Full Member Type => "
                      & Result_Image (FM.Get_Status = "Full Member"));
            Put_Line ("Testing Discount of Associate Member Type => "
```

(continues on next page)

(continued from previous page)

```
                        & Result_Image (AM.Get_Price (100.0) = 100.0));
            Put_Line ("Testing Discount of Full Member Type => "
                        & Result_Image (FM.Get_Price (100.0) = 80.0));
         end;
         when Unit_Test_Chk =>
            Simple_Test;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.14 Standard library: Containers

18.14.1 Simple todo list

Listing 164: todo_lists.ads

```
with Ada.Containers.Vectors;

package Todo_Lists is

   type Todo_Item is access String;

   package Todo_List_Pkg is new Ada.Containers.Vectors
     (Index_Type   => Natural,
      Element_Type => Todo_Item);

   subtype Todo_List is Todo_List_Pkg.Vector;

   procedure Add (Todos : in out Todo_List;
                  Item  : String);

   procedure Display (Todos : Todo_List);

end Todo_Lists;
```

Listing 165: todo_lists.adb

```
with Ada.Text_IO; use Ada.Text_IO;

package body Todo_Lists is

   procedure Add (Todos : in out Todo_List;
                  Item  : String) is
   begin
      Todos.Append (new String'(Item));
   end Add;

   procedure Display (Todos : Todo_List) is
```

(continues on next page)

(continued from previous page)

```
   begin
      Put_Line ("TO-DO LIST");
      for T of Todos loop
         Put_Line (T.all);
      end loop;
   end Display;

end Todo_Lists;
```

Listing 166: main.adb

```
with Ada.Command_Line;  use Ada.Command_Line;
with Ada.Text_IO;       use Ada.Text_IO;

with Todo_Lists;        use Todo_Lists;

procedure Main is
   type Test_Case_Index is
     (Todo_List_Chk);

   procedure Check (TC : Test_Case_Index) is
      T : Todo_List;
   begin
      case TC is
         when Todo_List_Chk =>
            Add (T, "Buy milk");
            Add (T, "Buy tea");
            Add (T, "Buy present");
            Add (T, "Buy tickets");
            Add (T, "Pay electricity bill");
            Add (T, "Schedule dentist appointment");
            Add (T, "Call sister");
            Add (T, "Revise spreasheet");
            Add (T, "Edit entry page");
            Add (T, "Select new design");
            Add (T, "Create upgrade plan");
            Display (T);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.14.2 List of unique integers

Listing 167: ops.ads

```
with Ada.Containers.Ordered_Sets;

package Ops is

```

(continues on next page)

(continued from previous page)

```
   type Int_Array is array (Positive range <>) of Integer;

   package Integer_Sets is new Ada.Containers.Ordered_Sets
     (Element_Type => Integer);

   subtype Int_Set is Integer_Sets.Set;

   function Get_Unique (A : Int_Array) return Int_Set;

   function Get_Unique (A : Int_Array) return Int_Array;

end Ops;
```

Listing 168: ops.adb

```
package body Ops is

   function Get_Unique (A : Int_Array) return Int_Set is
      S : Int_Set;
   begin
      for E of A loop
         S.Include (E);
      end loop;

      return S;
   end Get_Unique;

   function Get_Unique (A : Int_Array) return Int_Array is
      S  : constant Int_Set := Get_Unique (A);
      AR : Int_Array (1 .. Positive (S.Length));
      I  : Positive := 1;
   begin
      for E of S loop
         AR (I) := E;
         I := I + 1;
      end loop;

      return AR;
   end Get_Unique;

end Ops;
```

Listing 169: main.adb

```
with Ada.Command_Line;          use Ada.Command_Line;
with Ada.Text_IO;               use Ada.Text_IO;

with Ops;                       use Ops;

procedure Main is
   type Test_Case_Index is
     (Get_Unique_Set_Chk,
      Get_Unique_Array_Chk);

   procedure Check (TC : Test_Case_Index;
                    A  : Int_Array) is

      procedure Display_Unique_Set (A : Int_Array) is
         S  : constant Int_Set := Get_Unique (A);
      begin
```

(continues on next page)

(continued from previous page)

```
         for E of S loop
            Put_Line (Integer'Image (E));
         end loop;
      end Display_Unique_Set;

      procedure Display_Unique_Array (A : Int_Array) is
         AU : constant Int_Array := Get_Unique (A);
      begin
         for E of AU loop
            Put_Line (Integer'Image (E));
         end loop;
      end Display_Unique_Array;

   begin
      case TC is
         when Get_Unique_Set_Chk   => Display_Unique_Set (A);
         when Get_Unique_Array_Chk => Display_Unique_Array (A);
      end case;
   end Check;

begin
   if Argument_Count < 3 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   else
      declare
         A : Int_Array (1 .. Argument_Count - 1);
      begin
         for I in A'Range loop
            A (I) := Integer'Value (Argument (1 + I));
         end loop;
         Check (Test_Case_Index'Value (Argument (1)), A);
      end;
   end if;
end Main;
```

18.15 Standard library: Dates & Times

18.15.1 Holocene calendar

Listing 170: to_holocene_year.adb

```
with Ada.Calendar; use Ada.Calendar;

function To_Holocene_Year (T : Time) return Integer is
begin
   return Year (T) + 10_000;
end To_Holocene_Year;
```

Listing 171: main.adb

```
with Ada.Command_Line;        use Ada.Command_Line;
with Ada.Text_IO;             use Ada.Text_IO;
with Ada.Calendar;            use Ada.Calendar;

with To_Holocene_Year;

procedure Main is
```

(continues on next page)

(continued from previous page)

```
   type Test_Case_Index is
     (Holocene_Chk);

   procedure Display_Holocene_Year (Y : Year_Number) is
      HY : Integer;
   begin
      HY := To_Holocene_Year (Time_Of (Y, 1, 1));
      Put_Line ("Year (Gregorian): " & Year_Number'Image (Y));
      Put_Line ("Year (Holocene):  " & Integer'Image (HY));
   end Display_Holocene_Year;

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Holocene_Chk =>
            Display_Holocene_Year (2012);
            Display_Holocene_Year (2020);
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.15.2 List of events

Listing 172: events.ads

```
with Ada.Containers.Vectors;

package Events is

   type Event_Item is access String;

   package Event_Item_Containers is new
     Ada.Containers.Vectors
       (Index_Type   => Positive,
        Element_Type => Event_Item);

   subtype Event_Items is Event_Item_Containers.Vector;

end Events;
```

Listing 173: events-lists.ads

```
with Ada.Calendar;                use Ada.Calendar;
with Ada.Containers.Ordered_Maps;

package Events.Lists is

   type Event_List is tagged private;

```

(continues on next page)

(continued from previous page)

```
   procedure Add (Events     : in out Event_List;
                  Event_Time :        Time;
                  Event      :        String);

   procedure Display (Events : Event_List);

private

   package Event_Time_Item_Containers is new
     Ada.Containers.Ordered_Maps
       (Key_Type         => Time,
        Element_Type     => Event_Items,
        "="              => Event_Item_Containers."=");

   type Event_List is new Event_Time_Item_Containers.Map with null record;

end Events.Lists;
```

Listing 174: events-lists.adb

```
with Ada.Text_IO;             use Ada.Text_IO;
with Ada.Calendar.Formatting; use Ada.Calendar.Formatting;

package body Events.Lists is

   procedure Add (Events     : in out Event_List;
                  Event_Time : Time;
                  Event      : String) is
      use Event_Item_Containers;
      E : constant Event_Item := new String'(Event);
   begin
      if not Events.Contains (Event_Time) then
         Events.Include (Event_Time, Empty_Vector);
      end if;
      Events (Event_Time).Append (E);
   end Add;

   function Date_Image (T : Time) return String is
      Date_Img : constant String := Image (T);
   begin
      return Date_Img (1 .. 10);
   end;

   procedure Display (Events : Event_List) is
      use Event_Time_Item_Containers;
      T : Time;
   begin
      Put_Line ("EVENTS LIST");
      for C in Events.Iterate loop
         T := Key (C);
         Put_Line ("- " & Date_Image (T));
         for I of Events (C) loop
            Put_Line ("    - " & I.all);
         end loop;
      end loop;
   end Display;

end Events.Lists;
```

Listing 175: main.adb

```
with Ada.Command_Line;         use Ada.Command_Line;
with Ada.Text_IO;              use Ada.Text_IO;
with Ada.Calendar;
with Ada.Calendar.Formatting; use Ada.Calendar.Formatting;

with Events.Lists;             use Events.Lists;

procedure Main is
   type Test_Case_Index is
     (Event_List_Chk);

   procedure Check (TC : Test_Case_Index) is
      EL : Event_List;
   begin
      case TC is
         when Event_List_Chk =>
            EL.Add (Time_Of (2018, 2, 16),
                    "Final check");
            EL.Add (Time_Of (2018, 2, 16),
                    "Release");
            EL.Add (Time_Of (2018, 12, 3),
                    "Brother's birthday");
            EL.Add (Time_Of (2018, 1, 1),
                    "New Year's Day");
            EL.Display;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.16 Standard library: Strings

18.16.1 Concatenation

Listing 176: str_concat.ads

```
with Ada.Strings.Unbounded; use Ada.Strings.Unbounded;

package Str_Concat is

   type Unbounded_Strings is array (Positive range <>) of Unbounded_String;

   function Concat (USA            : Unbounded_Strings;
                    Trim_Str       : Boolean;
                    Add_Whitespace : Boolean) return Unbounded_String;

   function Concat (USA            : Unbounded_Strings;
                    Trim_Str       : Boolean;
```

(continues on next page)

(continued from previous page)

```
                    Add_Whitespace : Boolean) return String;

end Str_Concat;
```

Listing 177: str_concat.adb

```
with Ada.Strings; use Ada.Strings;

package body Str_Concat is

   function Concat (USA            : Unbounded_Strings;
                    Trim_Str       : Boolean;
                    Add_Whitespace : Boolean) return Unbounded_String is

      function Retrieve (USA        : Unbounded_Strings;
                         Trim_Str   : Boolean;
                         Index      : Positive) return Unbounded_String is
         US_Internal : Unbounded_String := USA (Index);
      begin
         if Trim_Str then
            US_Internal := Trim (US_Internal, Both);
         end if;
         return US_Internal;
      end Retrieve;

      US : Unbounded_String := To_Unbounded_String ("");
   begin
      for I in USA'First .. USA'Last - 1 loop
         US := US & Retrieve (USA, Trim_Str, I);
         if Add_Whitespace then
            US := US & " ";
         end if;
      end loop;
      US := US & Retrieve (USA, Trim_Str, USA'Last);

      return US;
   end Concat;

   function Concat (USA            : Unbounded_Strings;
                    Trim_Str       : Boolean;
                    Add_Whitespace : Boolean) return String is
   begin
      return To_String (Concat (USA, Trim_Str, Add_Whitespace));
   end Concat;

end Str_Concat;
```

Listing 178: main.adb

```
with Ada.Command_Line;        use Ada.Command_Line;
with Ada.Text_IO;             use Ada.Text_IO;
with Ada.Strings.Unbounded;   use Ada.Strings.Unbounded;

with Str_Concat;              use Str_Concat;

procedure Main is
   type Test_Case_Index is
     (Unbounded_Concat_No_Trim_No_WS_Chk,
      Unbounded_Concat_Trim_No_WS_Chk,
      String_Concat_Trim_WS_Chk,
```

(continues on next page)

(continued from previous page)

```
      Concat_Single_Element);

   procedure Check (TC : Test_Case_Index) is
   begin
      case TC is
         when Unbounded_Concat_No_Trim_No_WS_Chk =>
            declare
               S : constant Unbounded_Strings := (
                  To_Unbounded_String ("Hello"),
                  To_Unbounded_String (" World"),
                  To_Unbounded_String ("!"));
            begin
               Put_Line (To_String (Concat (S, False, False)));
            end;
         when Unbounded_Concat_Trim_No_WS_Chk =>
            declare
               S : constant Unbounded_Strings := (
                  To_Unbounded_String (" This "),
                  To_Unbounded_String (" _is_ "),
                  To_Unbounded_String ("  a   "),
                  To_Unbounded_String (" _check "));
            begin
               Put_Line (To_String (Concat (S, True, False)));
            end;
         when String_Concat_Trim_WS_Chk =>
            declare
               S : constant Unbounded_Strings := (
                   To_Unbounded_String ("  This  "),
                   To_Unbounded_String ("  is a  "),
                   To_Unbounded_String ("  test.  "));
            begin
               Put_Line (Concat (S, True, True));
            end;
         when Concat_Single_Element =>
            declare
               S : constant Unbounded_Strings := (
                   1 => To_Unbounded_String ("  Hi "));
            begin
               Put_Line (Concat (S, True, True));
            end;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.16.2 List of events

Listing 179: events.ads

```
with Ada.Strings.Unbounded;  use Ada.Strings.Unbounded;
with Ada.Containers.Vectors;
```

(continues on next page)

(continued from previous page)

```
3
4  package Events is
5
6     subtype Event_Item is Unbounded_String;
7
8     package Event_Item_Containers is new
9       Ada.Containers.Vectors
10        (Index_Type   => Positive,
11         Element_Type => Event_Item);
12
13    subtype Event_Items is Event_Item_Containers.Vector;
14
15 end Events;
```

Listing 180: events-lists.ads

```
1  with Ada.Calendar;                use Ada.Calendar;
2  with Ada.Containers.Ordered_Maps;
3
4  package Events.Lists is
5
6     type Event_List is tagged private;
7
8     procedure Add (Events     : in out Event_List;
9                    Event_Time :        Time;
10                   Event      :        String);
11
12    procedure Display (Events : Event_List);
13
14 private
15
16    package Event_Time_Item_Containers is new
17      Ada.Containers.Ordered_Maps
18        (Key_Type         => Time,
19         Element_Type     => Event_Items,
20         "="              => Event_Item_Containers."=");
21
22    type Event_List is new Event_Time_Item_Containers.Map with null record;
23
24 end Events.Lists;
```

Listing 181: events-lists.adb

```
1  with Ada.Text_IO;              use Ada.Text_IO;
2  with Ada.Calendar.Formatting; use Ada.Calendar.Formatting;
3
4  package body Events.Lists is
5
6     procedure Add (Events     : in out Event_List;
7                    Event_Time : Time;
8                    Event      : String) is
9        use Event_Item_Containers;
10       E : constant Event_Item := To_Unbounded_String (Event);
11    begin
12       if not Events.Contains (Event_Time) then
13          Events.Include (Event_Time, Empty_Vector);
14       end if;
15       Events (Event_Time).Append (E);
16    end Add;
17
```

(continues on next page)

(continued from previous page)

```
   function Date_Image (T : Time) return String is
      Date_Img : constant String := Image (T);
   begin
      return Date_Img (1 .. 10);
   end;

   procedure Display (Events : Event_List) is
      use Event_Time_Item_Containers;
      T : Time;
   begin
      Put_Line ("EVENTS LIST");
      for C in Events.Iterate loop
         T := Key (C);
         Put_Line ("- " & Date_Image (T));
         for I of Events (C) loop
            Put_Line ("    - " & To_String (I));
         end loop;
      end loop;
   end Display;

end Events.Lists;
```

Listing 182: main.adb

```
with Ada.Command_Line;        use Ada.Command_Line;
with Ada.Text_IO;             use Ada.Text_IO;
with Ada.Calendar;
with Ada.Calendar.Formatting; use Ada.Calendar.Formatting;
with Ada.Strings.Unbounded;   use Ada.Strings.Unbounded;

with Events;
with Events.Lists;            use Events.Lists;

procedure Main is
   type Test_Case_Index is
     (Unbounded_String_Chk,
      Event_List_Chk);

   procedure Check (TC : Test_Case_Index) is
      EL : Event_List;
   begin
      case TC is
         when Unbounded_String_Chk =>
            declare
               S : constant Events.Event_Item := To_Unbounded_String ("Checked");
            begin
               Put_Line (To_String (S));
            end;
         when Event_List_Chk =>
            EL.Add (Time_Of (2018, 2, 16),
                    "Final check");
            EL.Add (Time_Of (2018, 2, 16),
                    "Release");
            EL.Add (Time_Of (2018, 12, 3),
                    "Brother's birthday");
            EL.Add (Time_Of (2018, 1, 1),
                    "New Year's Day");
            EL.Display;
      end case;
   end Check;

```

(continues on next page)

(continued from previous page)

```
begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.17 Standard library: Numerics

18.17.1 Decibel Factor

Listing 183: decibels.ads

```
package Decibels is

   subtype Decibel is Float;
   subtype Factor  is Float;

   function To_Decibel (F : Factor) return Decibel;

   function To_Factor (D : Decibel) return Factor;

end Decibels;
```

Listing 184: decibels.adb

```
with Ada.Numerics.Elementary_Functions; use Ada.Numerics.Elementary_Functions;

package body Decibels is

   function To_Decibel (F : Factor) return Decibel is
   begin
      return 20.0 * Log (F, 10.0);
   end To_Decibel;

   function To_Factor (D : Decibel) return Factor is
   begin
      return 10.0 ** (D / 20.0);
   end To_Factor;

end Decibels;
```

Listing 185: main.adb

```
with Ada.Command_Line; use Ada.Command_Line;
with Ada.Text_IO;      use Ada.Text_IO;

with Decibels;         use Decibels;

procedure Main is
   type Test_Case_Index is
     (Db_Chk,
      Factor_Chk);

```

(continues on next page)

(continued from previous page)

```
   procedure Check (TC : Test_Case_Index; V : Float) is

      package F_IO is new Ada.Text_IO.Float_IO (Factor);
      package D_IO is new Ada.Text_IO.Float_IO (Decibel);

      procedure Put_Decibel_Cnvt (D : Decibel) is
         F : constant Factor := To_Factor (D);
      begin
         D_IO.Put (D, 0, 2, 0);
         Put (" dB => Factor of ");
         F_IO.Put (F, 0, 2, 0);
         New_Line;
      end;

      procedure Put_Factor_Cnvt (F : Factor) is
         D : constant Decibel := To_Decibel (F);
      begin
         Put ("Factor of ");
         F_IO.Put (F, 0, 2, 0);
         Put (" => ");
         D_IO.Put (D, 0, 2, 0);
         Put_Line (" dB");
      end;
   begin
      case TC is
         when Db_Chk =>
            Put_Decibel_Cnvt (Decibel (V));
         when Factor_Chk =>
            Put_Factor_Cnvt (Factor (V));
      end case;
   end Check;

begin
   if Argument_Count < 2 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 2 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)), Float'Value (Argument (2)));
end Main;
```

18.17.2 Root-Mean-Square

Listing 186: signals.ads

```
package Signals is

   subtype Sig_Value is Float;

   type Signal is array (Natural range <>) of Sig_Value;

   function Rms (S : Signal) return Sig_Value;

end Signals;
```

Listing 187: signals.adb

```
with Ada.Numerics.Elementary_Functions; use Ada.Numerics.Elementary_Functions;

package body Signals is

   function Rms (S : Signal) return Sig_Value is
      Acc : Float := 0.0;
   begin
      for V of S loop
         Acc := Acc + V * V;
      end loop;

      return Sqrt (Acc / Float (S'Length));
   end;

end Signals;
```

Listing 188: signals-std.ads

```
package Signals.Std is

   Sample_Rate : Float := 8000.0;

   function Generate_Sine (N : Positive; Freq : Float) return Signal;

   function Generate_Square (N : Positive) return Signal;

   function Generate_Triangular (N : Positive) return Signal;

end Signals.Std;
```

Listing 189: signals-std.adb

```
with Ada.Numerics;                      use Ada.Numerics;
with Ada.Numerics.Elementary_Functions; use Ada.Numerics.Elementary_Functions;

package body Signals.Std is

   function Generate_Sine (N : Positive; Freq : Float) return Signal is
      S : Signal (0 .. N - 1);
   begin
      for I in S'First .. S'Last loop
         S (I) := 1.0 * Sin (2.0 * Pi * (Freq * Float (I) / Sample_Rate));
      end loop;

      return S;
   end;

   function Generate_Square (N : Positive) return Signal is
      S : constant Signal (0 .. N - 1) := (others => 1.0);
   begin
      return S;
   end;

   function Generate_Triangular (N : Positive) return Signal is
      S      : Signal (0 .. N - 1);
      S_Half : constant Natural := S'Last / 2;
   begin
      for I in S'First .. S_Half loop
         S (I) := 1.0 * (Float (I) / Float (S_Half));
```

(continues on next page)

(continued from previous page)

```
      end loop;
      for I in S_Half .. S'Last loop
         S (I) := 1.0 - (1.0 * (Float (I - S_Half) / Float (S_Half)));
      end loop;

      return S;
   end;

end Signals.Std;
```

Listing 190: main.adb

```
with Ada.Command_Line;        use Ada.Command_Line;
with Ada.Text_IO;             use Ada.Text_IO;

with Signals;                 use Signals;
with Signals.Std;             use Signals.Std;

procedure Main is
   type Test_Case_Index is
     (Sine_Signal_Chk,
      Square_Signal_Chk,
      Triangular_Signal_Chk);

   procedure Check (TC : Test_Case_Index) is
      package Sig_IO is new Ada.Text_IO.Float_IO (Sig_Value);

      N    : constant Positive := 1024;
      S_Si : constant Signal := Generate_Sine (N, 440.0);
      S_Sq : constant Signal := Generate_Square (N);
      S_Tr : constant Signal := Generate_Triangular (N + 1);
   begin
      case TC is
         when Sine_Signal_Chk =>
            Put ("RMS of Sine Signal: ");
            Sig_IO.Put (Rms (S_Si), 0, 2, 0);
            New_Line;
         when Square_Signal_Chk =>
            Put ("RMS of Square Signal: ");
            Sig_IO.Put (Rms (S_Sq), 0, 2, 0);
            New_Line;
         when Triangular_Signal_Chk =>
            Put ("RMS of Triangular Signal: ");
            Sig_IO.Put (Rms (S_Tr), 0, 2, 0);
            New_Line;
      end case;
   end Check;

begin
   if Argument_Count < 1 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 1 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)));
end Main;
```

18.17.3 Rotation

Listing 191: rotation.ads

```
with Ada.Numerics.Complex_Types;
use  Ada.Numerics.Complex_Types;

package Rotation is

   type Complex_Points is array (Positive range <>) of Complex;

   function Rotation (N : Positive) return Complex_Points;

end Rotation;
```

Listing 192: rotation.adb

```
with Ada.Numerics; use Ada.Numerics;

package body Rotation is

   function Rotation (N : Positive) return Complex_Points is
      C_Angle : constant Complex :=
                  Compose_From_Polar (1.0, 2.0 * Pi / Float (N));
   begin
      return C : Complex_Points (1 .. N + 1) do
         C (1) := Compose_From_Cartesian (1.0, 0.0);

         for I in C'First + 1 .. C'Last loop
            C (I) := C (I - 1) * C_Angle;
         end loop;
      end return;
   end;

end Rotation;
```

Listing 193: angles.ads

```
with Rotation; use Rotation;

package Angles is

   subtype Angle is Float;

   type Angles is array (Positive range <>) of Angle;

   function To_Angles (C : Complex_Points) return Angles;

end Angles;
```

Listing 194: angles.adb

```
with Ada.Numerics;                use Ada.Numerics;
with Ada.Numerics.Complex_Types; use Ada.Numerics.Complex_Types;

package body Angles is

   function To_Angles (C : Complex_Points) return Angles is
   begin
      return A : Angles (C'Range) do
         for I in A'Range loop
```

(continues on next page)

(continued from previous page)

```
            A (I) := Argument (C (I)) / Pi * 180.0;
         end loop;
      end return;
   end To_Angles;

end Angles;
```

Listing 195: rotation-tests.ads

```
package Rotation.Tests is

   procedure Test_Rotation (N : Positive);

   procedure Test_Angles (N : Positive);

end Rotation.Tests;
```

Listing 196: rotation-tests.adb

```
with Ada.Text_IO;            use Ada.Text_IO;
with Ada.Text_IO.Complex_IO;
with Ada.Numerics;           use Ada.Numerics;

with Angles;                 use Angles;

package body Rotation.Tests is

   package C_IO is new Ada.Text_IO.Complex_IO (Complex_Types);
   package F_IO is new Ada.Text_IO.Float_IO (Float);

   --
   --  Adapt value due to floating-point inaccuracies
   --

   function Adapt (C : Complex) return Complex is
      function Check_Zero (F : Float) return Float is
        (if F <= 0.0 and F >= -0.01 then 0.0 else F);
   begin
      return C_Out : Complex := C do
         C_Out.Re := Check_Zero (C_Out.Re);
         C_Out.Im := Check_Zero (C_Out.Im);
      end return;
   end Adapt;

   function Adapt (A : Angle) return Angle is
     (if A <= -179.99 and A >= -180.01 then 180.0 else A);

   procedure Test_Rotation (N : Positive) is
      C : constant Complex_Points := Rotation (N);
   begin
      Put_Line ("---- Points for " & Positive'Image (N) & " slices ----");
      for V of C loop
         Put ("Point: ");
         C_IO.Put (Adapt (V), 0, 1, 0);
         New_Line;
      end loop;
   end Test_Rotation;

   procedure Test_Angles (N : Positive) is
      C : constant Complex_Points := Rotation (N);
```

(continues on next page)

(continued from previous page)

```
      A : constant Angles.Angles  := To_Angles (C);
   begin
      Put_Line ("---- Angles for " & Positive'Image (N) & " slices ----");
      for V of A loop
         Put ("Angle: ");
         F_IO.Put (Adapt (V), 0, 2, 0);
         Put_Line (" degrees");
      end loop;
   end Test_Angles;

end Rotation.Tests;
```

Listing 197: main.adb

```
with Ada.Command_Line;          use Ada.Command_Line;
with Ada.Text_IO;               use Ada.Text_IO;

with Rotation.Tests;            use Rotation.Tests;

procedure Main is
   type Test_Case_Index is
     (Rotation_Chk,
      Angles_Chk);

   procedure Check (TC : Test_Case_Index; N : Positive) is
   begin
      case TC is
         when Rotation_Chk =>
            Test_Rotation (N);
         when Angles_Chk =>
            Test_Angles (N);
      end case;
   end Check;

begin
   if Argument_Count < 2 then
      Put_Line ("ERROR: missing arguments! Exiting...");
      return;
   elsif Argument_Count > 2 then
      Put_Line ("Ignoring additional arguments...");
   end if;

   Check (Test_Case_Index'Value (Argument (1)), Positive'Value (Argument (2)));
end Main;
```